

Package ‘metaSEM’

August 9, 2023

Type Package

Title Meta-Analysis using Structural Equation Modeling

Version 1.3.1

Date 2023-08-08

Depends R (>= 3.4.0), OpenMx

Imports Matrix, MASS, ellipse, graphics, stats, utils, mvtnorm,
numDeriv, lavaan

Suggests metafor, semPlot, R.rsp, testthat, matrixcalc

VignetteBuilder R.rsp

Maintainer Mike Cheung <mikewlcheung@nus.edu.sg>

Description A collection of functions for conducting meta-analysis using a structural equation modeling (SEM) approach via the 'OpenMx' and 'lavaan' packages. It also implements various procedures to perform meta-analytic structural equation modeling on the correlation and covariance matrices, see Cheung (2015) <[doi:10.3389/fpsyg.2014.01521](https://doi.org/10.3389/fpsyg.2014.01521)>.

License GPL (>= 2)

LazyLoad yes

LazyData yes

ByteCompile yes

URL <https://github.com/mikewlcheung/metasem>

BugReports <https://github.com/mikewlcheung/metasem/issues>

NeedsCompilation no

Author Mike Cheung [aut, cre] (<<https://orcid.org/0000-0003-0113-0758>>)

Repository CRAN

Date/Publication 2023-08-09 18:50:02 UTC

R topics documented:

| | |
|------------------|----|
| metaSEM-package | 4 |
| Aloe14 | 5 |
| anova | 7 |
| as.mxAlgebra | 8 |
| as.mxMatrix | 10 |
| as.symMatrix | 12 |
| asyCov | 13 |
| BCG | 15 |
| bdiagMat | 16 |
| bdiagRep | 17 |
| Becker09 | 18 |
| Becker83 | 22 |
| Becker92 | 23 |
| Becker94 | 25 |
| Berkey98 | 27 |
| Boer16 | 29 |
| bootuniR1 | 30 |
| bootuniR2 | 31 |
| Bornmann07 | 32 |
| calEffSizes | 34 |
| checkRAM | 36 |
| Cheung00 | 37 |
| Cheung09 | 39 |
| coef | 40 |
| Cooke16 | 42 |
| Cooper03 | 44 |
| Cor2DataFrame | 45 |
| create.Fmatrix | 47 |
| create.modMatrix | 48 |
| create.mxMatrix | 49 |
| create.mxModel | 50 |
| create.Tau2 | 52 |
| create.V | 53 |
| create.vechsR | 54 |
| Diag | 56 |
| Digman97 | 57 |
| Gleser94 | 60 |
| Gnambs18 | 61 |
| HedgesOlkin85 | 62 |
| homoStat | 63 |
| Hox02 | 65 |
| Hunter83 | 66 |
| impliedR | 69 |
| indirectEffect | 72 |
| is.pd | 73 |
| issp05 | 74 |

| | |
|------------------------|-----|
| issp89 | 76 |
| Jaramillo05 | 78 |
| Kalaian96 | 79 |
| lavaan2RAM | 80 |
| list2matrix | 82 |
| Mak09 | 83 |
| Mathieu15 | 84 |
| matrix2bdiag | 86 |
| meta | 88 |
| meta2semPlot | 91 |
| meta3L | 92 |
| Nam03 | 95 |
| Nohe15 | 96 |
| Norton13 | 99 |
| osmasem | 100 |
| osmasemR2 | 102 |
| osmasemSRMR | 103 |
| pattern.n | 103 |
| pattern.na | 104 |
| plot | 105 |
| print | 109 |
| rCor | 110 |
| readData | 111 |
| reml | 113 |
| reml3L | 116 |
| rerun | 118 |
| Roorda11 | 119 |
| Scalco17 | 120 |
| smdMES | 121 |
| smdMTS | 123 |
| Stadler15 | 125 |
| summary | 126 |
| Tenenbaum02 | 128 |
| tssem1 | 129 |
| tssemParaVar | 131 |
| uniR1 | 132 |
| uniR2 | 133 |
| vanderPol17 | 135 |
| VarCorr | 136 |
| vcov | 137 |
| vec2symMat | 138 |
| wls | 139 |
| wvs94a | 144 |
| wvs94b | 146 |

metaSEM-package

*Meta-Analysis using Structural Equation Modeling***Description**

A collection of functions for conducting meta-analysis using a structural equation modeling (SEM) approach via the 'OpenMx' and 'lavaan' packages. It also implements various procedures to perform meta-analytic structural equation modeling on the correlation and covariance matrices.

Details

Package: metaSEM
 Type: Package
 Version: 1.3.1
 Date: 2023-08-08
 License: GPL (>=2)
 LazyLoad: yes

Author(s)

Mike W.-L. Cheung <mikewlcheung@nus.edu.sg>

Maintainer: Mike W.-L. Cheung <mikewlcheung@nus.edu.sg>

References

- Cheung, M. W.-L. (2008). A model for integrating fixed-, random-, and mixed-effects meta-analyses into structural equation modeling. *Psychological Methods*, **13** (3), 182-202. <https://doi.org/10.1037/a0013163>
- Cheung, M. W.-L. (2009). Constructing approximate confidence intervals for parameters with structural equation models. *Structural Equation Modeling*, **16** (2), 267-294. <https://doi.org/10.1080/10705510902751291>
- Cheung, M. W.-L. (2010). Fixed-effects meta-analyses as multiple-group structural equation models. *Structural Equation Modeling*, **17** (3), 481-509. <https://doi.org/10.1080/10705511.2010.489367>
- Cheung, M. W.-L. (2013). Implementing restricted maximum likelihood estimation in structural equation models. *Structural Equation Modeling*, **20** (1), 157-167. <https://doi.org/10.1080/10705511.2013.742404>
- Cheung, M. W.-L. (2013). Multivariate meta-analysis as structural equation models. *Structural Equation Modeling*, **20** (3), 429-454. <https://doi.org/10.1080/10705511.2013.797827>
- Cheung, M. W.-L. (2014). Modeling dependent effect sizes with three-level meta-analyses: A structural equation modeling approach. *Psychological Methods*, **19** (2), 211-229. <https://doi.org/10.1037/a0032968>
- Cheung, M. W.-L. (2014). Fixed- and random-effects meta-analytic structural equation modeling: Examples and analyses in R. *Behavior Research Methods*, **46** (1), 29-40. <https://doi.org/10.3758/s13428-013-0361-y>

- Cheung, M. W.-L. (2015). metaSEM: An R package for meta-analysis using structural equation modeling. *Frontiers in Psychology*, *5* (1521). <https://doi.org/10.3389/fpsyg.2014.01521>
- Cheung, M. W.-L. (2015). *Meta-Analysis: A Structural Equation Modeling Approach*. Chichester, West Sussex: John Wiley & Sons, Inc.
- Cheung, M. W.-L. (2018). Issues in solving the problem of effect size heterogeneity in meta-analytic structural equation modeling: A commentary and simulation study on Yu, Downes, Carter, and O'Boyle (2016). *Journal of Applied Psychology*, *103* (7), 787-803. <https://doi.org/10.1037/apl0000284>
- Cheung, M. W.-L. (2018). Computing multivariate effect sizes and their sampling covariance matrices with structural equation modeling: Theory, examples, and computer simulations. *Frontiers in Psychology*, *9* (1387). <https://doi.org/10.3389/fpsyg.2018.01387>
- Cheung, M. W.-L. (2019). Some reflections on combining meta-analysis and structural equation modeling. *Research Synthesis Methods*, *10* (1), 15-22. <https://doi.org/10.1002/jrsm.1321>
- Cheung, M. W.-L. (2021). Meta-analytic structural equation modeling. In *Oxford Research Encyclopedia of Business and Management*. Oxford University Press. <https://doi.org/10.1093/acrefore/9780190224851.013.225>
- Cheung, M. W.-L., & Chan, W. (2004). Testing dependent correlation coefficients via structural equation modeling. *Organizational Research Methods*, *7* (2), 206-223. <https://doi.org/10.1177/1094428104264024>
- Cheung, M. W.-L., & Chan, W. (2005). Meta-analytic structural equation modeling: A two-stage approach. *Psychological Methods*, *10* (1), 40-64. <https://doi.org/10.1037/1082-989X.10.1.40>
- Cheung, M. W.-L., & Chan, W. (2009). A two-stage approach to synthesizing covariance matrices in meta-analytic structural equation modeling. *Structural Equation Modeling*, *16* (1), 28-53. <https://doi.org/10.1080/10705510802561295>
- Cheung, M. W.-L., & Cheung, S.-F. (2016). Random-effects models for meta-analytic structural equation modeling: Review, issues, and illustrations. *Research Synthesis Methods*, *7* (2), 140-155. <https://doi.org/10.1002/jrsm.1166>
- Jak, S., & Cheung, M. W.-L. (2018). Testing moderator hypotheses in meta-analytic structural equation modeling using subgroup analysis. *Behavior Research Methods*, *50* (4), 1359-1373. <https://doi.org/10.3758/s13428-018-1046-3>
- Jak, S., & Cheung, M. W.-L. (2020). Meta-analytic structural equation modeling with moderating effects on SEM parameters. *Psychological Methods*, *25* (4), 430-455. <https://doi.org/10.1037/met0000245>

Aloe14

Multivariate effect sizes between classroom management self-efficacy (CMSE) and other variables reported by Aloe et al. (2014)

Description

This study reports sixteen studies on the effect sizes (correlation coefficients) between CMSE and emotional exhaustion (EE), depersonalization (DP), and (lowered) personal accomplishment (PA) reported by Aloe et al. (2014).

Usage

```
data("Aloe14")
```

Format

A data frame with 16 observations on the following 14 variables.

Study a factor with levels Betoret Brouwers & Tomic Bumen Chang Durr Evers et al. Friedman
Gold Huk Kress Kumarakulasingam Martin et al. Ozdemir Skaalvik and Skaalvik Williams

Year Year of publication

EE Emotional exhaustion

DP Depersonalization

PA (Lowered) personal accomplishment

V_EE Sampling variance of emotional exhaustion

V_DP Sampling variance of depersonalization

V_PA Sampling variance of (lowered) personal accomplishment

C_EE_DP Sampling covariance between EE and DP

C_EE_PA Sampling covariance between EE and PA

C_DP_PA Sampling covariance between DP and PA

Publication_type Either Dissertation or Journal

Percentage_females Percentage of females in the study

Years_experience Average years of experience

Source

Aloe, A. M., Amo, L. C., & Shanahan, M. E. (2014). Classroom management self-efficacy and burnout: A multivariate meta-analysis. *Educational Psychology Review*, **26(1)**, 101-126. doi:10.1007/s10648-013-9244-0

Examples

```
## Not run:
data(Aloe14)

## Random-effects meta-analysis
meta1 <- meta(cbind(EE,DP,PA),
             cbind(V_EE, C_EE_DP, C_EE_PA, V_DP, C_DP_PA, V_PA),
             data=Aloe14)
## Remove error code
meta1 <- rerun(meta1)

summary(meta1)

## Extract the coefficients for the variance component of the random effects
coef1 <- coef(meta1, select="random")

## Convert it into a symmetric matrix by row major
my.cov <- vec2symMat(coef1, byrow=TRUE)

## Convert it into a correlation matrix
```

```

cov2cor(my.cov)

## Plot the multivariate effect sizes
plot(meta1)

## End(Not run)

```

anova

*Compare Nested Models with Likelihood Ratio Statistic***Description**

It compares nested models with the likelihood ratio statistic from various objects. It is a wrapper of [mxCompare](#).

Usage

```

## S3 method for class 'wls'
anova(object, ..., all=FALSE)
## S3 method for class 'meta'
anova(object, ..., all=FALSE)
## S3 method for class 'meta3LFIML'
anova(object, ..., all=FALSE)
## S3 method for class 'reml'
anova(object, ..., all=FALSE)
## S3 method for class 'osmasem'
anova(object, ..., all=FALSE)

```

Arguments

| | |
|--------|--------------------------------------------------------------------------------------------------------------------------------------------|
| object | An object or a list of objects of various classes. It will be passed to the base argument in mxCompare . |
| ... | An object or a list of objects of various classes. It will be passed to the comparison argument in mxCompare . |
| all | A Boolean value on whether to compare all bases with all comparisons. It will be passed to the all argument in mxCompare . |

Value

A table of comparisons between the models in base and comparison.

Note

When the objects are class [wls](#), the degrees of freedom in the base and comparison models are incorrect, while the degrees of freedom of the difference between them is correct. If users want to obtain the correct degrees of freedom in the base and comparison models, they may individually apply the [summary](#) function on the base and comparison models.

Author(s)

Mike W.-L. Cheung <mikewlcheung@nus.edu.sg>

Examples

```
## Test the significance of a predictor with likelihood ratio test
## Model0: No predictor
model0 <- meta(y=yi, v=vi, data=Hox02, model.name="No predictor")

## Model1: With a predictor
model1 <- meta(y=yi, v=vi, x=weeks, data=Hox02, model.name="One predictor")

## Compare these two models
anova(model1, model0)
```

as.mxAlgebra

Convert a Character Matrix into MxAlgebra-class

Description

It converts a character matrix into MxAlgebra object.

Usage

```
as.mxAlgebra(x, startvalues=NULL, name="X")
```

Arguments

| | |
|-------------|-------------------------------------------------------------------------------------------------------------|
| x | A character or numeric matrix, which consists of valid operators in mxAlgebra. |
| startvalues | A list of starting values of the free parameters. If it is not provided, all free parameters are assumed 0. |
| name | A character string of the names of the objects based on. |

Details

Suppose the name argument is "X", the output is a list of the following elements.

Value

| | |
|------------|--------------------------------------------------|
| mxalgebra | An mxAlgebra object. |
| parameters | A column vector mxMatrix of the free parameters. |
| list | A list of mxMatrix to form the mxAlgebra object. |

Author(s)

Mike W.-L. Cheung <mikewlcheung@nus.edu.sg>

See Also[as.mxMatrix, mxAlgebra](#)**Examples**

```

## a, b, and c are free parameters
(A1 <- matrix(c(1, "a*b", "a^b", "exp(c)"), ncol=2, nrow=2))
##      [,1] [,2]
## [1,] "1"  "a^b"
## [2,] "a*b" "exp(c)"

A <- as.mxAlgebra(A1, startvalues=list(a=1, b=2), name="A")

## An object of mxAlgebra
A$mxalgebra
## mxAlgebra 'A'
## $formula: rbind(cbind(A1_1, A1_2), cbind(A2_1, A2_2))
## $result: (not yet computed) <0 x 0 matrix>
## dimnames: NULL

## A matrix of parameters
A$parameters
## FullMatrix 'Avars'

## $labels
##      [,1]
## [1,] "a"
## [2,] "b"
## [3,] "c"

## $values
##      [,1]
## [1,] 1
## [2,] 2
## [3,] 0

## $free
##      [,1]
## [1,] TRUE
## [2,] TRUE
## [3,] TRUE

## $lbound: No lower bounds assigned.

## $ubound: No upper bounds assigned.

## A list of matrices of elements for the mxAlgebra
A$list
## $A1_1
## mxAlgebra 'A1_1'
## $formula: 1

```

```
## $result: (not yet computed) <0 x 0 matrix>
## dimnames: NULL

## $A2_1
## mxAlgebra 'A2_1'
## $formula: a * b
## $result: (not yet computed) <0 x 0 matrix>
## dimnames: NULL

## $A1_2
## mxAlgebra 'A1_2'
## $formula: a^b
## $result: (not yet computed) <0 x 0 matrix>
## dimnames: NULL

## $A2_2
## mxAlgebra 'A2_2'
## $formula: exp(c)
## $result: (not yet computed) <0 x 0 matrix>
## dimnames: NULL
```

as.mxMatrix

Convert a Matrix into MxMatrix-class

Description

It converts a matrix into MxMatrix-class via mxMatrix.

Usage

```
as.mxMatrix(x, name, ...)
```

Arguments

| | |
|------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x | A character or numeric matrix. If x is not a matrix, as.matrix(x) is applied first. |
| name | An optional character string as the name of the MxMatrix object created by mxModel function. If the name is missing, the name of x will be used. |
| ... | Further arguments to be passed to mxMatrix. It should be noted that type, nrow, ncol, values, free, name and labels will be created automatically. Thus, these arguments except labels should be avoided in ... |

Details

If there are non-numeric values in x, they are treated as the labels of the parameters. If a "*" is present, the numeric value on the left-hand side will be treated as the starting value for a free parameter. If an "@" is present, the numeric value on the left-hand side will be considered as the value for a fixed parameter. If it is a matrix of numeric values, there are no free parameters in the output matrix.

Value

A `MxMatrix-class` object with the same dimensions as `x`

Author(s)

Mike W.-L. Cheung <mikewlcheung@nus.edu.sg>

See Also

`mxMatrix`, `create.mxMatrix`, `create.Fmatrix`, `checkRAM`, `lavaan2RAM`, `as.symMatrix`

Examples

```
## a and b are free parameters with starting values and labels
(a1 <- matrix(c(1:4, "5*a", 6, "7*b", 8, 9), ncol=3, nrow=3))
#      [,1] [,2] [,3]
# [1,] "1"  "4"  "7*b"
# [2,] "2"  "5*a" "8"
# [3,] "3"  "6"  "9"

a1 <- as.mxMatrix(a1)

## a and b are fixed parameters without any labels, name="new2"
(a2 <- matrix(1:9, ncol=3, nrow=3))
#      [,1] [,2] [,3]
# [1,]  1   4   7
# [2,]  2   5   8
# [3,]  3   6   9

new2 <- as.mxMatrix(a2, name="new2")

## Free parameters without starting values
(a3 <- matrix(c(1:4, "*a", 6, "*b", 8, 9), ncol=3, nrow=3))
#      [,1] [,2] [,3]
# [1,] "1"  "4"  "*b"
# [2,] "2"  "*a" "8"
# [3,] "3"  "6"  "9"

a3 <- as.mxMatrix(a3, lbound=0)

## A free parameter without label
(a4 <- matrix(c(1:4, "5*", 6, "7*b", 8, 9), ncol=3, nrow=3))
#      [,1] [,2] [,3]
# [1,] "1"  "4"  "7*b"
# [2,] "2"  "5*" "8"
# [3,] "3"  "6"  "9"

a4 <- as.mxMatrix(a4)

## Convert a scalar into mxMatrix object
## "name" is required as "3*a" is not a valid name.
(a5 <- as.mxMatrix("3*a", name="a5"))
```

```
## Free and fixed parameters
(a6 <- matrix(c(1, "2*a", "3@b", 4), ncol=2, nrow=2))

as.mxMatrix(a6)
```

| | |
|--------------|------------------------------------------------------------------------------------------------------|
| as.symMatrix | <i>Convert a Character Matrix with Starting Values to a Character Matrix without Starting Values</i> |
|--------------|------------------------------------------------------------------------------------------------------|

Description

It converts a character matrix with starting values to a character matrix without the starting values.

Usage

```
as.symMatrix(x)
```

Arguments

x A character or numeric matrix or a list of character or numeric matrices.

Details

If there are non-numeric values in x, they are treated as the labels of the free parameters. If a "*" is present, the numeric value on the left-hand side will be treated as the starting value for a free parameter or a fixed value for a fixed parameter. If it is a matrix of numeric values, there are no free parameters in the output matrix. This function removes the starting values and "*" in the matrices.

Value

A character matrix.

Author(s)

Mike W.-L. Cheung <mikewlcheung@nus.edu.sg>

See Also

[as.mxMatrix](#)

Examples

```
## a and b are free parameters with starting values and labels
(a1 <- matrix(c(1:4, "5*a", 6, "7*b", 8, 9), ncol=3, nrow=3))
#      [,1] [,2] [,3]
# [1,] "1"  "4"  "7*b"
# [2,] "2"  "5*a" "8"
# [3,] "3"  "6"  "9"

(as.symMatrix(a1))
#      [,1] [,2] [,3]
# [1,] "1"  "4"  "b"
# [2,] "2"  "a"  "8"
# [3,] "3"  "6"  "9"
```

| | |
|--------|--------------------------------------------------------------------------------|
| asyCov | <i>Compute Asymptotic Covariance Matrix of a Correlation/Covariance Matrix</i> |
|--------|--------------------------------------------------------------------------------|

Description

It computes the asymptotic sampling covariance matrix of a correlation/covariance matrix under the assumption of multivariate normality.

Usage

```
asyCov(x, n, cor.analysis = TRUE, as.matrix = TRUE,
       acov=c("weighted", "individual", "unweighted"), ...)
asyCovOld(x, n, cor.analysis = TRUE, dropNA = FALSE, as.matrix = TRUE,
         acov=c("individual", "unweighted", "weighted"),
         suppressWarnings = TRUE, silent = TRUE, run = TRUE, ...)
```

Arguments

| | |
|--------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x | A correlation/covariance matrix or a list of correlation/covariance matrices. NA on the variables or other values defined in <code>na.strings</code> will be removed before the analysis. Note that it only checks the diagonal elements of the matrices. If there are missing values, make sure that the diagonals are coded with NA or values defined in <code>na.strings</code> . |
| n | Sample size or a vector of sample sizes |
| cor.analysis | Logical. The output is either a correlation or covariance matrix. |
| dropNA | Logical. If it is TRUE, the resultant dimensions will be reduced by dropping the missing variables. If it is FALSE, the resultant dimensions are the same as the input by keeping the missing variables. |
| as.matrix | Logical. If it is TRUE and x is a list of correlation/covariance matrices with the same dimensions, the asymptotic covariance matrices will be column vectorized and stacked together. If it is FALSE, the output will be a list of asymptotic covariance matrices. Note that if it is TRUE, dropNA will be FALSE automatically. This option is useful when passing the asymptotic covariance matrices to meta |

| | |
|------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| acov | If it is individual (the default), the sampling variance-covariance matrices are calculated based on the individual correlation/covariance matrix. If it is either unweighted or weighted, the average correlation/covariance matrix is calculated based on the unweighted or weighted mean with the sample sizes. The average correlation/covariance matrix is used to calculate the sampling variance-covariance matrices. |
| suppressWarnings | Logical. If TRUE, warnings are suppressed. It is passed to <code>mxRun</code> . |
| silent | Logical. An argument to be passed to <code>mxRun</code> |
| run | Logical. If FALSE, only return the mx model without running the analysis. |
| ... | It is ignored in <code>asyCov</code> . The additional arguments will be passed to <code>mxRun</code> in <code>asyCovOld</code> . |

Value

An asymptotic covariance matrix of the vectorized correlation/covariance matrix or a list of these matrices. If `as.matrix=TRUE` and `x` is a list of matrices, the output is a stacked matrix.

Note

Before 1.2.6, `asyCov` used an SEM approach based on Cheung and Chan (2004). After 1.2.6, `asyCov` was rewritten based on Olkin and Siotani (1976) for correlation matrix and Yuan and Bentler (2007, p. 371) for covariance matrix. Arguments such as `dropNA`, `suppressWarnings`, `silent`, and `run` were dropped. The original version was renamed to `asyCovOld` for compatibility.

Author(s)

Mike W.-L. Cheung <mikewlcheung@nus.edu.sg>

References

- Cheung, M. W.-L., & Chan, W. (2004). Testing dependent correlation coefficients via structural equation modeling. *Organizational Research Methods*, *7*, 206-223.
- Olkin, I., & Siotani, M. (1976). Asymptotic distribution of functions of a correlation matrix. In S. Ideka (Ed.), *Essays in probability and statistics* (pp. 235-251). Shinko Tsusho.
- Yuan, K.-H., & Bentler, P. M. (2007). Robust procedures in structural equation modeling. In S.-Y. Lee (Ed.), *Handbook of Latent Variable and Related Models* (pp. 367-397). Elsevier/North-Holland.

Examples

```
## Not run:
C1 <- matrix(c(1,0.5,0.4,0.5,1,0.2,0.4,0.2,1), ncol=3)
asyCov(C1, n=100)

## Data with missing values
C2 <- matrix(c(1,0.4,NA,0.4,1,NA,NA,NA,NA), ncol=3)
C3 <- matrix(c(1,0.2,0.2,1), ncol=2)
```

```
## Output is a stacked matrix of asymptotic covariance matrices
asyCov(list(C1,C2), n=c(100,50), as.matrix=TRUE)

## Output is a stacked matrix of asymptotic covariance matrices
asyCov(list(C3,C3), n=c(100,50), as.matrix=TRUE)

## Output is a list of asymptotic covariance matrices using the old version
asyCovOld(list(C1,C2,C3), n=c(100,50,50), dropNA=TRUE, as.matrix=FALSE)

## End(Not run)
```

| | |
|-----|------------------------------------------------------------------------------------|
| BCG | <i>Dataset on the Effectiveness of the BCG Vaccine for Preventing Tuberculosis</i> |
|-----|------------------------------------------------------------------------------------|

Description

This dataset includes 13 studies on the effectiveness of the Bacillus Calmette-Guerin (BCG) vaccine for preventing tuberculosis (see van Houwelingen, Arends, & Stijnen (2002) for details).

Usage

```
data(BCG)
```

Details

A list of data with the following structure:

Trial Number of the trials

Author Authors of the original studies

Year Year of publication

VD Vaccinated group with disease

VWD Vaccinated group without the disease

NVD Not vaccinated group with disease

NVWD Not vaccinated group without the disease

Latitude Geographic latitude of the place where the study was done

Allocation Method of treatment allocation

ln_OR Natural logarithm of the odds ratio: $\log((VD/VWD)/(NVD/NVWD))$

v_ln_OR Sampling variance of ln_OR: $1/VD+1/VWD+1/NVD+1/NVWD$

ln_Odd_V Natural logarithm of the odds of the vaccinated group: $\log(VD/VWD)$

ln_Odd_NV Natural logarithm of the odds of the not vaccinated group: $\log(NVD/NVWD)$

v_ln_Odd_V Sampling variance of ln_Odd_V: $1/VD+1/VWD$

cov_V_NV Sampling covariance between ln_Odd_V and ln_Odd_NV: It is always 0

v_ln_Odd_NV Sampling variance of ln_Odd_NV: $1/NVD+1/NVWD$

Source

Colditz, G. A., Brewer, T. F., Berkey, C. S., Wilson, M. E., Burdick, E., Fineberg, H. V., & Mosteller, F. (1994). Efficacy of BCG vaccine in the prevention of tuberculosis: Meta-analysis of the published literature. *Journal of the American Medical Association*, **271**, 698–702.

References

Berkey, C. S., Hoaglin, D. C., Mosteller, F., & Colditz, G. A. (1995). A random-effects regression model for meta-analysis. *Statistics in Medicine*, **14**, 395–411.

van Houwelingen, H. C., Arends, L. R., & Stijnen, T. (2002). Advanced methods in meta-analysis: Multivariate approach and meta-regression. *Statistics in Medicine*, **21**, 589–624.

Viechtbauer, W. (2010). Conducting meta-analyses in R with the metafor package. *Journal of Statistical Software*, **36**(3), 1–48. <https://www.jstatsoft.org/v36/i03/>.

Examples

```
data(BCG)

## Univariate meta-analysis on the log of the odds ratio
summary( meta(y=ln_OR, v=v_ln_OR, data=BCG,
             x=cbind(scale(Latitude,scale=FALSE),
                     scale(Year,scale=FALSE))) )

## Multivariate meta-analysis on the log of the odds
## The conditional sampling covariance is 0
bcg <- meta(y=cbind(ln_Odd_V, ln_Odd_NV), data=BCG,
           v=cbind(v_ln_Odd_V, cov_V_NV, v_ln_Odd_NV))
summary(bcg)

plot(bcg)
```

bdiagMat

Create a Block Diagonal Matrix

Description

It creates a block diagonal matrix from a list of numeric or character matrices.

Usage

```
bdiagMat(x)
```

Arguments

x A list of numeric or character matrices (or values)

Value

A numeric or character block diagonal matrix

Author(s)

Mike W.-L. Cheung <mikewlcheung@nus.edu.sg>

References

It was based on a function posted by Scott Chasalow at <http://www.math.yorku.ca/Who/Faculty/Monette/pub/stmp/0827.html>

See Also

[bdiagRep](#), [matrix2bdiag](#)

Examples

```
## Block diagonal matrix of numbers
bdiagMat( list(matrix(1:4,nrow=2,ncol=2),
               matrix(5:6,nrow=1,ncol=2)) )
#      [,1] [,2] [,3] [,4]
# [1,]  1   3   0   0
# [2,]  2   4   0   0
# [3,]  0   0   5   6

## Block diagonal matrix of characters
bdiagMat( list(matrix(letters[1:4],nrow=2,ncol=2),
               matrix(letters[5:6],nrow=1,ncol=2)) )
#      [,1] [,2] [,3] [,4]
# [1,] "a"  "c"  "0"  "0"
# [2,] "b"  "d"  "0"  "0"
# [3,] "0"  "0"  "e"  "f"
```

bdiagRep

Create a Block Diagonal Matrix by Repeating the Input

Description

It creates a block diagonal matrix by repeating the input matrix several times.

Usage

```
bdiagRep(x, times)
```

Arguments

x A numeric or character matrix (or values)
times Number of times of x to be repeated

Value

A numeric or character block diagonal matrix

Author(s)

Mike W.-L. Cheung <mikewlcheung@nus.edu.sg>

See Also

[bdiagMat](#), [matrix2bdiag](#)

Examples

```
## Block diagonal matrix of numerics
bdiagRep( matrix(1:4,nrow=2,ncol=2), 2 )
#      [,1] [,2] [,3] [,4]
# [1,]  1   3   0   0
# [2,]  2   4   0   0
# [3,]  0   0   1   3
# [4,]  0   0   2   4

## Block diagonal matrix of characters
bdiagRep( matrix(letters[1:4],nrow=2,ncol=2), 2 )
#      [,1] [,2] [,3] [,4]
# [1,] "a"  "c"  "0"  "0"
# [2,] "b"  "d"  "0"  "0"
# [3,] "0"  "0"  "a"  "c"
# [4,] "0"  "0"  "b"  "d"
```

Becker09

Ten Studies of Correlation Matrices used by Becker (2009)

Description

This dataset includes ten studies on the relationships between CSAI subscales and sports behavior. The original data were used in Craft et al. (2003), whereas a subset of them was illustrated in Becker (2009).

Usage

```
data("Becker09")
```

Details

A list of data with the following structure:

data A list of 4x4 correlation matrices. The variables are *Performance*, *Cognitive*, *Somatic*, and *Self_confidence*

n A vector of sample sizes

Type_of_sport Samples based on *Individual* or *Team*

Source

Craft, L. L., Magyar, T. M., Becker, B. J., & Feltz, D. L. (2003). The relationship between the Competitive State Anxiety Inventory-2 and sport performance: a meta-analysis. *Journal of Sport and Exercise Psychology*, **25**(1), 44-65.

References

Becker, B. J. (2009). Model-based meta-analysis. In H. Cooper, L. V. Hedges, & J. C. Valentine (Eds.), *The handbook of research synthesis and meta-analysis* (2nd ed., pp. 377-395). New York: Russell Sage Foundation.

Examples

```
## Not run:
data(Becker09)

#### Fixed-effects model
## First stage analysis
fixed1 <- tssem1(Becker09$data, Becker09$n, method="FEM")
summary(fixed1)

## Prepare a regression model using create.mxMatrix()
A1 <- create.mxMatrix(c(0, "0.1*Cog2Per", "0.1*S02Per", "0.1*SC2Per",
                        0, 0, 0, 0,
                        0, 0, 0, 0,
                        0, "0.1*Cog2SC", "0.1*S02SC", 0),
                      type="Full", byrow=TRUE, ncol=4, nrow=4,
                      as.mxMatrix=FALSE)

## This step is not necessary but it is useful for inspecting the model.
dimnames(A1)[[1]] <- dimnames(A1)[[2]] <- c("Performance", "Cognitive",
                                             "Somatic", "Self_confidence")

## Display A1
A1

S1 <- create.mxMatrix(c("0.1*var_Per",
                        0, 1,
                        0, "0.1*cor", 1,
                        0, 0, 0, "0.1*var_SC"), byrow=TRUE, type="Symm",
                      as.mxMatrix=FALSE)

## This step is not necessary but it is useful for inspecting the model.
dimnames(S1)[[1]] <- dimnames(S1)[[2]] <- c("Performance", "Cognitive",
                                             "Somatic", "Self_confidence")

## Display S1
S1

#####
## Alternative model specification in lavaan model syntax
model <- "## Regression paths"
```

```

Performance ~ Cog2Per*Cognitive + S02Per*Somatic + SC2Per*Self_confidence
Self_confidence ~ Cog2SC*Cognitive + S02SC*Somatic
## Fix the variances of Cog and S0 at 1
Cognitive ~~ 1*Cognitive
Somatic ~~ 1*Somatic
## Label the correlation between Cog and S0
Cognitive ~~ cor*Somatic
## Label the error variances of Per and SC
Performance ~~ var_Per*Performance
Self_confidence ~~ var_SC*Self_confidence"

## Display the model
plot(model, layout="spring")

RAM <- lavaan2RAM(model, obs.variables=c("Performance", "Cognitive",
                                         "Somatic", "Self_confidence"))

RAM

A1 <- RAM$A
S1 <- RAM$S
#####

## Second stage analysis
fixed2 <- tssem2(fixed1, Amatrix=A1, Smatrix=S1, diag.constraints=TRUE,
                 intervals.type="LB", model.name="TSSEM2 Becker09",
                 mx.algebras=list( Cog=mxAlgebra(Cog2SC*SC2Per, name="Cog"),
                                   SO=mxAlgebra(S02SC*SC2Per, name="S0"),
                                   Cog_S0=mxAlgebra(Cog2SC*SC2Per+S02SC*SC2Per,
                                                    name="Cog_S0")) )

summary(fixed2)

## Display the model with the parameter estimates
plot(fixed2, layout="spring")

#### Fixed-effects model: with type of sport as cluster
## First stage analysis
cluster1 <- tssem1(Becker09$data, Becker09$n, method="FEM",
                  cluster=Becker09$Type_of_sport)
summary(cluster1)

## Second stage analysis
cluster2 <- tssem2(cluster1, Amatrix=A1, Smatrix=S1, diag.constraints=TRUE,
                  intervals.type="LB", model.name="TSSEM2 Becker09",
                  mx.algebras=list( Cog=mxAlgebra(Cog2SC*SC2Per, name="Cog"),
                                    SO=mxAlgebra(S02SC*SC2Per, name="S0"),
                                    Cog_S0=mxAlgebra(Cog2SC*SC2Per+S02SC*SC2Per,
                                                       name="Cog_S0")) )

summary(cluster2)

## Convert the model to semPlotModel object with 2 plots
## Use the short forms of the variable names
my.plots <- lapply(X=cluster2, FUN=meta2semPlot, manNames=c("Per", "Cog", "S0", "SC") )

```

```

## Load the library
library("semPlot")

## Setup two plots
layout(t(1:2))
## The labels are overlapped. We may modify it by using layout="spring"
semPaths(my.plots[[1]], whatLabels="est", nCharNodes=10, color="orange",
         layout="spring", edge.label.cex=0.8)
title("Individual sport")
semPaths(my.plots[[2]], whatLabels="est", nCharNodes=10, color="skyblue",
         layout="spring", edge.label.cex=0.8)
title("Team sport")

#### Random-effects model
## First stage analysis
random1 <- tssem1(Becker09$data, Becker09$n, method="REM", RE.type="Diag")
summary(random1)

## Second stage analysis
random2 <- tssem2(random1, Amatrix=A1, Smatrix=S1, diag.constraints=TRUE,
                 intervals.type="LB", model.name="TSSEM2 Becker09",
                 mx.algebras=list( Cog=mxAlgebra(Cog2SC*SC2Per, name="Cog"),
                                   SO=mxAlgebra(SO2SC*SC2Per, name="SO"),
                                   Cog_SO=mxAlgebra(Cog2SC*SC2Per+SO2SC*SC2Per,
                                                    name="Cog_SO"))) )
summary(random2)

## Display the model
plot(random2, what="path", layout="spring")

## Display the model with the parameter estimates
plot(random2, layout="spring", color="yellow")

#### Univariate r approach
#### First stage of the analysis
uni1 <- uniR1(Becker09$data, Becker09$n)
uni1

#### Second stage of analysis using OpenMx
model2 <- "## Regression paths
          Performance ~ Cog2Per*Cognitive + SO2Per*Somatic + SC2Per*Self_confidence
          Self_confidence ~ Cog2SC*Cognitive + SO2SC*Somatic
          ## Provide starting values for Cog and SO
          Cognitive ~~ start(1)*Cognitive
          Somatic   ~~ start(1)*Somatic
          ## Label the correlation between Cog and SO
          Cognitive ~~ cor*Somatic
          ## Label the error variances of Per and SC
          Performance ~~ var_Per*Performance
          Self_confidence ~~ var_SC*Self_confidence"

RAM2 <- lavaan2RAM(model2, obs.variables=c("Performance", "Cognitive",

```

```

"Somatic", "Self_confidence"))
RAM2

uni2mx <- uniR2mx(uni1, RAM=RAM2)
summary(uni2mx)

#### Second stage of analysis Using lavaan
model3 <- "## Regression paths
          Performance ~ Cognitive + Somatic + Self_confidence
          Self_confidence ~ Cognitive + Somatic"

uni2lavaan <- uniR2lavaan(uni1, model3)
lavaan::summary(uni2lavaan)

## End(Not run)

```

Becker83

Studies on Sex Differences in Conformity Reported by Becker (1983)

Description

The data set includes studies on sex differences in conformity using the fictitious norm group paradigm reported by Becker (1983).

Usage

```
data(Becker83)
```

Details

The variables are:

study study number

di Standardized mean difference

vi Sampling variance of the effect size

percentage Percentage of male authors

items Number of items

Source

Becker, B. J. (1983, April). Influence again: A comparison of methods for meta-analysis. *Paper presented at the annual meeting of the American Educational Research Association, Montreal.*

Hedges, L. V., & Olkin, I. (1985). *Statistical methods for meta-analysis*. Orlando, FL: Academic Press.

References

Cheung, M. W.-L. (2010). Fixed-effects meta-analyses as multiple-group structural equation models. *Structural Equation Modeling*, **17**, 481-509.

Examples

```

data(Becker83)

## Random-effects meta-analysis
summary( meta(y=di, v=vi, data=Becker83) )

## Mixed-effects meta-analysis with log(items) as the predictor
summary( meta(y=di, v=vi, x=log(items), data=Becker83) )

```

Becker92

Six Studies of Correlation Matrices reported by Becker (1992; 1995)

Description

This data set includes six studies of correlation matrices reported by Becker (1992; 1995).

Usage

```
data(Becker92)
```

Details

A list of data with the following structure:

data A list of 6 studies of correlation matrices. The variables are *Math* (math aptitude), *Spatial* (spatial ability), and *Verbal* (verbal ability)

n A vector of sample sizes

Source

Becker, B. J. (1992). Using results from replicated studies to estimate linear models. *Journal of Educational Statistics*, **17**(4), 341-362. doi:10.3102/10769986017004341

Becker, B. J. (1995). Corrections to "Using Results from Replicated Studies to Estimate Linear Models." *Journal of Educational and Behavioral Statistics*, **20**(1), 100-102. doi:10.2307/1165390

Examples

```

## Not run:
data(Becker92)

#### Fixed-effects model
## First stage analysis
## Replicate Becker's (1992) analysis using 4 studies only

fixed1 <- tssem1(Becker92$data[1:4], Becker92$n[1:4], method="FEM")
summary(fixed1)

## ## Prepare a regression model using create.mxMatrix()

```

```

## A1 <- create.mxMatrix(c(0,0,0,"0.2*Spatial2Math",
##                          0,0,"0.2*Verbal2Math",0,0), type="Full",
##                          ncol=3, nrow=3, as.mxMatrix=FALSE)

## var.names <- c("Math_aptitude","Spatial","Verbal")

## ## This step is not necessary but it is useful for inspecting the model.
## dimnames(A1)[[1]] <- dimnames(A1)[[2]] <- var.names

## ## Display A1
## A1

## S1 <- create.mxMatrix(c("0.2*ErrorVarMath",0,0,1,"0.2*CorSpatialVerbal",1),
##                          type="Symm", as.mxMatrix=FALSE)

## ## This step is not necessary but it is useful for inspecting the model.
## dimnames(S1)[[1]] <- dimnames(S1)[[2]] <- var.names

## ## Display S1
## S1

#####
## Alternative model specification in lavaan model syntax
model <- "## Regression paths
          Math ~ Spatial2Math*Spatial + Verbal2Math*Verbal
          Spatial ~~ CorSpatialVerbal*Verbal
          ## Fix the variances of Spatial and Verbal at 1
          Spatial ~~ 1*Spatial
          Verbal ~~ 1*Verbal
          ## Label the error variance of Math
          Math ~~ ErrorVarMath*Math + start(0.2)*Math"

## Display the model
plot(model)

RAM <- lavaan2RAM(model, obs.variables=c("Math", "Spatial", "Verbal"))
RAM

#####

## Fixed-effects model: Second stage analysis
## Two equivalent versions to calculate the R2 and its 95% LBCI
fixed2 <- tssem2(fixed1, RAM=RAM, intervals.type="LB",
                mx.algebras=list(R1=mxAlgebra(Spatial2Math^2+Verbal2Math^2
                +2*CorSpatialVerbal*Spatial2Math*Verbal2Math, name="R1"),
                R2=mxAlgebra(One-Smatrix[1,1], name="R2"),
                One=mxMatrix("Iden", ncol=1, nrow=1, name="One")))

summary(fixed2)

## Display the model with the parameter estimates
plot(fixed2)

#### Random-effects model

```



```

## First stage analysis
## No random effects for off-diagonal elements
random1 <- tssem1(Becker92$data, Becker92$n, method="REM", RE.type="Diag")
summary(random1)

## Random-effects model: Second stage analysis
random2 <- tssem2(random1, RAM=RAM)
summary(random2)

## Display the model with the parameter estimates
plot(random2, color="yellow")

#### Similar to conventional fixed-effects GLS approach
## First stage analysis
## No random effects
## Replicate Becker's (1992) analysis using 4 studies only
gls1 <- tssem1(Becker92$data[1:4], Becker92$n[1:4], method="REM", RE.type="Zero",
              model.name="Fixed effects GLS Stage 1")
summary(gls1)

## Fixed-effects GLS model: Second stage analysis
gls2 <- tssem2(gls1, RAM=RAM, model.name="Fixed effects GLS Stage 2")
summary(gls2)

## End(Not run)

```

Becker94

Five Studies of Ten Correlation Matrices reported by Becker and Schram (1994)

Description

This data set includes five studies of ten correlation matrices reported by Becker and Schram (1994).

Usage

```
data(Becker94)
```

Details

A list of data with the following structure:

data A list of 10 correlation matrices. The variables are *Math* (math aptitude), *Spatial* (spatial ability), and *Verbal* (verbal ability)

n A vector of sample sizes

gender *Females* or *Males* samples

Source

Becker, B. J., & Schram, C. M. (1994). Examining explanatory models through research synthesis. In H. Cooper & L. V. Hedges (Eds.), *The handbook of research synthesis* (pp. 357-381). New York: Russell Sage Foundation.

Examples

```
## Not run:
data(Becker94)

#### Fixed-effects model
## First stage analysis
fixed1 <- tssem1(Becker94$data, Becker94$n, method="FEM")
summary(fixed1)

## Prepare a regression model using create.mxMatrix()
## A1 <- create.mxMatrix(c(0,0,0,"0.2*Spatial2Math",
##                        0,0,"0.2*Verbal2Math",0,0), type="Full",
##                        ncol=3, nrow=3, name="A1")
## S1 <- create.mxMatrix(c("0.2*ErrorVarMath",0,0,1,
##                        "0.2*CorBetweenSpatialVerbal",1),
##                        type="Symm", name="S1")

## An alternative method to create a regression model with the lavaan syntax
model <- "## Regression model
        Math ~ Spatial2Math*Spatial + Verbal2Math*Verbal
        ## Error variance of Math
        Math ~~ ErrorVarMath*Math
        ## Variances of Spatial and Verbal fixed at 1.0
        Spatial ~~ 1*Spatial
        Verbal  ~~ 1*Verbal
        ## Correlation between Spatial and Verbal
        Spatial ~~ CorBetweenSpatialVerbal*Verbal"

## Display the model
plot(model)

RAM <- lavaan2RAM(model, obs.variables=c("Math", "Spatial", "Verbal"))
RAM

## Second stage analysis
## A1 <- RAM$A
## S1 <- RAM$S
## fixed2 <- tssem2(fixed1, Amatrix=A1, Smatrix=S1, intervals.type="LB")

fixed2 <- tssem2(fixed1, RAM=RAM, intervals.type="LB")
summary(fixed2)

## Display the model with the parameter estimates
plot(fixed2)

#### Fixed-effects model: with gender as cluster
```

```

## First stage analysis
cluster1 <- tssem1(Becker94$data, Becker94$n, method="FEM", cluster=Becker94$gender)
summary(cluster1)

## Second stage analysis
cluster2 <- tssem2(cluster1, RAM=RAM, intervals.type="LB")
summary(cluster2)

#### Conventional fixed-effects GLS approach
## First stage analysis
## No random effects
## Replicate Becker's (1992) analysis using 4 studies only
gls1 <- tssem1(Becker92$data[1:4], Becker92$n[1:4], method="REM", RE.type="Zero",
               model.name="Fixed effects GLS Stage 1")
summary(gls1)

## Fixed-effects GLS model: Second stage analysis
gls2 <- tssem2(gls1, RAM=RAM, intervals.type="LB",
               model.name="Fixed effects GLS Stage 2")
summary(gls2)

## End(Not run)

```

Berkey98

Five Published Trails from Berkey et al. (1998)

Description

The data set includes five published trials, reported by Berkey et al. (1998), comparing surgical and non-surgical treatments for medium-severity periodontal disease, one year after treatment.

Usage

```
data(Berkey98)
```

Details

The variables are:

trial Trial number

pub_year Publication year

no_of_patients Number of patients

PD Patient improvements (mm) in *probing depth*

AL Patient improvements (mm) in *attachment level*

var_PD Sampling variance of PD

cov_PD_AL Sampling covariance between PD and AD

var_AL Sampling variance of AL

Source

Berkey, C. S., Hoaglin, D. C., Antczak-Bouckoms, A., Mosteller, F., & Colditz, G. A. (1998). Meta-analysis of multiple outcomes by regression with random effects. *Statistics in Medicine*, **17**, 2537-2550.

Examples

```
## Not run:
data(Berkey98)

#### ML estimation method
## Multivariate meta-analysis
x <- meta(y=cbind(PD, AL), v=cbind(var_PD, cov_PD_AL, var_AL), data=Berkey98)
x <- rerun(x)
summary(x)
plot(x)

## Plot individual studies proportional to the weights
plot(x, study.weight.plot=TRUE)

## Include forest plot from the metafor package
library(metafor)
plot(x, diag.panel=TRUE, main="Multivariate meta-analysis",
      axis.label=c("PD", "AL"))
forest( rma(yi=PD, vi=var_PD, data=Berkey98) )
title("Forest plot of PD")
forest( rma(yi=AL, vi=var_AL, data=Berkey98) )
title("Forest plot of AL")

## Multivariate meta-analysis with "publication year-1979" as the predictor
summary( meta(y=cbind(PD, AL), v=cbind(var_PD, cov_PD_AL, var_AL),
            x=scale(pub_year, center=1979), data=Berkey98,
            RE.lbound=NA) )

## Multivariate meta-analysis with equality constraint on the regression coefficients
summary( meta(y=cbind(PD, AL), v=cbind(var_PD, cov_PD_AL, var_AL),
            x=scale(pub_year, center=1979), data=Berkey98,
            coef.constraints=matrix(c("0.3*Eq_slope", "0.3*Eq_slope"),
            nrow=2)) )

#### REML estimation method
## Multivariate meta-analysis
summary( reml(y=cbind(PD, AL), v=cbind(var_PD, cov_PD_AL, var_AL),
            data=Berkey98,
            model.name="Multivariate meta analysis with REML") )

## Multivariate meta-analysis with "publication year-1979" as the predictor
## Diagonal structure for the variance component
summary( reml(y=cbind(PD, AL), v=cbind(var_PD, cov_PD_AL, var_AL),
            RE.constraints=Diag(c("1e-5*Tau2_1_1", "1e-5*Tau2_2_2")),
            x=scale(pub_year, center=1979), data=Berkey98) )
```

```
## End(Not run)
```

 Boer16

Correlation Matrices from Boer et al. (2016)

Description

The data set includes correlation matrices of leader-member exchange in transformational leadership reported by Boer et al. (2016).

Usage

```
data(Boer16)
```

Details

A list of data with the following structure:

data A list of correlation matrices. The variables are *LMX* (leader-member exchange), *TFL* (transformational leadership), *JS* (job satisfaction), *OC* (organizational commitment), and *LE* (leader effectiveness)

n A vector of sample sizes

RelLMX The reliability of *LMX*

RelTFL The reliability of *TFL*

Source

Boer, D., Deinert, A., Homan, A. C., & Voelpel, S. C. (2016). Revisiting the mediating role of leader-member exchange in transformational leadership: the differential impact model. *European Journal of Work and Organizational Psychology*, **25**(6), 883-899.

Examples

```
## Not run:
## Stage 1 analysis
rand1 <- tssem1(Boer16$data, Boer16$n, method="REM", RE.type="Diag",
               acov="weighted")
summary(rand1)

## Stage 2 analysis
model2a <- 'JS+OC+LE ~ LMX+TFL
           LMX ~ TFL
           ## Variance of TFL is fixed at 1
           TFL ~~ 1*TFL
           ## Correlated residuals
           JS ~~ OC
           JS ~~ LE
           OC ~~ LE'
```

```

## Display the model
plot(model2a)

RAM2a <- lavaan2RAM(model2a, obs.variables = c("LMX", "TFL", "JS", "OC", "LE"),
                  A.notation="on", S.notation="with")

rand2a <- tssem2(rand1, Amatrix=RAM2a$A, Smatrix=RAM2a$S)
summary(rand2a)

## Display the model with the parameter estimates
plot(rand2a, layout="spring")

## End(Not run)

```

bootuniR1

Parametric bootstrap on the univariate R (uniR) object

Description

It generates correlation matrices with the parametric bootstrap on the univariate R (uniR) object.

Usage

```
bootuniR1(x, Rep, nonPD.pop=c("replace", "nearPD", "accept"))
```

Arguments

| | |
|-----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x | An object of class 'uniR1' |
| Rep | Number of replications of the parametric bootstrap |
| nonPD.pop | If it is replace, generated non-positive definite matrices are replaced by generated new ones which are positive definite. If it is nearPD, they are replaced by nearly positive definite matrices by calling <code>Matrix::nearPD()</code> . If it is accept, they are accepted. |

Details

This function implements the parametric bootstrap approach suggested by Yu et al. (2016). It is included in this package for research interests. Please refer to Cheung (2018) for the issues associated with this parametric bootstrap approach.

Value

An object of the generated correlation matrices.

Author(s)

Mike W.-L. Cheung <mikewlcheung@nus.edu.sg>

References

Cheung, M. W.-L. (2018). Issues in solving the problem of effect size heterogeneity in meta-analytic structural equation modeling: A commentary and simulation study on Yu, Downes, Carter, and O'Boyle (2016). *Journal of Applied Psychology*, **103**, 787-803.

Yu, J. (Joya), Downes, P. E., Carter, K. M., & O'Boyle, E. H. (2016). The problem of effect size heterogeneity in meta-analytic structural equation modeling. *Journal of Applied Psychology*, **101**, 1457-1473.

See Also

[rCor](#), [bootuniR2](#), [Nohe15](#)

bootuniR2

Fit Models on the bootstrapped correlation matrices

Description

It fits structural equation models on the bootstrapped correlation matrices.

Usage

```
bootuniR2(model, data, n, ...)
```

Arguments

| | |
|-------|---------------------------------------------------------|
| model | A model in sem syntax. |
| data | A list of correlation matrices. |
| n | Sample size in fitting the structural equation models |
| ... | Further arguments to be passed to sem . |

Details

This function fits the lavaan model with the bootstrapped correlation matrices. It implements the parametric bootstrap approach suggested by Yu et al. (2016). It is included in this package for research interests. Please refer to Cheung (2018) for the issues associated with this parametric bootstrap approach.

Value

A list of the fitted object from [sem](#).

Author(s)

Mike W.-L. Cheung <mikewlcheung@nus.edu.sg>

References

Cheung, M. W.-L. (2018). Issues in solving the problem of effect size heterogeneity in meta-analytic structural equation modeling: A commentary and simulation study on Yu, Downes, Carter, and O'Boyle (2016). *Journal of Applied Psychology*, **103**, 787-803.

Yu, J. (Joya), Downes, P. E., Carter, K. M., & O'Boyle, E. H. (2016). The problem of effect size heterogeneity in meta-analytic structural equation modeling. *Journal of Applied Psychology*, **101**, 1457-1473.

See Also

[bootuniR2](#), [tssemParaVar](#), [Nohe15](#)

Bornmann07

A Dataset from Bornmann et al. (2007)

Description

A dataset from Bornmann et al. (2007) for three-level meta-analysis.

Usage

```
data(Bornmann07)
```

Details

The variables are:

ID ID of the study

Study Study name

Cluster Cluster for effect sizes

logOR Effect size: log odds ratio

v Sampling variance of logOR

Year Year of publication

Type Type of proposal: either **Grant** or **Fellowship**

Discipline Discipline of the proposal: either **Physical sciences**, **Life sciences/biology**, **Social sciences/humanities** or **Multidisciplinary**)

Country Country of the proposal: either the **United States**, **Canada**, **Australia**, **United Kingdom** or **Europe**

Source

Bornmann, L., Mutz, R., & Daniel, H.-D. (2007). Gender differences in grant peer review: A meta-analysis. *Journal of Informetrics*, **1(3)**, 226-238. doi:10.1016/j.joi.2007.03.001

References

- Cheung, M. W.-L. (2014). Modeling dependent effect sizes with three-level meta-analyses: A structural equation modeling approach. *Psychological Methods*, **19**, 211-229.
- Marsh, H. W., Bornmann, L., Mutz, R., Daniel, H.-D., & O'Mara, A. (2009). Gender Effects in the Peer Reviews of Grant Proposals: A Comprehensive Meta-Analysis Comparing Traditional and Multilevel Approaches. *Review of Educational Research*, **79**(3), 1290-1326. doi:10.3102/0034654309334143

Examples

```
## Not run:
data(Bornmann07)

#### ML estimation method
## No predictor
summary( meta3L(y=logOR, v=v, cluster=Cluster, data=Bornmann07) )

## Type as a predictor
## Grant: 0
## Fellowship: 1
summary( meta3L(y=logOR, v=v, x=(as.numeric(Type)-1),
               cluster=Cluster, data=Bornmann07) )

## Centered Year as a predictor
summary( meta3L(y=logOR, v=v, x=scale(Year, scale=FALSE),
               cluster=Cluster, data=Bornmann07) )

#### REML estimation method
## No predictor
summary( reml3L(y=logOR, v=v, cluster=Cluster, data=Bornmann07) )

## Type as a predictor
## Grants: 0
## Fellowship: 1
summary( reml3L(y=logOR, v=v, x=(as.numeric(Type)-1),
               cluster=Cluster, data=Bornmann07) )

## Centered Year as a predictor
summary( reml3L(y=logOR, v=v, x=scale(Year, scale=FALSE),
               cluster=Cluster, data=Bornmann07) )

## Handling missing covariates with FIML
## MCAR
## Set seed for replication
set.seed(1000000)

## Copy Bornmann07 to my.df
my.df <- Bornmann07
## "Fellowship": 1; "Grant": 0
my.df$type_MCAR <- ifelse(Bornmann07$Type=="Fellowship", yes=1, no=0)

## Create 17 out of 66 missingness with MCAR
```

```

my.df$Type_MCAR[sample(1:66, 17)] <- NA
summary(meta3LFIML(y=logOR, v=v, cluster=Cluster, x2=Type_MCAR, data=my.df))

## MAR
Type_MAR <- ifelse(Bornmann07$Type=="Fellowship", yes=1, no=0)

## Create 27 out of 66 missingness with MAR for cases Year<1996
index_MAR <- ifelse(Bornmann07$Year<1996, yes=TRUE, no=FALSE)
Type_MAR[index_MAR] <- NA

## Include auxiliary variable
summary(meta3LFIML(y=logOR, v=v, cluster=Cluster, x2=Type_MAR, av2=Year, data=my.df))

## End(Not run)

```

calEffSizes

Calculate Effect Sizes using lavaan Models

Description

It calculates effect sizes with Delta Method by formulating the effect sizes as functions of SEM in lavaan.

Usage

```
calEffSizes(model, data=NULL, n, Cov, Mean=NULL, group=NULL, lavaan.output=FALSE, ...)
```

Arguments

| | |
|---------------|---------------------------------------------------------------------------------------------------------|
| model | A lavaan model. Effect sizes are defined as functions of SEM parameters with :=. |
| data | A data frame of the observed variables. If it is NULL, summary statistics are required. |
| n | Sample sizes |
| Cov | A covariance matrix or a list of covariance matrices. |
| Mean | Optional sample means. |
| group | A character of the variable name in the data frame defining the groups in a multiple group analysis. |
| lavaan.output | If TRUE, it returns the fitted object instead of the effect sizes and their sampling covariance matrix. |
| ... | Further arguments passed to sem . |

Value

Effect sizes and their sampling covariance matrix or a lavaan fitted object.

Note

The input matrices are treated as covariance matrices unless there are explicit constraints in the model.

Author(s)

Mike W.-L. Cheung <mikewlcheung@nus.edu.sg>

References

Cheung, M. W.-L. (2015). *Meta-analysis: A structural equation modeling approach*. Chichester, West Sussex: John Wiley & Sons, Inc.

Cheung, M. W.-L. (2018). Computing multivariate effect sizes and their sampling covariance matrices with structural equation modeling: Theory, examples, and computer simulations. *Frontiers in Psychology*, **9**(1387). <https://doi.org/10.3389/fpsyg.2018.01387>

See Also

[smdMES](#), [smdMTS](#)

Examples

```
## Not run:
## Select ATT, Bi, and BEH
obs.vars <- c("BEH", "BI", "ATT")

## Select one study from Cooke16 for illustration
my.cor <- Cooke16$data[[4]][obs.vars, obs.vars]
my.n <- Cooke16$n[4]

## Effect sizes: indirect effect and direct effect
model <- "BEH ~ c*ATT + b*BI
         BI ~ a*ATT
         ## Indirect effect
         Ind := a*b
         Dir := c"

calEffSizes(model=model, n=my.n, Cov=my.cor, lavaan.output=FALSE)

## Return the lavaan fitted model
fit <- calEffSizes(model=model, n=my.n, Cov=my.cor, lavaan.output=TRUE)
lavaan::summary(fit)

lavaan::parameterestimates(fit)

## End(Not run)
```

 checkRAM

Check the correctness of the RAM formulation

Description

It provides simple checks on the correctness of the RAM formulation.

Usage

```
checkRAM(Amatrix, Smatrix, cor.analysis=TRUE)
```

Arguments

| | |
|--------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Amatrix | An asymmetric matrix in the RAM specification with <code>MxMatrix-class</code> . If it is a matrix, it will be converted into <code>MxMatrix-class</code> by the <code>as.mxMatrix</code> function. |
| Smatrix | A symmetric matrix in the RAM specification with <code>MxMatrix-class</code> . If it is a matrix, it will be converted into <code>MxMatrix-class</code> by the <code>as.mxMatrix</code> function. |
| cor.analysis | Logical. Analysis of correlation or covariance structure. There are additional checks for <code>cor.analysis=TRUE</code> . |

Value

It returns silently if no error has been detected; otherwise, it returns a warning message.

Author(s)

Mike W.-L. Cheung <mikewlcheung@nus.edu.sg>

See Also

[as.mxMatrix](#), [lavaan2RAM](#)

Examples

```
## Not run:
## Digman97 example
model1 <- "## Factor loadings
          Alpha=~A+C+ES
          Beta=~E+I
          ## Factor correlation
          Alpha~~Beta"

RAM1 <- lavaan2RAM(model1, obs.variables=c("A","C","ES","E","I"),
                  A.notation="on", S.notation="with")

RAM1

## The model is okay.
checkRAM(Amatrix=RAM1$A, Smatrix=RAM1$S)
```

```

## Hunter83 example
model2 <- "## Regression paths
  Job_knowledge ~ A2J*Ability
  Work_sample ~ A2W*Ability + J2W*Job_knowledge
  Supervisor ~ J2S*Job_knowledge + W2S*Work_sample

  ## Fix the variance of Ability at 1
  Ability ~~ 1*Ability

  ## Label the error variances of the dependent variables
  Job_knowledge ~~ VarE_J*Job_knowledge
  Work_sample ~~ VarE_W*Work_sample
  Supervisor ~~ VarE_S*Supervisor"

RAM2 <- lavaan2RAM(model2, obs.variables=c("Ability", "Job_knowledge",
  "Work_sample", "Supervisor"))

## The model is okay.
checkRAM(Amatrix=RAM2$A, Smatrix=RAM2$S)

## End(Not run)

```

 Cheung00

Fifty Studies of Correlation Matrices used in Cheung and Chan (2000)

Description

This data set includes fifty studies of correlation matrices on the theory of planned theory reported by Cheung and Chan (2000).

Usage

```
data(Cheung00)
```

Details

A list of data with the following structure:

data A list of 50 studies of correlation matrices. The variables are the attitude toward behavior *att*, subjective norm *sn*, behavioral intention *bi*, and behavior *beh*

n A vector of sample sizes

Note

These studies were extracted from the original data set for illustration purpose. Some samples contained two or more correlation matrices, and only one of them was arbitrarily selected to avoid the problem of dependence. Moreover, studies with less than 3 correlation coefficients were also excluded.

Source

Cheung, S.-F., & Chan, D. K.-S. (2000). The role of perceived behavioral control in predicting human behavior: A meta-analytic review of studies on the theory of planned behavior. *Unpublished manuscript*, Chinese University of Hong Kong.

References

Cheung, M.W.-L., & Cheung, S.-F. (2016). Random-effects models for meta-analytic structural equation modeling: Review, issues, and illustrations. *Research Synthesis Methods*, *7*, 140-155.

Examples

```
## Not run:
data(Cheung00)

## Variable labels
labels <- colnames(Cheung00$data[[1]])

## Full mediation model
S <- create.mxMatrix(c("1",
                      ".2*cov_att_sn", "1",
                      "0", "0", ".2*e_bi",
                      "0", "0", "0", ".2*e_beh"),
                    type="Symm", as.mxMatrix=FALSE, byrow=TRUE)
dimnames(S) <- list(labels, labels)
S

A <- matrix(c("0", "0", "0", "0",
              "0", "0", "0", "0",
              ".2*att2bi", ".2*sn2bi", "0", "0",
              "0", "0", ".2*bi2beh", "0"),
            byrow=TRUE, 4, 4)
dimnames(A) <- list(labels, labels)
A

#### Random-effects model

## Stage 1 analysis
random_1 <- tssem1(Cheung00$data, Cheung00$n, method="REM", RE.type="Diag",
                  acov="weighted")
summary(random_1)

## Stage 2 analysis
random_2 <- tssem2(random_1, Amatrix=A, Smatrix=S, intervals.type="LB",
                  diag.constraints=TRUE)
summary(random_2)

## Display the model
plot(random_2, what="path")

## Display the model with the parameter estimates
plot(random_2, color="yellow")
```

```
## Load the library
library("semPlot")

## End(Not run)
```

Cheung09

A Dataset from TSSEM User's Guide Version 1.11 by Cheung (2009)

Description

Four studies were selected from the data set used by Cheung and Chan (2005; 2009). Some variables were randomly deleted to illustrate the analysis with missing data.

Usage

```
data(Cheung09)
```

Details

A list of data with the following structure:

data A list of 4 studies of correlation matrices

n A vector of sample sizes

Source

Cheung, M. W.-L. (2009). TSSEM: A LISREL syntax generator for two-stage structural equation modeling (Version 1.11) [Computer software]. Retrieved from <http://courses.nus.edu.sg/course/psycwlm/internet/tssem.zip>.

References

Cheung, M. W.-L., & Chan, W. (2005). Meta-analytic structural equation modeling: A two-stage approach. *Psychological Methods*, **10**, 40-64.

Cheung, M. W.-L., & Chan, W. (2009). A two-stage approach to synthesizing covariance matrices in meta-analytic structural equation modeling. *Structural Equation Modeling*, **16**, 28-53.

Examples

```
## Not run:
data(Cheung09)

#### Fixed-effects model: Stage 1 analysis
fixed1 <- tssem1(Cheung09$data, Cheung09$n, method="FEM")
summary(fixed1)

## Prepare a model implied matrix
## Factor correlation matrix
```

```

Phi <- create.mxMatrix( c("0.3*corf2f1","0.3*corf3f1","0.3*corf3f2"),
                        type="Stand", as.mxMatrix=FALSE )
## Error variances
Psi <- create.mxMatrix( paste("0.2*e", 1:9, sep=""), type="Diag",
                        as.mxMatrix=FALSE )

## Create Smatrix
S1 <- bdiagMat(list(Psi, Phi))
## dimnames(S1)[[1]] <- dimnames(S1)[[2]] <- c(paste("x",1:9,sep=""),
##                                             paste("f",1:3,sep=""))
## S1
S1 <- as.mxMatrix(S1)

## Factor loadings
Lambda <- create.mxMatrix( c(".3*f1x1",".3*f1x2",".3*f1x3",rep(0,9),
                             ".3*f2x4",".3*f2x5",".3*f2x6",".3*f2x7",
                             rep(0,9),".3*f3x8",".3*f3x9"), type="Full",
                           ncol=3, nrow=9, as.mxMatrix=FALSE )
Zero1 <- matrix(0, nrow=9, ncol=9)
Zero2 <- matrix(0, nrow=3, ncol=12)

## Create Amatrix
A1 <- rbind( cbind(Zero1, Lambda),
            Zero2 )
## dimnames(A1)[[1]] <- dimnames(A1)[[2]] <- c(paste("x",1:9,sep=""),
##                                             paste("f",1:3,sep=""))
## A1
A1 <- as.mxMatrix(A1)

## Create Fmatrix
F1 <- create.Fmatrix(c(rep(1,9), rep(0,3)))

#### Fixed-effects model: Stage 2 analysis
fixed2 <- tssem2(fixed1, Amatrix=A1, Smatrix=S1, Fmatrix=F1,
                intervals.type="LB")
summary(fixed2)

## Display the model
plot(fixed2, what="path")

## Display the model with the parameter estimates
plot(fixed2, latNames=c("f1", "f2", "f3"), edge.label.cex=0.8,
     color="yellow")

## End(Not run)

```

coef

Extract Parameter Estimates from various classes.

Description

It extracts the parameter estimates from objects of various classes.

Usage

```
## S3 method for class 'tssem1FEM'
coef(object, ...)
## S3 method for class 'tssem1FEM.cluster'
coef(object, ...)
## S3 method for class 'tssem1REM'
coef(object, select = c("all", "fixed", "random"), ...)
## S3 method for class 'wls'
coef(object, ...)
## S3 method for class 'wls.cluster'
coef(object, ...)
## S3 method for class 'meta'
coef(object, select = c("all", "fixed", "random"), ...)
## S3 method for class 'meta3LFIML'
coef(object, select = c("all", "fixed", "random", "allX"), ...)
## S3 method for class 'reml'
coef(object, ...)
## S3 method for class 'MxRAMModel'
coef(object, ...)
## S3 method for class 'osmasem'
coef(object, select=c("fixed", "all", "random"), ...)
```

Arguments

| | |
|--------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| object | An object returned from either class <code>tssem1FEM</code> , class <code>tssem1FEM.cluster</code> , class <code>tssem1REM</code> , class <code>wls</code> , class <code>wls.cluster</code> , class <code>meta</code> , class <code>reml</code> or class <code>MxRAMModel</code> |
| select | Select all for both fixed- and random-effects parameters, fixed for the fixed-effects parameters or random for the random-effects parameters. For <code>meta3LFIML</code> objects, <code>allX</code> is used to extract all parameters including the predictors and auxiliary variables. |
| ... | Further arguments; currently none is used |

Value

Parameter estimates for both fixed-effects (if any) and random-effects (if any)

Note

`coef.MxRAMModel` is simply a wrapper of `omxGetParameters`. Extra arguments will be passed to it

Author(s)

Mike W.-L. Cheung <mikewlcheung@nus.edu.sg>

See Also

[tssem1](#), [wls](#), [meta](#), [reml](#), [omxGetParameters](#), [osmasem](#)

Examples

```
## Random-effects meta-analysis
model1 <- meta(y=yi, v=vi, data=Hox02)
coef(model1)

## Fixed-effects only
coef(model1, select="fixed")
```

Cooke16

Correlation Matrices from Cooke et al. (2016)

Description

The data set includes correlation matrices on using the theory of planned behavior to predict alcohol consumption reported by Cooke et al. (2016).

Usage

```
data(Cooke16)
```

Details

A list of data with the following structure:

data A list of correlation matrices. The variables are *SN* (subjective norm), *ATT* (attitude), *PBC* (perceived behavior control), *BI* (behavioral intention), and *BEH* (behavior).

n A vector of sample sizes.

MeanAge Mean age of the participants except for Ajzen and Sheikh (2013), which is the median age, and Glassman, et al. (2010a) to Glassman, et al. (2010d), which are based on the range of 18 to 24.

Female Percentage of female participants.

Source

Cooke, R., Dahdah, M., Norman, P., & French, D. P. (2016). How well does the theory of planned behaviour predict alcohol consumption? A systematic review and meta-analysis. *Health Psychology Review*, **10**(2), 148-167.

References

Cheung, M. W.-L., & Hong, R. Y. (2017). Applications of meta-analytic structural equation modeling in health psychology: Examples, issues, and recommendations. *Health Psychology Review*, **11**, 265-279.

Examples

```

## Not run:
## Check whether the correlation matrices are valid (positive definite)
Cooke16$data[is.pd(Cooke16$data)==FALSE]

## Since the correlation matrix in Study 3 is not positive definite,
## we exclude it in the following analyses
my.data <- Cooke16$data[-3]
my.n <- Cooke16$n[-3]

## Show the no. of studies per correlation
pattern.na(my.data, show.na = FALSE)

## Show the total sample sizes per correlation
pattern.n(my.data, my.n)

## Stage 1 analysis
## Random-effects model
random1 <- tssem1(my.data, my.n, method="REM", RE.type="Diag", acov="weighted")
summary(random1)

A1 <- create.mxMatrix(c(0,0,0,0,0,
                        0,0,0,0,0,
                        0,0,0,0,0,
                        "0.2*SN2BI", "0.2*ATT2BI", "0.2*PBC2BI", 0,0,
                        0,0, "0.2*PBC2BEH", "0.2*BI2BEH", 0),
                      type="Full", ncol=5, nrow=5,
                      byrow=TRUE, as.mxMatrix=FALSE)

## This step is not necessary but it is useful for inspecting the model.
dimnames(A1)[[1]] <- dimnames(A1)[[2]] <- colnames(Cooke16$data[[1]])

## Display A1
A1

S1 <- create.mxMatrix(c(1,
                        "0.1*ATT_SN", 1,
                        "0.1*PBC_SN", "0.1*PBC_ATT", 1,
                        0, 0, 0, "0.5*VarBI",
                        0, 0, 0, 0, "0.5*VarBEH"),
                      type = "Symm", ncol=5, nrow=5,
                      byrow=TRUE, as.mxMatrix=FALSE)

dimnames(S1)[[1]] <- dimnames(S1)[[2]] <- colnames(Cooke16$data[[1]])
S1

## Stage 2 analysis
random2 <- tssem2(random1, Amatrix=A1, Smatrix=S1, diag.constraints=FALSE,
                  intervals.type="LB")
summary(random2)

## Display the model

```

```
plot(random2, what="path")

## Display the model with the parameter estimates
plot(random2, color="yellow")

## End(Not run)
```

Cooper03

Selected effect sizes from Cooper et al. (2003)

Description

Fifty-six effect sizes from 11 districts from Cooper et al. (2003) were reported by Konstantopoulos (2011).

Usage

```
data(Cooper03)
```

Details

The variables are:

District District ID

Study Study ID

y Effect size

v Sampling variance

Year Year of publication

Source

Cooper, H., Valentine, J. C., Charlton, K., & Melson, A. (2003). The Effects of Modified School Calendars on Student Achievement and on School and Community Attitudes. *Review of Educational Research*, **73**(1), 1-52. doi:10.3102/00346543073001001

References

Konstantopoulos, S. (2011). Fixed effects and variance components estimation in three-level meta-analysis. *Research Synthesis Methods*, **2**, 61-76. doi:10.1002/jrsm.35

Examples

```

## Not run:
data(Cooper03)

#### ML estimation method
## No predictor
summary( model1 <- meta3L(y=y, v=v, cluster=District, data=Cooper03) )

## Show all heterogeneity indices and their 95% confidence intervals
summary( meta3L(y=y, v=v, cluster=District, data=Cooper03,
               intervals.type="LB", I2=c("I2q", "I2hm", "I2am", "ICC")) )

## Year as a predictor
summary( meta3L(y=y, v=v, cluster=District, x=scale(Year, scale=FALSE),
               data=Cooper03, model.name="Year as a predictor") )

## Equality of level-2 and level-3 heterogeneity
summary( model2 <- meta3L(y=y, v=v, cluster=District, data=Cooper03,
               RE2.constraints="0.2*EqTau2",
               RE3.constraints="0.2*EqTau2",
               model.name="Equal Tau2") )

## Compare model2 vs. model1
anova(model1, model2)

#### REML estimation method
## No predictor
summary( reml3L(y=y, v=v, cluster=District, data=Cooper03) )

## Level-2 and level-3 variances are constrained equally
summary( reml3L(y=y, v=v, cluster=District, data=Cooper03,
               RE.equal=TRUE, model.name="Equal Tau2") )

## Year as a predictor
summary( reml3L(y=y, v=v, cluster=District, x=scale(Year, scale=FALSE),
               data=Cooper03, intervals.type="LB") )

## Handling missing covariates with FIML
## Create 20/56 MCAR data in Year
set.seed(10000)
Year_MCAR <- Cooper03$Year
Year_MCAR[sample(56, 20)] <- NA
summary( meta3LFIML(y=y, v=v, cluster=District, x2=scale(Year_MCAR, scale=FALSE),
                  data=Cooper03, model.name="NA in Year_MCAR") )

## End(Not run)

```

Description

It converts the correlation or covariance matrices into a dataframe of correlations or covariances with their asymptotic sampling covariance matrices. It uses the `asyCov` at the backend.

Usage

```
Cor2DataFrame(x, n, v.na.replace = TRUE, row.names.unique = FALSE,
             cor.analysis = TRUE, acov="weighted", append.vars=TRUE,
             asyCovOld=FALSE, ...)
```

Arguments

| | |
|-------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>x</code> | A list of data with correlation/covariance matrix in <code>x\$data</code> and sample sizes <code>x\$n</code> . Additional variables in <code>x</code> can be attached. |
| <code>n</code> | If <code>x</code> is a list of correlation matrices without <code>x\$data</code> and <code>x\$n</code> , a vector of sample sizes <code>n</code> must be provided. |
| <code>v.na.replace</code> | Logical. Missing value is not allowed in definition variables. If it is TRUE (the default), missing value is replaced by a large value (1e10). These values are not used in the analysis. |
| <code>row.names.unique</code> | Logical, If it is FALSE (the default), unique row names are not created. |
| <code>cor.analysis</code> | Logical. The output is either a correlation or covariance matrix. |
| <code>acov</code> | If it is weighted, the average correlation/covariance matrix is calculated based on the weighted mean with the sample sizes. The average correlation/covariance matrix is used to calculate the sampling variance-covariance matrices. |
| <code>append.vars</code> | Whether to append the additional variables to the output dataframe. |
| <code>asyCovOld</code> | Whether to use the old version of <code>asyCov</code> . See asyCov . |
| <code>...</code> | Further arguments to be passed to asyCov . |

Value

A list of components: (1) a data frame of correlations or covariances with their sampling covariance matrices; (2) a vector of sample sizes; (3) labels of the correlations; and (3) labels of their sampling covariance matrices.

Author(s)

Mike W.-L. Cheung <mikewlcheung@nus.edu.sg>

See Also

[asyCov](#), [osmasem](#), [create.vechsR](#), [create.Tau2](#), [create.V](#)

Examples

```
## Not run:
## Provide a list of correlation matrices and a vector of sample sizes as the inputs
my.df1 <- Cor2DataFrame(Nohe15A1$data, Nohe15A1$n)

## Add Lag time as a variable
my.df1$data <- data.frame(my.df1$data, Lag=Nohe15A1$Lag, check.names=FALSE)

## Data
my.df1$data

## Sample sizes
my.df1$n

## ylabels
my.df1$ylabels

## vlabels
my.df1$vlabels

#### Simplified version to do it
my.df2 <- Cor2DataFrame(Nohe15A1)

## End(Not run)
```

create.Fmatrix *Create an F matrix to select observed variables*

Description

It creates an F matrix to select observed variables for wls function.

Usage

```
create.Fmatrix(x, name, as.mxMatrix=TRUE, ...)
```

Arguments

| | |
|-------------|-----------------------------------------------------------------------------------------------------------|
| x | A vector of logical type |
| name | Name of the matrix. If it is missing, "Fmatrix" will be used. |
| as.mxMatrix | Logical. If it is TRUE, the output is a matrix of MxMatrix-class. If it is FALSE, it is a numeric matrix. |
| ... | Not used. |

Author(s)

Mike W.-L. Cheung <mikewlcheung@nus.edu.sg>

See Also

[as.mxMatrix](#), [create.mxMatrix](#), [wls](#)

Examples

```
## Select the first 3 variables while the other 2 variables are latent.
create.Fmatrix(c(1,1,1,0,0))
# FullMatrix 'Fmatrix'
#
# @labels: No labels assigned.
#
# @values
#      [,1] [,2] [,3] [,4] [,5]
# [1,]  1   0   0   0   0
# [2,]  0   1   0   0   0
# [3,]  0   0   1   0   0
#
# @free: No free parameters.
#
# @lbound: No lower bounds assigned.
#
# @ubound: No upper bounds assigned.

create.Fmatrix(c(1,1,1,0,0), as.mxMatrix=FALSE)
#      [,1] [,2] [,3] [,4] [,5]
# [1,]  1   0   0   0   0
# [2,]  0   1   0   0   0
# [3,]  0   0   1   0   0
```

create.modMatrix *Create a moderator matrix used in OSMASEM*

Description

It creates a moderator matrix used in OSMASEM.

Usage

```
create.modMatrix(RAM, output=c("A", "S"), mod)
```

Arguments

| | |
|--------|---------------------------------------------------------------------------------------------------|
| RAM | A RAM object including a list of matrices of the model returned from lavaan2RAM . |
| output | Whether the output is an "A" or "S" matrix. |
| mod | A string of moderator in the dataset. |

Value

A character matrix.

Author(s)

Mike W.-L. Cheung <mikewlcheung@nus.edu.sg>

Examples

```
## A multiple regression model
model <- "y ~ x1 + x2
         x1 ~~ 1*x1
         x2 ~~ 1*x2
         x1 ~~ x2"

## RAM specification
RAM <- lavaan2RAM(model, obs.variables=c("y", "x1", "x2"))

## Create a moderator matrix on A with "meanAge" as the moderator.
A1 <- create.modMatrix(RAM=RAM, output="A", mod="meanAge")
A1

## Create a moderator matrix on S with "meanAge" as the moderator.
S1 <- create.modMatrix(RAM=RAM, output="S", mod="meanAge")
S1
```

create.mxMatrix

Create a Vector into MxMatrix-class

Description

It converts a vector into MxMatrix-class via mxMatrix.

Usage

```
create.mxMatrix(x, type=c("Full","Symm","Diag","Stand"), ncol=NA,
               nrow=NA, as.mxMatrix=TRUE, byrow=FALSE, ...)
```

Arguments

| | |
|-------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x | A character or numeric vector |
| type | Matrix type similar to those listed in mxMatrix |
| ncol | The number of columns. It is necessary when type="Full". It is ignored and determined by the length of x for the other types of matrices. |
| nrow | The number of rows. It is necessary when type="Full". It is ignored and determined by the length of x for the other types of matrices. |
| as.mxMatrix | Logical. If it is TRUE, the output is a matrix of MxMatrix-class. If it is FALSE, it is a numeric matrix. |
| byrow | Logical. If FALSE (the default) the matrix is filled by columns, otherwise the matrix is filled by rows. |
| ... | Further arguments to be passed to mxMatrix . Please note that type, nrow, ncol, values, free and labels will be created automatically. Thus, these arguments except labels should be avoided in ... |

Details

If there are non-numeric values in `x`, they are treated as the labels of the free parameters. If an "*" is present, the numeric value on the left-hand side will be treated as the starting value for a free parameter or a fixed value for a fixed parameter. If it is a matrix of numeric values, there are no free parameters in the output matrix. `nrow` and `ncol` will be calculated from the length of `x` unless `type="Full"` is specified.

Value

A `MxMatrix-class` object with the same dimensions as `x`

Author(s)

Mike W.-L. Cheung <mikewlcheung@nus.edu.sg>

See Also

[mxMatrix](#), [create.mxMatrix](#), [create.Fmatrix](#)

Examples

```
## a and b are free parameters with starting values and labels
(a1 <- c(1:4, "5*a", 6, "7*b", 8, 9))

(mat1 <- create.mxMatrix(a1, ncol=3, nrow=3, name="mat1"))

## Arrange the elements by row
(mat2 <- create.mxMatrix(a1, ncol=3, nrow=3, as.mxMatrix=FALSE, byrow=TRUE))

(a3 <- c(1:3, "4*f4", "5*f5", "6*f6"))

(mat3 <- create.mxMatrix(a3, type="Symm", name="mat3"))

## Create character matrix
(mat4 <- create.mxMatrix(a3, type="Symm", as.mxMatrix=FALSE))

## Arrange the elements by row
(mat5 <- create.mxMatrix(a3, type="Symm", as.mxMatrix=FALSE, byrow=TRUE))

(mat6 <- create.mxMatrix(a3, type="Diag", lbound=6:1, name="mat6"))
```

create.mxModel

Create an mxModel

Description

It creates a `mxModel` from a RAM object.

Usage

```
create.mxModel(model.name="mxModel", RAM=NULL, data=NULL,
               Cov=NULL, means=NULL, numObs,
               intervals.type = c("z", "LB"), startvalues=NULL,
               mxModel.Args=NULL, run=TRUE, mxTryHard=FALSE,
               silent=TRUE, ...)
```

Arguments

| | |
|----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| model.name | A string for the model name in mxModel . |
| RAM | A RAM object including a list of matrices of the model returned from lavaan2RAM . |
| data | A data frame or matrix of data. |
| Cov | A covariance matrix may also be used if data==NULL. |
| means | A named vector of means (options) if Cov is used. |
| numObs | If Cov is used, a sample size must be provided. |
| intervals.type | Either z (default if missing) or LB. If it is z, it calculates the 95% confidence intervals (CIs) based on the estimated standard error. If it is LB, it calculates the 95% likelihood-based CIs on the parameter estimates. |
| startvalues | A list of starting values for the free parameters. |
| mxModel.Args | A list of arguments passed to mxModel . |
| run | Logical. If FALSE, only return the mx model without running the analysis. |
| mxTryHard | If TRUE, call mxTryHard to run the analysis. If FALSE, call mxRun to run the analysis. |
| silent | Logical. An argument is passed to either mxRun or mxTryHard |
| ... | Further arguments will be passed to either mxRun or mxTryHard |

Value

An object of class `mxModel`

Author(s)

Mike W.-L. Cheung <mikewlcheung@nus.edu.sg>

Examples

```
## Not run:
## Generate data
set.seed(100)
n <- 100
x <- rnorm(n)
y <- 0.5*x + rnorm(n, mean=0, sd=sqrt(1-0.5^2))
my.df <- data.frame(y=y, x=x)

## A regression model
model <- "y ~ x # Regress y on x"
```

```

      y ~ 1 # Intercept of y
      x ~ 1 # Mean of x"
plot(model)

RAM <- lavaan2RAM(model, obs.variables=c("y", "x"))

my.fit <- create.mxModel(RAM=RAM, data=my.df)
summary(my.fit)

## A meta-analysis
model <- "f =~ 1*yi
      f ~ mu*1      ## Average effect
      f ~~ tau2*f   ## Heterogeneity variance
      yi ~~ data.vi*yi ## Known sampling variance"
plot(model)

## Do not standardize the latent variable (f): std.lv=FALSE
RAM <- lavaan2RAM(model, obs.variables="yi", std.lv=FALSE)

## Use likelihood-based CI
my.fit <- create.mxModel(RAM=RAM, data=Hox02, intervals="LB")
summary(my.fit)

## End(Not run)

```

| | |
|-------------|-------------------------------------------------------------------------------|
| create.Tau2 | <i>Create a variance component of the heterogeneity of the random effects</i> |
|-------------|-------------------------------------------------------------------------------|

Description

It creates variance component of the heterogeneity of the random effects by decomposing the variance component into matrices of correlation and standard deviations.

Usage

```

create.Tau2(RAM, no.var, Tau1.labels=seq(no.var),
            RE.type = c("Diag", "Symm", "Zero", "User"),
            level=c("single", "between", "within"),
            RE.User=NULL, Transform = c("expLog", "sqSD"),
            RE.startvalues=0.05)

```

Arguments

| | |
|-------------|----------------------------------------------------------------------------------------------------------------------------|
| RAM | The RAM model for testing. no.var is calculated from it. |
| no.var | If RAM is missing, the user has to specify the no.var argument. It represents the no.var by no.var of the random effects). |
| Tau1.labels | Parameter labels in Tau1. The default is Tau1_1, Tau1_2, etc. |

| | |
|----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| RE.type | Either "Diag", "Symm", "Zero" or "User". If it is "Diag" (the default if missing), a diagonal matrix is used for the random effects meaning that the random effects are independent. If it is "Symm", a symmetric matrix is used for the random effects on the covariances among the correlation (or covariance) vectors. If it is "Zero", a zero matrix is assumed on the variance component of the random effects. If it is "User", users have to specify the RE.User argument. |
| level | whether it is for single-level, between-, or within-level analyses. The only difference are the names of the matrices. |
| RE.User | It represents the no.var by no.var symmetric matrix of TRUE or FALSE for the variance component. If the elements are FALSE, they are fixed at 0. |
| Transform | Either "expLog" or "sqSD". If it is "expLog", the variances are estimated by applying a log and exp transformation. If it is "sqSD", the variances are estimated by applying a square on the SD. The transformation may improve the estimation when the heterogeneity is small or close to zero. |
| RE.startvalues | Starting values for the variances. |

Value

A list of `MxMatrix`-class. The variance component is computed in `Tau2`.

Author(s)

Mike W.-L. Cheung <mikewlcheung@nus.edu.sg>

See Also

[osmasem](#), [create.V](#), [create.vechsR](#)

Examples

```
## Not run:
T0 <- create.Tau2(no.var=4, RE.type="Diag", Transform="expLog", RE.startvalues=0.05)
T0

T1 <- create.Tau2(no.var=4, Tau1.labels=c("a", "b", "c", "d"))
T1

## End(Not run)
```

create.V

Create a V-known matrix

Description

It creates a V-known matrix of the sampling covariance matrix using definition variables.

Usage

```
create.V(x, type = c("Symm", "Diag", "Full"), as.mxMatrix = TRUE)
```

Arguments

x A character vector of variable names of the sampling covariance matrix.

type Either "Symm", "Diag" or "Full". Suppose the number of variables is p , the numbers of variable names for "Symm", "Diag", and "Full" are $p(p-1)/2$, p , and $p * p$, respectively. The elements are arranged in a column major.

as.mxMatrix Logical. Whether to convert the output into MxMatrix-class.

Value

A list of MxMatrix-class. The V-known sampling covariance matrix is computed in V.

Author(s)

Mike W.-L. Cheung <mikewlcheung@nus.edu.sg>

See Also

[osmasem](#), [create.Tau2](#), [create.vechsR](#)

Examples

```
## Not run:
my.df <- Cor2DataFrame(Nohe15A1)

## Create known sampling variance covariance matrix
V0 <- create.V(my.df$vlabels)
V0

## End(Not run)
```

| | |
|---------------|-------------------------------------------------------------------------------------|
| create.vechsR | <i>Create a model implied correlation matrix with implicit diagonal constraints</i> |
|---------------|-------------------------------------------------------------------------------------|

Description

It creates implicit diagonal constraints on the model implied correlation matrix by treating the error variances as functions of other parameters.

Usage

```
create.vechsR(A0, S0, F0 = NULL, Ax = NULL, Sx = NULL, A.lbound=NULL, A.ubound=NULL)
```

Arguments

| | |
|----------|------------------------------------------------------------------------------------------------------------------|
| A0 | A Amatrix, which will be converted into MxMatrix-class via as.mxMatrix. |
| S0 | A Smatrix, which will be converted into MxMatrix-class via as.mxMatrix. |
| F0 | A Fmatrix, which will be converted into MxMatrix-class via as.mxMatrix. |
| Ax | A Amatrix of a list of Amatrix with definition variables as the moderators of the Amatrix. |
| Sx | A Smatrix of a list of Smatrix with definition variables as the moderators of the Smatrix. |
| A.lbound | A matrix of lower bound of the Amatrix. If a scalar is given, the lbound matrix will be filled with this scalar. |
| A.ubound | A matrix of upper bound of the Amatrix. If a scalar is given, the ubound matrix will be filled with this scalar. |

Value

A list of MxMatrix-class. The model implied correlation matrix is computed in impliedR and vechsR.

Note

Since A0 are the intercepts and Ax are the regression coefficients. The parameters in Ax must be a subset of those in A0.

Author(s)

Mike W.-L. Cheung <mikewlcheung@nus.edu.sg>

See Also

[osmasem](#), [create.Tau2](#), [create.V](#)

Examples

```
## Not run:
## Proposed model
model1 <- 'W2 ~ w2w*W1 + s2w*S1
          S2 ~ w2s*W1 + s2s*S1
          W1 ~~ w1WITHs1*S1
          W2 ~~ w2WITHs2*S2
          W1 ~~ 1*W1
          S1 ~~ 1*S1
          W2 ~~ Errw2*W2
          S2 ~~ Errs2*S2'

## Convert into RAM
RAM1 <- lavaan2RAM(model1, obs.variables=c("W1", "S1", "W2", "S2"))

## No moderator
```

```

M0 <- create.vechsR(A0=RAM1$A, S0=RAM1$S, F0=NULL, Ax=NULL, Sx=NULL)

## Lag (definition variable) as a moderator on the paths in the Amatrix
Ax <- matrix(c(0,0,0,0,
              0,0,0,0,
              "0*data.Lag", "0*data.Lag", 0,0,
              "0*data.Lag", "0*data.Lag", 0,0),
            nrow=4, ncol=4, byrow=TRUE)

M1 <- create.vechsR(A0=RAM1$A, S0=RAM1$S, F0=NULL, Ax=Ax, Sx=NULL)

## Lag (definition variable) as a moderator on the correlation in the Smatrix
Sx <- matrix(c(0, "0*data.Lag", 0,0,
              "0*data.Lag", 0,0,0,
              0,0,0, "0*data.Lag",
              0,0, "0*data.Lag", 0),
            nrow=4, ncol=4, byrow=TRUE)

M2 <- create.vechsR(A0=RAM1$A, S0=RAM1$S, F0=NULL, Ax=NULL, Sx=Sx)

## End(Not run)

```

 Diag

Matrix Diagonals

Description

Extract or replace the diagonal of a matrix, or construct a diagonal matrix with the same behaviors as `diag` prior to R-3.0.0.

Usage

```

Diag(x, ...)
Diag(x) <- value

```

Arguments

| | |
|--------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>x</code> | A matrix, vector or 1D array, or missing. |
| <code>...</code> | Optional dimensions (<code>nrow</code> and <code>ncol</code>) for the result when <code>x</code> is not a matrix. |
| <code>value</code> | Either a single value or a vector of length equal to that of the current diagonal. Should be of a mode which can be coerced to that of <code>x</code> . |

Details

Started from R-3.0.0, `diag(x)` returns a numeric matrix with NA in the diagonals when `x` is a character vector. Although this follows what the manual says, this breaks the metaSEM. The `Diag` has the same functions as `diag` except that `Diag(x)` works for a character vector of `x` by returning a square matrix of character "0" with `x` as the diagonals.

Note

See <http://r.789695.n4.nabble.com/Behaviors-of-diag-with-character-vector-in-R-3-0-0-td4663735.html> for the discussion.

Author(s)

Mike W.-L. Cheung <mikewlcheung@nus.edu.sg>

See Also

[diag](#)

Examples

```
v <- c("a", "b")
Diag(v)
```

Digman97

Factor Correlation Matrices of Big Five Model from Digman (1997)

Description

The data set includes fourteen studies of the factor correlation matrices of the Five-Factor Model of personality reported by Digman (1997).

Usage

```
data(Digman97)
```

Details

A list of data with the following structure:

data A list of 14 studies of correlation matrices. The variables are *Agreeableness* (A), *Conscientiousness* (C), *Emotional Stability* (ES), *Extraversion* (E) and *Intellect* (I)

n A vector of sample sizes

cluster Types of participants of the studies

Source

Digman, J.M. (1997). Higher-order factors of the Big Five. *Journal of Personality and Social Psychology*, **73**, 1246-1256.

References

Cheung, M. W.-L., & Chan, W. (2005). Classifying correlation matrices into relatively homogeneous subgroups: A cluster analytic approach. *Educational and Psychological Measurement*, **65**, 954-979.

Examples

```

## Not run:
Digman97

##### Fixed-effects TSSEM
fixed1 <- tssem1(Digman97$data, Digman97$n, method="FEM")
summary(fixed1)

## Factor covariance among latent factors
Phi <- matrix(c(1,"0.3*cor","0.3*cor",1), ncol=2, nrow=2)

## Error covariance matrix
Psi <- Diag(c("0.2*e1","0.2*e2","0.2*e3","0.2*e4","0.2*e5"))

## S matrix
S1 <- bdiagMat(list(Psi, Phi))

## This step is not necessary but it is useful for inspecting the model.
dimnames(S1)[[1]] <- dimnames(S1)[[2]] <- c("A","C","ES","E","I","Alpha","Beta")

## Display S1
S1

## A matrix
Lambda <-
matrix(c(".3*Alpha_A",".3*Alpha_C",".3*Alpha_ES",rep(0,5),".3*Beta_E",".3*Beta_I"),
       ncol=2, nrow=5)
A1 <- rbind( cbind(matrix(0,ncol=5,nrow=5), Lambda),
            matrix(0, ncol=7, nrow=2) )

## This step is not necessary but it is useful for inspecting the model.
dimnames(A1)[[1]] <- dimnames(A1)[[2]] <- c("A","C","ES","E","I","Alpha","Beta")

## Display A1
A1

## F matrix to select the observed variables
F1 <- create.Fmatrix(c(1,1,1,1,1,0,0), as.mxMatrix=FALSE)

## Display F1
F1

#####
## Alternative model specification in lavaan model syntax
model <- "## Factor loadings
         Alpha~A+C+ES
         Beta~E+I
         ## Factor correlation
         Alpha~~Beta"

## Display the model
plot(model)

```

```

RAM <- lavaan2RAM(model, obs.variables=c("A","C","ES","E","I"),
                 A.notation="on", S.notation="with")
RAM

A1 <- RAM$A
S1 <- RAM$S
F1 <- RAM$F

#####
fixed2 <- tssem2(fixed1, Amatrix=A1, Smatrix=S1, Fmatrix=F1,
                 model.name="TSSEM2 Digman97")
summary(fixed2)

## Display the model with the parameter estimates
plot(fixed2)

#### Fixed-effects TSSEM with several clusters
#### Create a variable for different samples
#### Younger participants: Children and Adolescents
#### Older participants: others
cluster <- ifelse(Digman97$cluster %in% c("Children","Adolescents"),
                 yes="Younger participants", no="Older participants")

#### Show the cluster
cluster

## Example of Fixed-effects TSSEM with several clusters
fixed1.cluster <- tssem1(Digman97$data, Digman97$n, method="FEM",
                       cluster=cluster)
summary(fixed1.cluster)

fixed2.cluster <- tssem2(fixed1.cluster, Amatrix=A1, Smatrix=S1, Fmatrix=F1)
#### Please note that the estimates for the younger participants are problematic.
summary(fixed2.cluster)

## Setup two plots
layout(t(1:2))

## Plot the first group
plot(fixed2.cluster[[1]])
title("Younger participants")

## Plot the second group
plot(fixed2.cluster[[2]])
title("Older participants")

#### Random-effects TSSEM with random effects on the diagonals
random1 <- tssem1(Digman97$data, Digman97$n, method="REM",
                 RE.type="Diag")
summary(random1)

random2 <- tssem2(random1, Amatrix=A1, Smatrix=S1, Fmatrix=F1)

```

```
summary(random2)

## Display the model with the parameter estimates
plot(random2, color="green")

## End(Not run)
```

Gleser94

Two Datasets from Gleser and Olkin (1994)

Description

It includes two datasets in multiple-treatment studies and multiple-endpoint studies reported by Gleser and Olkin (1994).

Usage

```
data("Gleser94")
```

Format

A list of two data frames.

MTS A data frame of multiple-treatment studies.

MES A data frame of multiple-endpoint studies.

Source

Gleser, L. J., & Olkin, I. (1994). Stochastically dependent effect sizes. In H. Cooper & L. V. Hedges (Eds.), *The handbook of research synthesis*. (pp. 339-355). New York: Russell Sage Foundation.

See Also

[smdMTS](#), [smdMES](#)

Examples

```
## Not run:
data(Gleser94)

#### Multiple-treatment studies
Gleser94$MTS

## Assuming homogeneity of variances
my.MTS <- t(apply(Gleser94$MTS, MARGIN=1,
  function(x)
    smdMTS(m=x[c("Mean.C", "Mean.E1", "Mean.E2", "Mean.E3", "Mean.E4", "Mean.E5")],
            v=x[c("SD.C", "SD.E1", "SD.E2", "SD.E3", "SD.E4", "SD.E5")]^2,
            n=x[c("N.C", "N.E1", "N.E2", "N.E3", "N.E4", "N.E5")]),
```

```

                                homogeneity="variance", list.output=FALSE)))

## Fixed-effects multivariate meta-analysis
fit.MTS <- meta(y=my.MTS[, 1:5],
               v=my.MTS[, 6:20],
               RE.constraints = diag(0, ncol=5, nrow=5),
               model.name="MTS")
summary(fit.MTS)

#### Multiple-endpoint studies
Gleser94$MES

## Calculate the sampling variances and covariance and amend into the data set
Gleser94$MES$Uncoached.V11 <- with(Gleser94$MES, SD.Uncoached.Math^2)
Gleser94$MES$Uncoached.V21 <- with(Gleser94$MES,
                                   SD.Uncoached.Math*Cor.Math.Verbal*SD.Uncoached.Verbal)
Gleser94$MES$Uncoached.V22 <- with(Gleser94$MES, SD.Uncoached.Verbal^2)

Gleser94$MES$Coached.V11 <- with(Gleser94$MES, SD.Coached.Math^2)
Gleser94$MES$Coached.V21 <- with(Gleser94$MES,
                                   SD.Coached.Math*Cor.Math.Verbal*SD.Coached.Verbal)
Gleser94$MES$Coached.V22 <- with(Gleser94$MES, SD.Coached.Verbal^2)

## Assuming homogeneity of covariance matrices
my.MES <- t(apply(Gleser94$MES, MARGIN=1,
                 function(x)
                   smdMES(m1=x[c("Mean.Uncoached.Math", "Mean.Uncoached.Verbal")],
                          m2=x[c("Mean.Coached.Math", "Mean.Coached.Verbal")],
                          V1=vec2symMat(x[c("Uncoached.V11", "Uncoached.V21", "Uncoached.V22")]),
                          V2=vec2symMat(x[c("Coached.V11", "Coached.V21", "Coached.V22")]),
                          n1=x["N.Uncoached"],
                          n2=x["N.Coached"],
                          homogeneity="covariance", list.output=FALSE)))

## Fixed-effects multivariate meta-analysis
fit.MES <- meta(y=my.MES[, 1:2],
               v=my.MES[, 3:5],
               RE.constraints = diag(0, ncol=2, nrow=2),
               model.name="MES")
summary(fit.MES)

## End(Not run)

```

Description

The data set includes 113 correlation matrices on the Rosenberg Self-Esteem Scale reported by Gnambs, Scharl, and Schroeders (2018). Thirty-six studies were based on the reported correlation

matrices (CorMat=1) whereas the correlation matrices of the other 77 studies were calculated from the reported factor loadings.

Usage

data(Gnambs18)

Details

A list of data with the following structure:

data A list of 113 correlation matrices. The variable names are from *I1* to *I10*.

n A vector of sample sizes.

Year The year of publications.

Country The country of studies conducted.

Language The language used in the studies.

Publication Whether the studies were published (1) or unpublished (0).

MeanAge Mean age of the participants.

FemaleProp Proportion of the female participants.

Individualism Individualism score of the country.

CorMat Whether the correlation matrices are obtained from the original studies (1) or reproduced from the factor loadings (0).

Source

Gnambs, T., Scharl, A., & Schroeders, U. (2018). The structure of the Rosenberg Self-Esteem Scale. *Zeitschrift Fur Psychologie*, **226**(1), 14-29. <https://doi.org/10.1027/2151-2604/a000317>

HedgesOlkin85

Effects of Open Education Reported by Hedges and Olkin (1985)

Description

Effects of open education on attitude toward school and on reading achievement reported by Hedges and Olkin (1985).

Usage

data(HedgesOlkin85)

Details

The variables are:

study Study number

d_att Standardized mean difference on *attitude*

d_ach Standardized mean difference on *achievement*

var_att Sampling variance of the effect size of *attitude*

cov_att_ach Sampling covariance between the effect sizes

var_ach Sampling variance of the effect size of *achievement*

Source

Hedges, L. V., & Olkin, I. (1985). *Statistical methods for meta-analysis*. Orlando, FL: Academic Press.

References

Cheung, M. W.-L. (2010). Fixed-effects meta-analyses as multiple-group structural equation models. *Structural Equation Modeling*, **17**, 481-509.

Examples

```
data(HedgesOlkin85)

## Fixed-effects meta-analysis
summary( meta(y=cbind(d_att, d_ach),
                  v=cbind(var_att, cov_att_ach, var_ach),
                  data=HedgesOlkin85,
                  RE.constraints=matrix(0, nrow=2, ncol=2)) )
```

homoStat

Test the Homogeneity of Effect Sizes

Description

It tests the homogeneity of univariate and multivariate effect sizes.

Usage

```
homoStat(y, v)
```

Arguments

| | |
|----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>y</code> | A vector of effect size for univariate meta-analysis or a $k \times p$ matrix of effect sizes for multivariate meta-analysis where k is the number of studies and p is the number of effect sizes. |
| <code>v</code> | A vector of the sampling variance of the effect size for univariate meta-analysis or a $k \times p^*$ matrix of the sampling covariance matrix of the effect sizes for multivariate meta-analysis where $p^* = p(p + 1)/2$. It is arranged by column major as used by <code>vech</code> . It is assumed that there is no missing value in <code>v</code> if <code>y</code> is complete. If there are missing values in <code>v</code> due to the missingness on <code>y</code> , the missing values in <code>v</code> will be removed automatically. |

Value

| | |
|-------------------|---------------------------------------------------------------------------------------------------------------------------------------------|
| A list of | |
| <code>Q</code> | Q statistic on the null hypothesis of homogeneity of effect sizes. It has an approximate chi-square distribution under the null hypothesis. |
| <code>Q.df</code> | Degrees of freedom of the Q statistic |
| <code>pval</code> | p-value on the test of homogeneity of effect sizes |

Author(s)

Mike W.-L. Cheung <mikewlcheung@nus.edu.sg>

References

- Becker, B. J. (1992). Using results from replicated studies to estimate linear models. *Journal of Educational Statistics*, **17**, 341-362.
- Cheung, M. W.-L. (2010). Fixed-effects meta-analyses as multiple-group structural equation models. *Structural Equation Modeling*, **17**, 481-509.
- Cochran, W. G. (1954). The combination of estimates from different experiments. *Biometrics*, **10**, 101-129.

See Also

[meta](#)

Examples

```
with( Hox02, homoStat(yi, vi) )

with( HedgesOlkkin85, homoStat(y=cbind(d_att, d_ach),
  v=cbind(var_att, cov_att_ach, var_ach)) )
```


Hox02

*Simulated Effect Sizes Reported by Hox (2002)***Description**

Twenty simulated studies on standardized mean difference and one continuous study characteristic reported by Hox (2002).

Usage

```
data(Hox02)
```

Details

The variables are:

study Study number

yi Effect size (standardized mean difference)

vi Sampling variance of the effect size

weeks Duration of the experimental intervention in terms of weeks

Source

Hox, J. J. (2002). *Multilevel analysis: Techniques and applications*. Mahwah, N.J.: Lawrence Erlbaum Associates.

References

Cheung, M. W.-L. (2008). A model for integrating fixed-, random-, and mixed-effects meta-analyses into structural equation modeling. *Psychological Methods*, **13**, 182-202.

Examples

```
## Not run:
data(Hox02)

#### ML estimation method
## Random-effects meta-analysis
summary( meta(y=yi, v=vi, data=Hox02, I2=c("I2q", "I2hm"), intervals.type="LB") )

## Fixed-effects meta-analysis
summary( meta(y=yi, v=vi, data=Hox02, RE.constraints=0,
             model.name="Fixed effects model") )

## Mixed-effects meta-analysis with "weeks" as a predictor
## Request likelihood-based CI
summary( meta(y=yi, v=vi, x=weeks, data=Hox02, intervals.type="LB",
             model.name="Mixed effects meta analysis with LB CI") )
```

```
#### REML estimation method
## Random-effects meta-analysis with REML
summary( VarComp <- reml(y=yi, v=vi, data=Hox02) )

## Extract the variance component
VarComp_REML <- matrix( coef(VarComp), ncol=1, nrow=1 )

## Meta-analysis by treating the variance component as fixed
summary( meta(y=yi, v=vi, data=Hox02, RE.constraints=VarComp_REML) )

## Mixed-effects meta-analysis with "weeks" as a predictor
## Request Wald CI
summary( reml(y=yi, v=vi, x=weeks, intervals.type="z",
              data=Hox02, model.name="REML with LB CI" ) )

## End(Not run)
```

 Hunter83

Fourteen Studies of Correlation Matrices reported by Hunter (1983)

Description

This dataset includes fourteen studies of Correlation Matrices reported by Hunter (1983)

Usage

```
data(Hunter83)
```

Details

A list of data with the following structure:

data A list of 14 studies of correlation matrices. The variables are *Ability*, *Job knowledge*, *Work sample* and *Supervisor rating*

n A vector of sample sizes

Source

Hunter, J. E. (1983). A causal analysis of cognitive ability, job knowledge, job performance, and supervisor ratings. In F. Landy, S. Zedeck, & J. Cleveland (Eds.), *Performance Measurement and Theory* (pp. 257-266). Hillsdale, NJ: Erlbaum.

Examples

```

## Not run:
data(Hunter83)

#### Fixed-effects model
## First stage analysis
fixed1 <- tssem1(Hunter83$data, Hunter83$n, method="FEM",
                model.name="TSSEM1 fixed effects model")
summary(fixed1)

#### Second stage analysis
## Model without direct effect from Ability to Supervisor
## A1 <- create.mxMatrix(c(0,"0.1*A2J","0.1*A2W",0,0,0,"0.1*J2W","0.1*J2S",
##                        0,0,0,"0.1*W2S",0,0,0,0),
##                        type="Full", ncol=4, nrow=4, as.mxMatrix=FALSE)

## ## This step is not necessary but it is useful for inspecting the model.
## dimnames(A1)[[1]] <- dimnames(A1)[[2]] <- c("Ability","Job","Work","Supervisor")
## A1

## S1 <- create.mxMatrix(c(1,"0.1*Var_e_J", "0.1*Var_e_W", "0.1*Var_e_S"),
##                        type="Diag", as.mxMatrix=FALSE)
## dimnames(S1)[[1]] <- dimnames(S1)[[2]] <- c("Ability","Job","Work","Supervisor")
## S1

#####
## Model specification in lavaan model syntax
## The "ind" effect can be defined within the syntax
model1 <- "## Regression paths
          Job_knowledge ~ A2J*Ability
          Work_sample ~ A2W*Ability + J2W*Job_knowledge
          Supervisor ~ J2S*Job_knowledge + W2S*Work_sample

          ## Fix the variance of Ability at 1
          Ability ~~ 1*Ability

          ## Label the error variances of the dependent variables
          Job_knowledge ~~ VarE_J*Job_knowledge
          Work_sample ~~ VarE_W*Work_sample
          Supervisor ~~ VarE_S*Supervisor

          ## Define an indirect effect
          ind := A2J*J2S+A2J*J2W*W2S+A2W*W2S"

## Display the model
plot(model1, layout="spring", sizeMan=10)

RAM1 <- lavaan2RAM(model1, obs.variables=c("Ability","Job_knowledge",
                                           "Work_sample","Supervisor"))
RAM1

#####

```

```

fixed2 <- tssem2(fixed1, RAM=RAM1, intervals.type="z",
                 diag.constraints=FALSE,
                 model.name="TSSEM2 fixed effects model")
summary(fixed2)

## Display the model with the parameter estimates
plot(fixed2, layout="spring")

## Coefficients
coef(fixed2)

## VCOV based on parametric bootstrap
vcov(fixed2)

#### Random-effects model with diagonal elements only
## First stage analysis
random1 <- tssem1(Hunter83$data, Hunter83$n, method="REM", RE.type="Diag",
                  acov="weighted", model.name="TSSEM1 random effects model")
summary(random1)

model2 <- "## Regression paths
Job_knowledge ~ A2J*Ability
Work_sample ~ A2W*Ability + J2W*Job_knowledge
Supervisor ~ J2S*Job_knowledge + W2S*Work_sample

## Fix the variance of Ability at 1
Ability ~~ 1*Ability

## Label the error variances of the dependent variables
Job_knowledge ~~ VarE_J*Job_knowledge
Work_sample ~~ VarE_W*Work_sample
Supervisor ~~ VarE_S*Supervisor"

RAM2 <- lavaan2RAM(model2, obs.variables=c("Ability", "Job_knowledge",
                                           "Work_sample", "Supervisor"))
RAM2

## Second stage analysis
## Model without direct effect from Ability to Supervisor

## The "ind" effect is defined in tssem2().
random2 <- tssem2(random1, RAM=RAM2, intervals.type="LB",
                  diag.constraints=FALSE,
                  mx.algebras=
                    list(ind=mxAlgebra(A2J*J2S+A2J*J2W*W2S+A2W*W2S, name="ind")),
                  model.name="TSSEM2 random effects model")

summary(random2)

## Display the model with the parameter estimates
plot(random2, layout="spring")

## End(Not run)

```

| | |
|----------|--------------------------------------------------------------------------------|
| impliedR | <i>Create or Generate the Model Implied Correlation or Covariance Matrices</i> |
|----------|--------------------------------------------------------------------------------|

Description

It creates or generates the model implied correlation or covariance matrices based on the RAM model specification.

Usage

```
impliedR(RAM, Amatrix, Smatrix, Fmatrix, corr=TRUE, labels, ...)
rimpliedR(RAM, Amatrix, Smatrix, Fmatrix, AmatrixSD, SmatrixSD,
           k=1, corr=TRUE, nonPD.pop=c("replace", "nearPD", "accept"))
```

Arguments

| | |
|-----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| RAM | A RAM object including a list of matrices of the model returned from lavaan2RAM . |
| Amatrix | If RAM is not specified, an Amatrix is required. An asymmetric matrix in the RAM specification with MxMatrix-class . If it is a matrix, it will be converted into MxMatrix-class by the <code>as.mxMatrix</code> function. |
| Smatrix | If RAM is not specified, an Smatrix is required. A symmetric matrix in the RAM specification with MxMatrix-class . If it is a matrix, it will be converted into MxMatrix-class by the <code>as.mxMatrix</code> function. |
| Fmatrix | A filter matrix in the RAM specification with MxMatrix-class . If it is missing, an identity matrix with the same dimensions of Smatrix will be created, which means that all variables are observed. If it is a matrix, it will be converted into MxMatrix-class by the <code>as.mxMatrix</code> function. It is not required when there is no latent variable. |
| AmatrixSD | Standard deviations (SD) of the elements in the Amatrix. If it is missing, a matrix of zero is created. |
| SmatrixSD | Standard deviations (SD) of the elements in the Smatrix. If it is missing, a matrix of zero is created. |
| k | Number of studies. |
| corr | Logical. The output is either the model implied correlation matrix or the covariance matrix. |
| labels | A character vector of the observed and latent variables with the same dimensions as that in the Amatrix and Smatrix. |
| nonPD.pop | If it is <code>replace</code> , generated non-positive definite matrices are replaced by generated new ones which are positive definite. If it is <code>nearPD</code> , they are replaced by nearly positive definite matrices by calling <code>Matrix::nearPD()</code> . If it is <code>accept</code> , they are accepted. |
| ... | Not used. |

Details

This function can be used to generate the model implied correlation matrix for the standardized parameters with the `corr=TRUE` argument. Suppose we want to calculate the population correlation matrix for a mediation model with x , m , and y . We only need to specify the population path coefficients among x , m , and y in the `Amatrix`. We do not need to specify the population error variances of m and y . We treat the error variances as unknown parameters by giving them starting values in the `Smatrix` matrix. When the covariance matrix is requested by specifying `corr=FALSE`, it simply calculates the population model covariance matrix by treating the values in `Smatrix` as the population values.

Value

A list of RAM matrices, the model implied correlation or covariance matrix of the observed variables (`SigmaObs`), of both observed and latent variables (`SigmaAll`), the minimum fit (`minFit`) which should be zero, and the status code of the optimization (`status`) which should also be zero when the optimization is fine. The last object is `mx.fit` which is the output after running the model. It can be used in the diagnosis.

Note

It is important to ensure that all the population values in `Amatrix` must be set as fixed parameters; otherwise, these values may be altered with the `corr=TRUE` argument. When there is an error or warning message about the status code, there is a high chance that some of the values in `Amatrix` are incorrectly set as free parameters.

Author(s)

Mike W.-L. Cheung <mikewlcheung@nus.edu.sg>

Examples

```
set.seed(100)

## A simple mediation model
## All are population parameters in the A matrix
A1 <- matrix(c(0, 0, 0,
              0.3, 0, 0,
              0.2, 0.4, 0), nrow=3, ncol=3, byrow=TRUE,
            dimnames=list(c("x", "m", "y"), c("x", "m", "y")))
A1

## Variance of x is fixed at 1 while the other variances are free.
S1 <- matrix(c(1, 0, 0,
              0, "0.1*ErrVarM", 0,
              0, 0, "0.1*ErrVarY"), nrow=3, ncol=3,
            dimnames=list(c("x", "m", "y"), c("x", "m", "y")))
S1

impliedR(Amatrix=A1, Smatrix=S1)
```



```
rimpliedR(Amatrix=A2, Smatrix=S2, Fmatrix=F2, AmatrixSD=A2SD,
          SmatrixSD=S2SD, k=2)
```

| | |
|----------------|----------------------------------------------------------------------------------------------------------------|
| indirectEffect | <i>Estimate the asymptotic covariance matrix of standardized or unstandardized indirect and direct effects</i> |
|----------------|----------------------------------------------------------------------------------------------------------------|

Description

It estimates the standardized or unstandardized indirect and direct effects and their asymptotic sampling covariance matrix.

Usage

```
indirectEffect(x, n, standardized = TRUE, direct.effect = TRUE, run = TRUE)
```

Arguments

| | |
|---------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x | A 3x3 correlation/covariance matrix or a list of correlation/covariance matrices. Variables are arranged as the dependent variable (y), mediator (m) and independent variable (x) |
| n | Sample size or a vector of sample sizes |
| standardized | Logical. Whether the indirect effect is standardized. |
| direct.effect | Logical. Whether the direct effect is estimated. If it is FALSE, the direct effect is fixed at zero. |
| run | Logical. If FALSE, only return the mx model without running the analysis. |

Details

Cheung (2009) estimated the standardized indirect effect and its standard error with non-linear constraints. Since OpenMx does not generate standard errors when there are non-linear constraints, Kwan and Chan's (2011) approach is used in this function. Delta method is used to calculate the asymptotic covariance matrix.

Value

A vector (or a matrix if the input is a list of matrices) of (standardized) indirect effect, standardized direct effect, and their asymptotic sampling covariance matrices

Author(s)

Mike W.-L. Cheung <mikewlcheung@nus.edu.sg>

References

Cheung, M. W.-L. (2009). Comparison of methods for constructing confidence intervals of standardized indirect effects. *Behavior Research Methods*, 41, 425-438.

Kwan, J., & Chan, W. (2011). Comparing standardized coefficients in structural equation modeling: a model reparameterization approach. *Behavior Research Methods*, 43, 730-745.

Examples

```
## A correlation matrix as input
x <- matrix(c(1, 0.4, 0.2, 0.4, 1, 0.3, 0.2, 0.3, 1), ncol=3)
dimnames(x) <- list( c("y", "m", "x"), c("y", "m", "x") )
indirectEffect(x, n=300)

## A list of correlation matrices
indirectEffect( list(x, x), n=c(300,500), standardized=FALSE )
```

 is.pd

Test Positive Definiteness of a List of Square Matrices

Description

It tests the positive definiteness of a square matrix or a list of square matrices. It returns TRUE if the matrix is positive definite. It returns FALSE if the matrix is either non-positive definite or not symmetric. Variables with NA in the diagonals will be removed before testing. It returns NA when there are missing correlations even after deleting the missing variables.

Usage

```
is.pd(x, check.aCov=FALSE, cor.analysis=TRUE, tol=1e-06)
```

Arguments

| | |
|--------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| x | A square matrix or a list of square matrices |
| check.aCov | If it is TRUE, it mirrors the checking in asyCov . |
| cor.analysis | Whether the input matrix is a correlation or a covariance matrix. It is ignored when check.aCov=FALSE. |
| tol | Tolerance (relative to largest variance) for numerical lack of positive-definiteness in x. It is adopted from mvrnorm . |

Value

If the input is a matrix, it returns TRUE, FALSE or NA. If the input is a list of matrices, it returns a list of TRUE, FALSE or NA.

Author(s)

Mike W.-L. Cheung <mikewlcheung@nus.edu.sg>

Examples

```

A <- diag(1,3)
is.pd(A)
# TRUE

B <- matrix(c(1,2,2,1), ncol=2)
is.pd(B)
# FALSE

is.pd(list(A, B))
# TRUE FALSE

C <- A
C[2,1] <- C[1,2] <- NA
is.pd(C)
# NA

```

issp05

A Dataset from ISSP (2005)

Description

Thirty-two covariance matrices on work-related attitudes were extracted from the International Social Survey Programme 2005: Work Orientation III (ISSP, 2005). Seven variables were selected for demonstration purposes. They were grouped into three constructs: *Importance of Job Prospects* measured by job security (JP1), high income (JP2), and opportunity for advancement (JP3); *Importance of Job Autonomy* measured by work independently (JA1) and decide time of work (JA2); and *Importance of Contributions to Society* measured by help other people (CS1) and a job useful to society (CS2).

Usage

```
data(issp05)
```

Details

A list of data with the following structure:

data A list of 32 covariance matrices

n A vector of sample sizes

Author(s)

Mike W.-L. Cheung <mikewlcheung@nus.edu.sg>

Source

ISSP Research Group (2007): *International Social Survey Programme 2005: Work Orientation III (ISSP 2005)*. GESIS Data Archive, Cologne. ZA4350 Data file Version 1.0.0, doi:10.4232/1.4350

See Also[issp89](#)**Examples**

```

## Not run:
data(issp05)

#### Fixed-effects TSSEM
fixed1 <- tssem1(issp05$data, issp05$n, method="FEM")
summary(fixed1)

## Prepare a model implied matrix
## Factor correlation matrix
Phi <- create.mxMatrix( c("0.3*corf2f1", "0.3*corf3f1", "0.3*corf3f2"),
                        type="Stand", as.mxMatrix=FALSE )

## Error variances
Psi <- create.mxMatrix( paste("0.2*e", 1:7, sep=""), type="Diag",
                        as.mxMatrix=FALSE )

## Create Smatrix
S1 <- bdiagMat(list(Psi, Phi))
## dimnames(S1)[[1]] <- dimnames(S1)[[2]] <- c(paste("x", 1:7, sep=""),
##                                           paste("f", 1:3, sep=""))
##
## S1
S1 <- as.mxMatrix(S1)

## Factor loadings
Lambda <- create.mxMatrix( c(".3*f1x1", ".3*f1x2", ".3*f1x3", rep(0,7),
                            ".3*f2x4", ".3*f2x5", rep(0,7), ".3*f3x6", ".3*f3x7"),
                          type="Full", ncol=3, nrow=7, as.mxMatrix=FALSE )
Zero1 <- matrix(0, nrow=7, ncol=7)
Zero2 <- matrix(0, nrow=3, ncol=10)

## Create Amatrix
A1 <- rbind( cbind(Zero1, Lambda),
            Zero2 )
## dimnames(A1)[[1]] <- dimnames(A1)[[2]] <- c(paste("x", 1:7, sep=""),
##                                           paste("f", 1:3, sep=""))
##
## A1
A1 <- as.mxMatrix(A1)

## Create Fmatrix
F1 <- create.Fmatrix(c(rep(1,7), rep(0,3)))

#### Fixed-effects model: Stage 2 analysis
fixed2 <- tssem2(fixed1, Amatrix=A1, Smatrix=S1, Fmatrix=F1,
                intervals.type="LB")
summary(fixed2)

```

```
plot(fixed2, nDigits=1)

## End(Not run)
```

issp89

A Dataset from Cheung and Chan (2005; 2009)

Description

Eleven covariance matrices on work-related attitudes were extracted from the Inter-University Consortium for Political and Social Research (1989). Nine variables were selected by Cheung and Chan (2005; 2009) for demonstration purposes. They were grouped into three constructs: *Job Prospects* measured by job security (JP1), income (JP2), and advancement opportunity (JP3); *Job Nature* measured by interesting job (JN1), independent work (JN2), help other people (JN3), and useful to society (JN4); and *Time Demand* measured by flexible working hours (TD1) and lots of leisure time (TD2).

Usage

```
data(issp89)
```

Details

A list of data with the following structure:

data A list of 11 studies of covariance matrices

n A vector of sample sizes

Author(s)

Mike W.-L. Cheung <mikewlcheung@nus.edu.sg>

Source

Inter-University Consortium for Political and Social Research. (1989). *International Social Survey Program: Work orientation*. Ann Arbor, MI: Author.

References

Cheung, M. W.-L., & Chan, W. (2005). Meta-analytic structural equation modeling: A two-stage approach. *Psychological Methods*, **10**, 40-64.

Cheung, M. W.-L., & Chan, W. (2009). A two-stage approach to synthesizing covariance matrices in meta-analytic structural equation modeling. *Structural Equation Modeling*, **16**, 28-53.

See Also

[issp05](#)

Examples

```

## Not run:
data(issp89)

#### Analysis of correlation structure in Cheung and Chan (2005)
#### Fixed-effects model: Stage 1 analysis
cor1 <- tssem1(issp89$data, issp89$n, method="FEM", cor.analysis=TRUE)
summary(cor1)

## Prepare a model implied matrix
## Factor correlation matrix
Phi <- create.mxMatrix( c("0.3*corf2f1", "0.3*corf3f1", "0.3*corf3f2"),
                        type="Stand", as.mxMatrix=FALSE )

## Error variances
Psi <- create.mxMatrix( paste("0.2*e", 1:9, sep=""), type="Diag",
                        as.mxMatrix=FALSE )

## Create Smatrix
S1 <- bdiagMat(list(Psi, Phi))
## dimnames(S1)[[1]] <- dimnames(S1)[[2]] <- c(paste("x", 1:9, sep=""),
##                                             paste("f", 1:3, sep=""))
## S1
S1 <- as.mxMatrix(S1)

## Factor loadings
Lambda <- create.mxMatrix( c(".3*f1x1", ".3*f1x2", ".3*f1x3", rep(0,9),
                             ".3*f2x4", ".3*f2x5", ".3*f2x6", ".3*f2x7",
                             rep(0,9), ".3*f3x8", ".3*f3x9"), type="Full",
                           ncol=3, nrow=9, as.mxMatrix=FALSE )
Zero1 <- matrix(0, nrow=9, ncol=9)
Zero2 <- matrix(0, nrow=3, ncol=12)

## Create Amatrix
A1 <- rbind( cbind(Zero1, Lambda),
            Zero2 )
## dimnames(A1)[[1]] <- dimnames(A1)[[2]] <- c(paste("x", 1:9, sep=""),
##                                             paste("f", 1:3, sep=""))
## A1
A1 <- as.mxMatrix(A1)

## Create Fmatrix
F1 <- create.Fmatrix(c(rep(1,9), rep(0,3)))

#### Fixed-effects model: Stage 2 analysis
cor2 <- tssem2(cor1, Amatrix=A1, Smatrix=S1, Fmatrix=F1, intervals.type="LB")
summary(cor2)

## Display the model with the parameter estimates
plot(cor2, nDigits=1)

#### Analysis of covariance structure in Cheung and Chan (2009)
#### Fixed-effects model: Stage 1 analysis

```

```

cov1 <- tssem1(issp89$data, issp89$n, method="FEM", cor.analysis=FALSE)
summary(cov1)

#### Fixed-effects model: Stage 2 analysis
cov2 <- tssem2(cov1, Amatrix=A1, Smatrix=S1, Fmatrix=F1)
summary(cov2)

## Display the model with the parameter estimates
plot(cov2, nDigits=1)

## End(Not run)

```

Jaramillo05

Dataset from Jaramillo, Mulki & Marshall (2005)

Description

A dataset of the relationship between organizational commitment (OC) and salesperson job performance (JP) from Jaramillo, Mulki & Marshall (2005).

Usage

```
data(Jaramillo05)
```

Format

A data frame with 61 observations on the following 10 variables.

Author a character vector of study

Sample_size sample size of the study

Sales sample type; either "mixed", "nonsales" or "sales"

Country a character vector of country of study

IDV Hofstede's (1997) individualism index

OC_scale scale of OC; either "Porter or Mowday", "Meyer" or "other"

OC_alpha Coefficient alpha of organizational commitment

JP_alpha Coefficient alpha of job performance

r correlation between organizational commitment and job performance

r_v sampling variance of r

Source

Jaramillo, F., Mulki, J. P., & Marshall, G. W. (2005). A meta-analysis of the relationship between organizational commitment and salesperson job performance: 25 years of research. *Journal of Business Research*, **58**(6), 705-714. doi:10.1016/j.jbusres.2003.10.004

Examples

```
## Not run:
## Research question 4.4.1
summary(meta(r, r_v, data=Jaramillo05))

## Research question 4.4.2
## Select cases with either "sales" or "nonsales"
Sales.df <- subset(Jaramillo05, Sales %in% c("sales", "nonsales"))

## Create a predictor with 1 and 0 when they are "sales" or "nonsales", respectively
predictor <- ifelse(Jaramillo05$Sales=="sales", yes=1, no=0)

## Mixed-effects meta-analysis
summary( meta(y = r, v = r_v, x = predictor, data = Jaramillo05) )

## Research question 4.4.3
summary(meta(r, r_v, x=IDV, data=Jaramillo05))

## End(Not run)
```

Kalaian96

*Multivariate effect sizes reported by Kalaian and Raudenbush (1996)***Description**

This data set includes 47 multivariate effect sizes reported by Kalaian and Raudenbush (1996, Table 1).

Usage

```
data(Kalaian96)
```

Details

A list of data with the following structure:

Study Study name

Year Year of publication

n_e Sample size of the experimental group

n_c Sample size of the control group

dSAT_V Standardized mean difference of the Scholastic Aptitude Test (SAT) on verbal

dSAT_M Standardized mean difference of SAT on math

var_V Sampling variance of dSAT_V

cov_VM Sampling covariance of dSAT_V and dSAT_M with a common correlation of 0.66

var_M Sampling variance of dSAT_M

Hr Hours of training

ETS Educational Testing Service

Study_type Either Randomized, Matched or Nonequivalent comparison

Home_work Home work

Source

Kalaian, H. A., & Raudenbush, S. W. (1996). A multivariate mixed linear model for meta-analysis. *Psychological Methods, 1*(3), 227-235. <https://doi.org/10.1037/1082-989X.1.3.227>

Examples

```
## Not run:
data(Kalaian96)

## End(Not run)
```

lavaan2RAM

Convert lavaan models to RAM models

Description

It converts models specified in lavaan model syntax to RAM models.

Usage

```
lavaan2RAM(model, obs.variables = NULL, A.notation = "ON",
            S.notation = "WITH", M.notation = "mean",
            A.start=0.1, S.start=0.5, M.start=0,
            auto.var = TRUE, std.lv = TRUE, ngroups = 1, ...)
```

Arguments

| | |
|---------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| model | A character string of model using the lavaan model syntax. |
| obs.variables | A character vector of the observed variables. The observed variables in the RAM specification will follow the order specified in obs.variables. It is important to check whether the order of the observed variables matches the order in the dataset. |
| A.notation | A character string to be used in the A matrix if the labels are not included in the lavaan model. For example, the label will be "yONx" for regressing "y" on "x". |
| S.notation | A character string to be used in the S matrix if the labels are not included in the lavaan model. For example, the label will be "yWITHx" for the covariance between "y" with "x" and "yWITHy" for the (error) variance of "y". |
| M.notation | A character string to be used in the M matrix if the labels are not included in the lavaan model. For example, the label will be "ymean" for the mean of "y" if M.notation="mean". |

| | |
|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| A.start | A numeric value of starting value for the Amatrix when the starting values are not provided. |
| S.start | A numeric value of starting value for the Smatrix when the starting values are not provided. |
| M.start | A numeric value of starting value for the Mmatrix when the starting values are not provided. |
| auto.var | Logical. If TRUE, the residual variances and the variances of exogenous latent variables are included in the model and set free. See model.syntax . |
| std.lv | Logical. If TRUE, the metric of each latent variable is determined by fixing their variances to 1.0. If FALSE, the metric of each latent variable is determined by fixing the factor loading of the first indicator to 1.0. See model.syntax . |
| ngroups | Number. The number of groups in the model. See model.syntax . |
| ... | Further arguments to be passed to model.syntax |

. Please note that `fixed.x` is set at FALSE. Thus it cannot be passed to

Details

It uses the [model.syntax](#) to do the conversion. Experimental: functions of parameters (‘:=’ in lavaan) and constraints (‘==’, ‘>’, and ‘<’ in lavaan) will be converted to mxAlgebra and mxConstraint in OpenMx. As there are differences between lavaan and OpenMx, they may not work properly.

Value

A list of RAM specification with A, S, F, and M matrices.

Author(s)

Mike W.-L. Cheung <mikewlcheung@nus.edu.sg>

See Also

[ramModel](#), [Becker92](#), [Becker09](#), [Digman97](#), [Hunter83](#), [as.mxMatrix](#), [checkRAM](#)

Examples

```
## Regression model on correlation matrix
model1 <- "## y is modelled by x1, x2, and x3
          y ~ b1*x1 + b2*x2 + b3*x3
          ## Fix the independent variables at 1
          x1 ~~ 1*x1
          x2 ~~ 1*x2
          x3 ~~ 1*x3
          ## Declare the correlations among the independent variables
          x1 ~~ x2
          x1 ~~ x3
          x2 ~~ x3
          ## Constraint"
```

```

      b3 == b1 + b2
      ## Function of parameters
      fn1 := b1*b2^b3"

## Compare the arrangements of variables with and without
## specifying the obs.variables arguments.
lavaan2RAM(model1, obs.variables=c("y", "x1", "x2", "x3"))

## Two-factor CFA model
model2 <- "f1 =~ x1 + x2 + x3
          f2 =~ x4 + x5 + x6
          ## Declare the correlation between f1 and f2
          ## and label it with cor_f1f2
          f1 ~~ cor_f1f2*f2"

lavaan2RAM(model2)

## Regression model with the mean structure
model3 <- "y ~ x
          ## Intercept of y
          y ~ 1
          ## Mean of x
          x ~ 1"

lavaan2RAM(model3)

## Multiple group regression model
## Different intercepts with a common slope
model4 <- "y ~ c(a1, a2)*1 + c(b, b)*x"

lavaan2RAM(model4, ngroups=2)

```

list2matrix

Convert a List of Symmetric Matrices into a Stacked Matrix

Description

It converts a list of symmetric matrices into a stacked matrix. Dimensions of the symmetric matrices have to be the same. It tries to preserve the dimension names if possible. Dimension names will be created if there are no dimension names in the first symmetric matrix.

Usage

```
list2matrix(x, diag = FALSE)
```

Arguments

| | |
|------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x | A list of k $p \times p$ symmetric matrices. |
| diag | Logical. If it is TRUE, <code>vech</code> is used to vectorize the (covariance) matrices. If it is FALSE, <code>vechs</code> is used to vectorize the (correlation) matrices. |

Value

A $k \times p^*$ stacked matrix where $p^* = p(p-1)/2$ for `diag=FALSE` or $p^* = p(p+1)/2$ for `diag=TRUE`.

Author(s)

Mike W.-L. Cheung <mikewlcheung@nus.edu.sg>

Examples

```
C1 <- matrix(c(1,0.5,0.4,0.5,1,0.2,0.4,0.2,1), ncol=3)
C2 <- matrix(c(1,0.4,NA,0.4,1,NA,NA,NA,NA), ncol=3)
```

```
## A list without dimension names
list2matrix(list(C1, C2))
#      x2_x1 x3_x1 x3_x2
# [1,]  0.5  0.4  0.2
# [2,]  0.4   NA   NA
```

```
dimnames(C1) <- list( c("x","y","z"), c("x","y","z") )
dimnames(C2) <- list( c("x","y","z"), c("x","y","z") )
```

```
## A list with dimension names
list2matrix(list(C1, C2))
#      y_x z_x z_y
# [1,] 0.5 0.4 0.2
# [2,] 0.4 NA  NA
```

Mak09

Eight studies from Mak et al. (2009)

Description

Eight studies from Mak et al. (2009) were reported by Cheung et al. (2012).

Usage

```
data(Mak09)
```

Format

A data frame with 8 observations on the following 10 variables.

`Study` a character vector of study

`type` a character vector

`AF.BP` a numeric vector

`Tot.BP` a numeric vector

`AF.non.BP` a numeric vector

Tot.non.BP a numeric vector
 yi a numeric vector
 vi a numeric vector
 age.mean a numeric vector
 study.duration a numeric vector

Source

Mak, A., Cheung, M. W.-L., Ho, R. C. M., Cheak, A. A. C., & Lau, C. S. (2009). Bisphosphonate and atrial fibrillation: Bayesian meta-analyses of randomized controlled trials and observational studies. *BMC Musculoskeletal Disorders*, **10**(113). doi:10.1186/1471-2474-10-113 Available at <https://bmc-musculoskeletal-disorders.biomedcentral.com/articles/10.1186/1471-2474-10-113>.

References

Cheung, M. W.-L., Ho, R. C. M., Lim, Y., & Mak, A. (2012). Conducting a meta-analysis: Basics and good practices. *International Journal of Rheumatic Diseases*, **15**(2), 129-135. doi:10.1111/j.1756-185X.2012.01712.x

Examples

```
## Random-effects meta-analysis
( meta1 <- summary(meta(y=yi, v=vi, data=Mak09, I2=c("I2q", "I2hm"))) )

## Convert the estimates back into odds ratio
OR <- with(coef(meta1), exp(c(Estimate[1], lbound[1], ubound[1])))
names(OR) <- c("Estimate in OR", "lbound in OR", "ubound in OR")
OR

## Mixed-effects meta-analysis with mean age as a predictor
summary( meta(y=yi, v=vi, x=age.mean, data=Mak09) )
```

Mathieu15

Correlation Matrices from Mathieu et al. (2015)

Description

The data set includes a list of correlation matrices of panel studies between cohesion (C) and performance (P) in Mathieu et al. (2015, Table 1).

Usage

```
data(Mathieu15)
```

Details

A list of data with the following structure:

data A list of studies of correlation matrices. The variables are *C1*, *P1*, *C2*, and *P2*.

n A vector of sample sizes.

Year Year of publication.

Sample Sample characteristics.

Student Whether the samples are student or non-student based on `Sample`.

Source

Mathieu, J. E., Kukenberger, M. R., D’Innocenzo, L., & Reilly, G. (2015). Modeling reciprocal team cohesion-performance relationships, as impacted by shared leadership and members’ competence. *Journal of Applied Psychology*, **100**(3), 713-734. <https://doi.org/10.1037/a0038898>

Examples

```
## Not run:
# TSSEM
## Model 1: no constraint
## Stage 1 analysis
tssem1.fit <- tssem1(Mathieu15$data, Mathieu15$n)
summary(tssem1.fit)

## Proposed model in lavaan syntax
model1 <- 'C2 ~ c2c*C1 + p2c*P1
          P2 ~ c2p*C1 + p2p*P1
          C1 ~~ c1withp1*P1
          C1 ~~ 1*C1
          P1 ~~ 1*P1
          C2 ~~ c2withp2*P2'

## Convert the lavaan model to RAM specification
RAM1 <- lavaan2RAM(model1, obs.variables=c("C1", "P1", "C2", "P2"))
RAM1

## Stage 2 analysis
tssem1b.fit <- tssem2(tssem1.fit, RAM=RAM1)
summary(tssem1b.fit)

plot(tssem1b.fit, col="yellow", edge.label.position=0.58)

## Model 2: Equality constraints on the path coefficient
## Proposed model with equal effects time 1 to time 2
model2 <- 'C2 ~ same*C1 + diff*P1
          P2 ~ diff*C1 + same*P1
          C1 ~~ c1withp1*P1
          C1 ~~ 1*C1
          P1 ~~ 1*P1
          C2 ~~ c2withp2*P2'
```

```

## Convert the lavaan model to RAM specification
RAM2 <- lavaan2RAM(model2, obs.variables=c("C1", "P1", "C2", "P2"))
RAM2

## Stage 2 analysis
tssem2b.fit <- tssem2(tssem1.fit, RAM=RAM2)
summary(tssem2b.fit)

## Compare the models with and without the constraints.
anova(tssem1b.fit, tssem2b.fit)

## Plot the model
plot(tssem2b.fit, col="yellow", edge.label.position=0.60)

## OSMASEM
my.df <- Cor2DataFrame(Mathieu15)

head(my.df$data)

## Model without any moderator
osmasem.fit1 <- osmasem(model.name="No moderator", RAM=RAM1, data=my.df)
summary(osmasem.fit1)

## Extract the heterogeneity variance-covariance matrix
diag(VarCorr(osmasem.fit1))

plot(osmasem.fit1, col="yellow", edge.label.position=0.6)

## Model with student sample as a moderator on the regression coefficients
A1 <- create.modMatrix(RAM1, output="A", "Student")
A1

## Model with a moderator
osmasem.fit2 <- osmasem(model.name="Student sample as a moderator", RAM=RAM1,
                      Ax=A1, data=my.df)
summary(osmasem.fit2)

## Compare the models with and without the moderator
anova(osmasem.fit2, osmasem.fit1)

## Get the R2 of the moderator
osmasemR2(osmasem.fit2, osmasem.fit1)

## End(Not run)

```

Description

It converts a matrix into a block diagonal matrix.

Usage

```
matrix2bdiag(x, ...)
```

Arguments

`x` A $k \times p$ matrix of numerics or characters.
`...` Further arguments to be passed to [vec2symMat](#)

Details

Each row of `x` is converted into a symmetric matrix via [vec2symMat](#). Then the list of the symmetric matrices is converted into a block diagonal matrix via a function written by Scott Chasalow posted at <http://www.math.yorku.ca/Who/Faculty/Monette/pub/stmp/0827.html>.

Author(s)

Mike W.-L. Cheung <mikewlcheung@nus.edu.sg>

See Also

[vec2symMat](#)

Examples

```
(m1 <- matrix(1:12, ncol=6, byrow=TRUE))
#      [,1] [,2] [,3] [,4] [,5] [,6]
# [1,]  1  2  3  4  5  6
# [2,]  7  8  9 10 11 12

matrix2bdiag(m1)
#      [,1] [,2] [,3] [,4] [,5] [,6]
# [1,]  1  2  3  0  0  0
# [2,]  2  4  5  0  0  0
# [3,]  3  5  6  0  0  0
# [4,]  0  0  0  7  8  9
# [5,]  0  0  0  8 10 11
# [6,]  0  0  0  9 11 12
```

| | |
|------|-------------------------------------------------------------------------------------|
| meta | <i>Univariate and Multivariate Meta-Analysis with Maximum Likelihood Estimation</i> |
|------|-------------------------------------------------------------------------------------|

Description

It conducts univariate and multivariate meta-analysis with maximum likelihood estimation method. Mixed-effects meta-analysis can be conducted by including study characteristics as predictors. Equality constraints on intercepts, regression coefficients, and variance components can be easily imposed by setting the same labels on the parameter estimates.

Usage

```
meta(y, v, x, data, intercept.constraints = NULL, coef.constraints = NULL,
     RE.constraints = NULL, RE.startvalues=0.1, RE.lbound = 1e-10,
     intervals.type = c("z", "LB"), I2="I2q", R2=TRUE,
     model.name="Meta analysis with ML", suppressWarnings = TRUE,
     silent = TRUE, run = TRUE, ...)
metaFIML(y, v, x, av, data, intercept.constraints=NULL,
         coef.constraints=NULL, RE.constraints=NULL,
         RE.startvalues=0.1, RE.lbound=1e-10,
         intervals.type=c("z", "LB"), R2=TRUE,
         model.name="Meta analysis with FIML",
         suppressWarnings=TRUE, silent=TRUE, run=TRUE, ...)
```

Arguments

| | |
|-----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| y | A vector of effect size for univariate meta-analysis or a $k \times p$ matrix of effect sizes for multivariate meta-analysis where k is the number of studies and p is the number of effect sizes. |
| v | A vector of the sampling variance of the effect size for univariate meta-analysis or a $k \times p^*$ matrix of the sampling covariance matrix of the effect sizes for multivariate meta-analysis where $p^* = p(p + 1)/2$. It is arranged by column major as used by vech . |
| x | A predictor or a $k \times m$ matrix of predictors where m is the number of predictors. |
| av | An auxiliary variable or a $k \times m$ matrix of auxiliary variables where m is the number of auxiliary variables. |
| data | An optional data frame containing the variables in the model. |
| intercept.constraints | A $1 \times p$ matrix specifying whether the intercepts of the effect sizes are fixed or free. If the input is not a matrix, the input is converted into a $1 \times p$ matrix with <code>t(as.matrix(intercept.constraints))</code> . The default is that the intercepts are free. When there is no predictor, these intercepts are the same as the pooled effect sizes. The format of this matrix follows as.mxMatrix . The intercepts can be constrained equally by using the same labels. |

| | |
|-------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>coef.constraints</code> | A $p \times m$ matrix specifying how the predictors predict the effect sizes. If the input is not a matrix, it is converted into a matrix by <code>as.matrix()</code> . The default is that all m predictors predict all p effect sizes. The format of this matrix follows <code>as.mxMatrix</code> . The regression coefficients can be constrained equally by using the same labels. |
| <code>RE.constraints</code> | A $p \times p$ matrix specifying the variance components of the random effects. If the input is not a matrix, it is converted into a matrix by <code>as.matrix()</code> . The default is that all covariance/variance components are free. The format of this matrix follows <code>as.mxMatrix</code> . Elements of the variance components can be constrained equally by using the same labels. If a zero matrix is specified, it becomes a fixed-effects meta-analysis. |
| <code>RE.startvalues</code> | A vector of p starting values on the diagonals of the variance component of the random effects. If only one scalar is given, it will be duplicated across the diagonals. Starting values for the off-diagonals of the variance component are all 0. A $p \times p$ symmetric matrix of starting values is also accepted. |
| <code>RE.lbound</code> | A vector of p lower bounds on the diagonals of the variance component of the random effects. If only one scalar is given, it will be duplicated across the diagonals. Lower bounds for the off-diagonals of the variance component are set at NA. A $p \times p$ symmetric matrix of the lower bounds is also accepted. |
| <code>intervals.type</code> | Either z (default if missing) or LB. If it is z, it calculates the 95% Wald confidence intervals (CIs) based on the z statistic. If it is LB, it calculates the 95% likelihood-based CIs on the parameter estimates. Note that the z values and their associated p values are based on the z statistic. They are not related to the likelihood-based CIs. |
| <code>I2</code> | Possible options are "I2q", "I2hm" and "I2am". They represent the I2 calculated by using a typical within-study sampling variance from the Q statistic, the harmonic mean and the arithmetic mean of the within-study sampling variances (Xiong, Miller, & Morris, 2010). More than one options are possible. If <code>intervals.type="LB"</code> , 95% confidence intervals on the heterogeneity indices will be constructed. |
| <code>R2</code> | Logical. If TRUE and there are predictors, R2 is calculated (Raudenbush, 2009). |
| <code>model.name</code> | A string for the model name in <code>mxModel</code> . |
| <code>suppressWarnings</code> | Logical. If TRUE, warnings are suppressed. The argument to be passed to <code>mxRun</code> . |
| <code>silent</code> | Logical. An argument to be passed to <code>mxRun</code> |
| <code>run</code> | Logical. If FALSE, only return the mx model without running the analysis. |
| <code>...</code> | Further arguments to be passed to <code>mxRun</code> |

Value

An object of class `meta` with a list of

| | |
|-------------------|--------------------------------------------|
| <code>call</code> | Object returned by <code>match.call</code> |
| <code>data</code> | A data matrix of y, v and x |

| | |
|---------|----------------------------------------------------------------------------------------------------------------------|
| no.y | No. of effect sizes |
| no.x | No. of predictors |
| miss.x | A vector indicating whether the predictors are missing. Studies will be removed before the analysis if they are TRUE |
| I2 | Types of I2 calculated |
| R2 | Logical |
| mx.fit | A fitted object returned from mxRun |
| mx0.fit | A fitted object without any predictor returned from mxRun |

Note

Missing values (NA) in y and their related elements in v will be removed automatically. When there are missing values in v but not in y, missing values will be replaced by 1e5. Effectively, these effect sizes will have little impact on the analysis. `metaFIML()` uses FIML to handle missing covariates in X. It is experimental. It may not be stable.

Author(s)

Mike W.-L. Cheung <mikewlcheung@nus.edu.sg>

References

- Cheung, M. W.-L. (2008). A model for integrating fixed-, random-, and mixed-effects meta-analyses into structural equation modeling. *Psychological Methods*, **13**, 182-202.
- Cheung, M. W.-L. (2009). Constructing approximate confidence intervals for parameters with structural equation models. *Structural Equation Modeling*, **16**, 267-294.
- Cheung, M. W.-L. (2013). Multivariate meta-analysis as structural equation models. *Structural Equation Modeling*, **20**, 429-454.
- Cheung, M. W.-L. (2015). *Meta-analysis: A structural equation modeling approach*. Chichester, West Sussex: John Wiley & Sons, Inc.
- Hardy, R. J., & Thompson, S. G. (1996). A likelihood approach to meta-analysis with random effects. *Statistics in Medicine*, **15**, 619-629.
- Neale, M. C., & Miller, M. B. (1997). The use of likelihood-based confidence intervals in genetic models. *Behavior Genetics*, **27**, 113-120.
- Raudenbush, S. W. (2009). Analyzing effect sizes: random effects models. In H. M. Cooper, L. V. Hedges, & J. C. Valentine (Eds.), *The handbook of research synthesis and meta-analysis* (2nd ed., pp. 295-315). New York: Russell Sage Foundation.
- Xiong, C., Miller, J. P., & Morris, J. C. (2010). Measuring study-specific heterogeneity in meta-analysis: application to an antecedent biomarker study of Alzheimer's disease. *Statistics in Biopharmaceutical Research*, **2**(3), 300-309. doi:10.1198/sbr.2009.0067

See Also

[reml](#), [Hox02](#), [Berkey98](#), [wvs94a](#)

| | |
|--------------|-----------------------------------------------------------------------|
| meta2semPlot | <i>Convert metaSEM objects into semPlotModel objects for plotting</i> |
|--------------|-----------------------------------------------------------------------|

Description

It converts objects in class `wls` into objects of class `semPlotModel`.

Usage

```
meta2semPlot(object, manNames = NULL, latNames = NULL, labels = c("labels", "RAM"), ...)
```

Arguments

| | |
|-----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>object</code> | An object of class <code>wls</code> returned from <code>wls()</code> or <code>tssem2()</code> . |
| <code>manNames</code> | A character vector of the manifest names. The program will try to get it from the object if it is not given. |
| <code>latNames</code> | A character vector of the latent names. The program will create it by using "L1", "L2", etc if it is not given. |
| <code>labels</code> | Either <code>labels</code> (default if missing) or <code>RAM</code> . If <code>labels</code> , the labels of the parameters are used in plotting. If <code>RAM</code> , the <code>RAM</code> notations are used in plotting. |
| <code>...</code> | Further arguments to be passed to ramModel |

Details

It uses the `ramModel()` to do the conversion.

Value

A "semPlotModel" object.

Author(s)

Mike W.-L. Cheung <mikewlcheung@nus.edu.sg>

See Also

[ramModel](#), [Becker92](#), [Becker09](#), [Digman97](#), [Hunter83](#)

meta3L

*Three-Level Univariate Meta-Analysis with Maximum Likelihood Estimation***Description**

It conducts three-level univariate meta-analysis with maximum likelihood estimation method. Mixed-effects meta-analysis can be conducted by including study characteristics as predictors. Equality constraints on the intercepts, regression coefficients and variance components on the level-2 and on the level-3 can be easily imposed by setting the same labels on the parameter estimates.

Usage

```
## Deprecated in the future
meta3(y, v, cluster, x, data, intercept.constraints = NULL,
      coef.constraints = NULL, RE2.constraints = NULL,
      RE2.lbound = 1e-10, RE3.constraints = NULL, RE3.lbound = 1e-10,
      intervals.type = c("z", "LB"), I2="I2q",
      R2=TRUE, model.name = "Meta analysis with ML",
      suppressWarnings = TRUE, silent = TRUE, run = TRUE, ...)
## Deprecated in the future
meta3X(y, v, cluster, x2, x3, av2, av3, data, intercept.constraints=NULL,
      coef.constraints=NULL, RE2.constraints=NULL, RE2.lbound=1e-10,
      RE3.constraints=NULL, RE3.lbound=1e-10, intervals.type=c("z", "LB"),
      R2=TRUE, model.name="Meta analysis with ML",
      suppressWarnings=TRUE, silent = TRUE, run = TRUE, ...)
meta3L(y, v, cluster, x, data, intercept.constraints = NULL,
      coef.constraints = NULL, RE2.constraints = NULL,
      RE2.lbound = 1e-10, RE3.constraints = NULL, RE3.lbound = 1e-10,
      intervals.type = c("z", "LB"), I2="I2q",
      R2=TRUE, model.name = "Meta analysis with ML",
      suppressWarnings = TRUE, silent = TRUE, run = TRUE, ...)
meta3LFIML(y, v, cluster, x2, x3, av2, av3, data, intercept.constraints=NULL,
      coef.constraints=NULL, RE2.constraints=NULL, RE2.lbound=1e-10,
      RE3.constraints=NULL, RE3.lbound=1e-10, intervals.type=c("z", "LB"),
      R2=TRUE, model.name="Meta analysis with ML",
      suppressWarnings=TRUE, silent = TRUE, run = TRUE, ...)
```

Arguments

| | |
|---------|---------------------------------------------------------------------------------------------------------------|
| y | A vector of k studies of effect size. |
| v | A vector of k studies of sampling variance. |
| cluster | A vector of k string or number indicating the clusters. |
| x | A predictor or a $k \times m$ matrix of level-2 and level-3 predictors where m is the number of predictors. |

| | |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x2 | A predictor or a $k \times m$ matrix of level-2 predictors where m is the number of predictors. |
| x3 | A predictor or a $k \times m$ matrix of level-3 predictors where m is the number of predictors. |
| av2 | A predictor or a $k \times m$ matrix of level-2 auxiliary variables where m is the number of variables. |
| av3 | A predictor or a $k \times m$ matrix of level-3 auxiliary variables where m is the number of variables. |
| data | An optional data frame containing the variables in the model. |
| intercept.constraints | A 1 x 1 matrix specifying whether the intercept of the effect size is fixed or constrained. The format of this matrix follows as.mxMatrix . The intercept can be constrained with other parameters by using the same label. |
| coef.constraints | A 1 x m matrix specifying how the level-2 and level-3 predictors predict the effect sizes. If the input is not a matrix, it is converted into a matrix by <code>as.matrix()</code> . The default is that all m predictors predict the effect size. The format of this matrix follows as.mxMatrix . The regression coefficients can be constrained equally by using the same labels. |
| RE2.constraints | A scalar or a 1 x 1 matrix specifying the variance components of the random effects. The default is that the variance components are free. The format of this matrix follows as.mxMatrix . Elements of the variance components can be constrained equally by using the same label. |
| RE2.lbound | A scalar or a 1 x 1 matrix of lower bound on the level-2 variance component of the random effects. |
| RE3.constraints | A scalar or a 1 x 1 matrix specifying the variance components of the random effects at level-3. The default is that the variance components are free. The format of this matrix follows as.mxMatrix . Elements of the variance components can be constrained equally by using the same label. |
| RE3.lbound | A scalar or a 1 x 1 matrix of lower bound on the level-3 variance component of the random effects. |
| intervals.type | Either z (default if missing) or LB. If it is z, it calculates the 95% Wald confidence intervals (CIs) based on the z statistic. If it is LB, it calculates the 95% likelihood-based CIs on the parameter estimates. Note that the z values and their associated p values are based on the z statistic. They are not related to the likelihood-based CIs. |
| I2 | Possible options are "I2q", "I2hm", "I2am" and "ICC". They represent the I2 calculated by using a typical within-study sampling variance from the Q statistic, the harmonic mean, the arithmetic mean of the within-study sampling variances, and the intra-class correlation. More than one options are possible. If <code>intervals.type="LB"</code> , 95% confidence intervals on the heterogeneity indices will be constructed. |
| R2 | Logical. If TRUE and there are predictors, R2 is calculated. |

| | |
|------------------|---------------------------------------------------------------------------------|
| model.name | A string for the model name in <code>mxModel</code> . |
| suppressWarnings | Logical. If TRUE, warnings are suppressed. It is passed to <code>mxRun</code> . |
| silent | Logical. An argument to be passed to <code>mxRun</code> |
| run | Logical. If FALSE, only return the mx model without running the analysis. |
| ... | Further arguments to be passed to <code>mxRun</code> |

Details

$$y_{ij} = \beta_0 + \beta' * \mathbf{x}_{ij} + u_{(2)ij} + u_{(3)j} + e_{ij}$$

where y_{ij} is the effect size for the i th study in the j th cluster, β_0 is the intercept, β is the regression coefficients, \mathbf{x}_{ij} is a vector of predictors, $u_{(2)ij} \sim N(0, \tau_2^2)$ and $u_{(3)j} \sim N(0, \tau_3^2)$ are the level-2 and level-3 heterogeneity variances, respectively, and $e_{ij} \sim N(0, v_{ij})$ is the conditional known sampling variance.

`meta3L()` does not differentiate between level-2 or level-3 variables in \mathbf{x} since both variables are treated as a design matrix. When there are missing values in \mathbf{x} , the data will be deleted. `meta3LFIML()` treats the predictors x_2 and x_3 as level-2 and level-3 variables. Thus, their means and covariance matrix will be estimated. Missing values in x_2 and x_3 will be handled by (full information) maximum likelihood (FIML) in `meta3LFIML()`. Moreover, auxiliary variables av_2 at level-2 and av_3 at level-3 may be included to improve the estimation. Although `meta3LFIML()` is more flexible in handling missing covariates, it is more likely to encounter estimation problems.

Author(s)

Mike W.-L. Cheung <mikewlcheung@nus.edu.sg>

References

- Cheung, M. W.-L. (2014). Modeling dependent effect sizes with three-level meta-analyses: A structural equation modeling approach. *Psychological Methods*, **19**, 211-229.
- Enders, C. K. (2010). *Applied missing data analysis*. New York: Guilford Press.
- Graham, J. (2003). Adding missing-data-relevant variables to FIML-based structural equation models. *Structural Equation Modeling: A Multidisciplinary Journal*, **10(1)**, 80-100.
- Konstantopoulos, S. (2011). Fixed effects and variance components estimation in three-level meta-analysis. *Research Synthesis Methods*, **2**, 61-76.

See Also

[rem13L](#), [Cooper03](#), [Bornmann07](#)

| | |
|-------|------------------------------------------------------------------------------|
| Nam03 | <i>Dataset on the Environmental Tobacco Smoke (ETS) on children's health</i> |
|-------|------------------------------------------------------------------------------|

Description

This dataset includes 59 studies reported by Nam, Mengersen, and Garthwaite (2003) on the potential health effects among children exposed to environmental tobacco smoke (ETS), or passive smoking. The effect sizes are the log odds ratios of asthma and lower respiratory disease (LRD).

Usage

```
data(Nam03)
```

Details

A list of data with the following structure:

ID Study identification number.

Size Total number of valid subjects in the study.

Age Mean age of participants.

Year Year of publication.

Country Country code.

Smoke Source of ETS.

Adj Whether the reported odds ratio is adjusted for covariates.

Asthma_logOR Log odds ratio of asthma.

LRD_logOR Log odds ratio of lower respiratory disease.

Asthma_v Sampling variance of Asthma_logOR.

AsthmaLRD_cov_05 Sampling covariance between Asthma_logOR and LRD_logOR by assuming a correlation of 0.5

LRD_v Sampling variance of LRD_logOR.

Source

Nam, I.-S., Mengersen, K., & Garthwaite, P. (2003). Multivariate meta-analysis. *Statistics in Medicine*, *22*(14), 2309-2333. <https://doi.org/10.1002/sim.1410>

Examples

```
data(Nam03)
```

Nohe15

*Correlation Matrices from Nohe et al. (2015)***Description**

The data sets include two lists of correlation matrices of panel studies between work-family conflict and strain reported in Table A1 (Nohe15A1) and Table A2 (Nohe15A2) by Nohe et al. (2015).

Usage

```
data(Nohe15A1)
data(Nohe15A2)
```

Details

A list of data with the following structure:

data A list of studies of correlation matrices. The variables are *W1*, *S1*, *W2*, and *S2* in Nohe15A1 and *F1*, *S1*, *F2*, and *S2* in Nohe15A2

n A vector of sample sizes

RelXX The reliabilities of *W1*, *S1*, *W2* and *S2* in Nohe15A1 and the reliabilities of *F1*, *S1*, *F2*, and *S2* in Nohe15A2

FemalePer Percentage of female participants

Publication Whether the studies were published (*P*) or unpublished (*U*)

Lag Time lag between the coded measurement waves in months

Source

Nohe, C., Meier, L. L., Sonntag, K., & Michel, A. (2015). The chicken or the egg? A meta-analysis of panel studies of the relationship between work-family conflict and strain. *Journal of Applied Psychology*, **100**(2), 522-536.

Examples

```
## Not run:
#### TSSEM

## Set seed for replicability
set.seed(23891)

## Table A1
randA1a <- tssem1(Nohe15A1$data, Nohe15A1$n, method="REM", RE.type="Diag")
summary(randA1a)

model1 <- 'W2 ~ w2w*W1 + s2w*S1
          S2 ~ w2s*W1 + s2s*S1
          W1 ~~ w1WITHs1*S1'
```



```

W2 ~~ w2WITHs2*S2
W1 ~~ 1*W1
S1 ~~ 1*S1
W2 ~~ Errw2*W2
S2 ~~ Errs2*S2'

## Display the model
plot(model1, layout="spring")

RAM1 <- lavaan2RAM(model1, obs.variables=c("W1", "S1", "W2", "S2"))
RAM1

randA1b <- tssem2(randA1a, Amatrix=RAM1$A, Smatrix=RAM1$S)
summary(randA1b)

## Display the model with the parameter estimates
plot(randA1b, layout="spring")

## Table A2
randA2a <- tssem1(Nohe15A2$data, Nohe15A2$n, method="REM", RE.type="Diag")
## Rerun to remove error code
randA2a <- rerun(randA2a)
summary(randA2a)

model2 <- 'F2 ~ f2f*F1 + s2F*S1
S2 ~ f2s*F1 + s2s*S1
F1 ~~ f1WITHs1*S1
F2 ~~ f2WITHs2*S2
F1 ~~ 1*F1
S1 ~~ 1*S1
F2 ~~ Errf2*F2
S2 ~~ Errs2*S2'

## Display the model
plot(model2, layout="spring")

RAM2 <- lavaan2RAM(model2, obs.variables=c("F1", "S1", "F2", "S2"))
RAM2

randA2b <- tssem2(randA2a, Amatrix=RAM2$A, Smatrix=RAM2$S)
summary(randA2b)

## Display the model with the parameter estimates
plot(randA2b, layout="spring")

## Estimate the heterogeneity of the parameter estimates
tssemParaVar(randA1a, randA2b)

## Parametric bootstrap based on Yu et al. (2016)
## I assume that you know what you are doing!

## Set seed for reproducibility
set.seed(39128482)

```

```

## Average the correlation coefficients with the univariate-r approach
uni1 <- uniR1(Nohe15A1$data, Nohe15A1$n)
uni1

## Generate random correlation matrices
boot.cor <- bootuniR1(uni1, Rep=50)

## Display the quality of the generated correlation matrices
summary(boot.cor)

## Proposed saturated model
model1 <- 'W2 + S2 ~ W1 + S1'

## Use the harmonic mean of the sample sizes as n in SEM
n <- uni1$n.harmonic

boot.fit1 <- bootuniR2(model=model1, data=boot.cor, n=n)
summary(boot.fit1)

## Proposed model with equal regression coefficients
model2 <- 'W2 ~ Same*W1 + Cross*S1
          S2 ~ Cross*W1 + Same*S1'

boot.fit2 <- bootuniR2(model=model2, data=boot.cor, n=n)
summary(boot.fit2)

#### OSMASEM

## Calculate the sampling variance-covariance matrix of the correlation matrices.
my.df <- Cor2DataFrame(Nohe15A1)

## Standardize the moderator "Lag"
my.df$data$Lag <- scale(my.df$data$Lag)

head(my.df$data)

## Proposed model
model1 <- 'W2 ~ w2w*W1 + s2w*S1
          S2 ~ w2s*W1 + s2s*S1
          W1 ~~ w1WITHs1*S1
          W2 ~~ w2WITHs2*S2
          W1 ~~ 1*W1
          S1 ~~ 1*S1
          W2 ~~ Errw2*W2
          S2 ~~ Errs2*S2'

plot(model1)

## Convert it into RAM specification
RAM1 <- lavaan2RAM(model1, obs.variables=c("W1", "S1", "W2", "S2"))
RAM1

## Create vechs of the model implied correlation matrix

```

```

## with implicit diagonal constraints
## M0 <- create.vechsR(A0=RAM1$A, S0=RAM1$S)

## Create heterogeneity variances
## RE.type= either "Diag" or "Symm"
##
## Transform= either "expLog" or "sqSD" for better estimation on variances
## T0 <- create.Tau2(RAM=RAM1, RE.type="Diag")
##
## Fit the model
## fit0 <- osmasem(model.name="No moderator", Mmatrix=M0, Tmatrix=T0, data=my.df)

## Fit the model
fit0 <- osmasem(model.name="No moderator", RAM=RAM1, data=my.df)
summary(fit0)

## Get the SRMR
osmasemSRMR(fit0)

## Get the transformed variance component of the random effects
VarCorr(fit0)

## "lag" as a moderator on A matrix
A1 <- matrix(c(0,0,0,0,
              0,0,0,0,
              "0*data.Lag", "0*data.Lag", 0,0,
              "0*data.Lag", "0*data.Lag", 0,0),
            nrow=4, ncol=4, byrow=TRUE)

## M1 <- create.vechsR(A0=RAM1$A, S0=RAM1$S, Ax=A1)
##
## Fit the model
## fit1 <- osmasem(model.name="Lag as a moderator for Amatrix", Mmatrix=M1,
##                Tmatrix=T0, data= my.df)

fit1 <- osmasem(model.name="Lag as a moderator for Amatrix",
                RAM=RAM1, Ax=A1, data= my.df)
summary(fit1)
VarCorr(fit1)

## Compare the models with and without the moderator "lag"
anova(fit1, fit0)

## Calculate the R2
osmasemR2(fit0, fit1)

## End(Not run)

```

Description

The data set includes 28 studies on 14 items measuring the Hospital Anxiety and Depression Scale (HADS) Reported by Norton et al. (2013).

Usage

```
data(Norton13)
```

Details

The variables are:

data A list of 28 studies of correlation matrices. The variables are 14 items (x1 to x14) measuring HADS.

n A vector of sample sizes

population A vector of the population of the data

group A vector of classification into *patients* vs. *non-patients* based on population

Source

Norton, S., Cosco, T., Doyle, F., Done, J., & Sacker, A. (2013). The Hospital Anxiety and Depression Scale: A meta confirmatory factor analysis. *Journal of Psychosomatic Research*, 74(1), 74-81.

References

Jak, S., & Cheung, M. W.-L. (2018). Addressing heterogeneity in meta-analytic structural equation modeling using subgroup analysis. *Behavior Research Methods*, **50**, 1359-1373.

Examples

```
data(Norton13)
```

 osmasem

One-stage meta-analytic structural equation modeling

Description

It fits MASEM with the one-stage MASEM (OSMASEM) approach.

Usage

```
osmasem(model.name="osmasem", RAM=NULL, Mmatrix=NULL,
        Tmatrix=NULL, Jmatrix=NULL, Ax=NULL, Sx=NULL,
        A.lbound=NULL, A.ubound=NULL,
        RE.type=c("Diag", "Symm"), data,
        subset.variables=NULL, subset.rows=NULL,
        intervals.type = c("z", "LB"),
        mxModel.Args=NULL, mxRun.Args=NULL,
        suppressWarnings=TRUE, silent=TRUE, run=TRUE, ...)
```

Arguments

| | |
|-------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>model.name</code> | A string for the model name in mxModel . |
| <code>RAM</code> | A RAM object including a list of matrices of the model returned from lavaan2RAM . If it is given, <code>Mmatrix</code> and <code>Tmatrix</code> arguments will be ignored. |
| <code>Mmatrix</code> | A list of matrices of the model implied correlation matrix created by the <code>create.vechsR</code> . It is only required when <code>RAM</code> is null. |
| <code>Tmatrix</code> | A list of matrices of the heterogeneity variance-covariance matrix created by the <code>create.Tau2</code> . It is only required when <code>RAM</code> is null. |
| <code>Jmatrix</code> | The Jacobian matrix of the mean structure in <code>mxMatrix</code> . The covariance structure is $Jmatrix \%\% Tau2 + Vi$. If it is not given, an identity matrix will be used. |
| <code>Ax</code> | A <code>Amatrix</code> of a list of <code>Amatrix</code> with definition variables as the moderators of the <code>Amatrix</code> . It is used to create the <code>Mmatrix</code> . |
| <code>Sx</code> | A <code>Smatrix</code> of a list of <code>Smatrix</code> with definition variables as the moderators of the <code>Smatrix</code> . It is used to create the <code>Mmatrix</code> . |
| <code>A.lbound</code> | A matrix of lower bound of the <code>Amatrix</code> . If a scalar is given, the <code>lbound</code> matrix will be filled with this scalar. |
| <code>A.ubound</code> | A matrix of upper bound of the <code>Amatrix</code> . If a scalar is given, the <code>ubound</code> matrix will be filled with this scalar. |
| <code>RE.type</code> | Type of the random effects. |
| <code>data</code> | A list of data created by the <code>Cor2DataFrame</code> . |
| <code>subset.variables</code> | A character vector of the observed variables selected for the analysis. |
| <code>subset.rows</code> | A logical vector of the same length as the number of rows in the data to select which rows are used in the analysis. |
| <code>intervals.type</code> | Either <code>z</code> (default if missing) or <code>LB</code> . If it is <code>z</code> , it calculates the 95% confidence intervals (CIs) based on the estimated standard error. If it is <code>LB</code> , it calculates the 95% likelihood-based CIs on the parameter estimates. |
| <code>mxModel.Args</code> | A list of arguments passed to mxModel . |
| <code>mxRun.Args</code> | A list of arguments passed to mxRun . |
| <code>suppressWarnings</code> | Logical. If it is <code>TRUE</code> , warnings are suppressed. This argument is passed to mxRun . |

| | |
|---------------------|---------------------------------------------------------------------------|
| <code>silent</code> | Logical. An argument is passed to <code>mxRun</code> |
| <code>run</code> | Logical. If FALSE, only return the mx model without running the analysis. |
| <code>...</code> | Not used yet. |

Value

An object of class `osmasem`

Author(s)

Mike W.-L. Cheung <mikewlcheung@nus.edu.sg>

References

Jak, S., & Cheung, M. W.-L. (2020). Meta-analytic structural equation modeling with moderating effects on SEM parameters. *Psychological Methods*, **25** (4), 430-455. <https://doi.org/10.1037/met0000245>

See Also

[Cor2DataFrame](#), [create.vechsR](#), [create.Tau2](#), [create.V](#), [osmasem](#), [Nohe15](#)

osmasemR2

Calculate the R2 in OSMASEM and OSMASEM3L

Description

It calculates the R2 of the moderators in explaining the variances in the heterogeneity variances.

Usage

```
osmasemR2(model1, model0, R2.truncate=TRUE)
```

Arguments

| | |
|--------------------------|----------------------------------------------|
| <code>model1</code> | An object in class <code>osmasem</code> . |
| <code>model0</code> | An object in class <code>osmasem</code> . |
| <code>R2.truncate</code> | Whether to truncate the negative R2 to zero. |

Value

`model1` and `model0` are the models with and without the moderators, respectively. The function does not check whether the models are nested. It is the users' responsibility to make sure that the models with and without the moderators are nested. It returns a list of the diagonals of the heterogeneity variances of the models without and with the moderators, and the R2.

Author(s)

Mike W.-L. Cheung <mikewlcheung@nus.edu.sg>

See Also[osmasem](#)

`osmasemSRMR`*Calculate the SRMR in OSMASEM and OSMASEM3L*

Description

It calculates the standardized root mean squared residuals (SRMR) in OSMASEM and OSMASEM3L.

Usage`osmasemSRMR(x)`**Arguments**

`x` An OSMASEM object without any moderators.

Value

It calculates the model implied correlation matrix and its saturated counterpart to calculate the SRMR. It should be noted that the heterogeneity variances are ignored in the calculations.

Author(s)

Mike W.-L. Cheung <mikewlcheung@nus.edu.sg>

See Also[osmasem](#), [Nohe15](#)

`pattern.n`*Display the Accumulative Sample Sizes for the Covariance Matrix*

Description

It displays the accumulative sample sizes for the covariance matrix.

Usage`pattern.n(x, n)`**Arguments**

`x` A list of square matrices
`n` A vector of sample sizes.

Value

A square matrix of the accumulative sample sizes of the input matrices.

Author(s)

Mike W.-L. Cheung <mikewlcheung@nus.edu.sg>

Examples

```
## Show the pattern of missing data
pattern.n(Hunter83$data, Hunter83$n)

#           Ability Knowledge Work sample Supervisor
# Ability      3815      3372      3281      3605
# Knowledge     3372      3532      2998      3322
# Work sample   3281      2998      3441      3231
# Supervisor    3605      3322      3231      3765
```

pattern.na

Display the Pattern of Missing Data of a List of Square Matrices

Description

It displays the pattern of missing data (or pattern of data that are present) of a list of square matrices with the same dimensions.

Usage

```
pattern.na(x, show.na = TRUE, type=c("tssem", "osmasem"))
```

Arguments

| | |
|---------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x | A list of square matrices |
| show.na | If it is TRUE, it shows the pattern of missing data. If it is FALSE, it shows the pattern of data that are present. |
| type | If it is tssem, it reports the pattern of missing correlations for the tssem approach. If it is osmasem, it reports the pattern of missing correlations for the data created by Cor2DataFrame . |

Value

A square matrix of numerical values with the same dimensions of the input matrices.

Author(s)

Mike W.-L. Cheung <mikewlcheung@nus.edu.sg>

Examples

```
## Show the pattern of missing data
pattern.na(Hunter83$data, show.na=TRUE)

#           Ability Knowledge Work sample Supervisor
# Ability      1           3           3           2
# Knowledge     3           2           4           3
# Work sample   3           4           2           3
# Supervisor    2           3           3           1

## Show the pattern of data that are present
pattern.na(Hunter83$data, show.na=FALSE)

#           Ability Knowledge Work sample Supervisor
# Ability      13           11           11           12
# Knowledge     11           12           10           11
# Work sample   11           10           12           11
# Supervisor    12           11           11           13
```

plot

Plot methods for various objects

Description

It plots the models from either the lavaan model or meta, wls, and osmasem objects.

Usage

```
## S3 method for class 'meta'
plot(x, effect.sizes, add.margin = 0.1, interval = 0.95,
     main= "Effect Sizes and their Confidence Ellipses",
     axis.labels= paste("Effect size ", effect.sizes, sep = ""),
     study.col = "black", study.pch = 19, study.min.cex = 0.8,
     study.weight.plot = FALSE, study.ellipse.plot = TRUE,
     study.ellipse.col = "black", study.ellipse.lty = 2,
     study.ellipse.lwd = 0.5, estimate.col = "blue",
     estimate.pch = 18, estimate.cex = 2,
     estimate.ellipse.plot = TRUE, estimate.ellipse.col = "red",
     estimate.ellipse.lty = 1, estimate.ellipse.lwd = 2,
     randeff.ellipse.plot = TRUE, randeff.ellipse.col = "green",
     randeff.ellipse.lty = 1, randeff.ellipse.lwd = 2,
     univariate.plot = TRUE, univariate.lines.col = "gray",
     univariate.lines.lty = 3, univariate.lines.lwd = 1,
     univariate.polygon.width = 0.02,
     univariate.polygon.col = "red",
     univariate.arrows.col = "green", univariate.arrows.lwd = 2,
     diag.panel = FALSE, xlim=NULL, ylim=NULL, ...)
## S3 method for class 'character'
```

```

plot(x, fixed.x=FALSE, nCharNodes=0, nCharEdges=0,
     layout=c("tree", "circle", "spring", "tree2", "circle2"),
     sizeMan=8, sizeLat=8, edge.label.cex=1.3, color="white", ...)
## S3 method for class 'wls'
plot(x, manNames=NULL, latNames=NULL, labels=c("labels", "RAM"),
     what="est", nCharNodes=0, nCharEdges=0,
     layout=c("tree", "circle", "spring", "tree2", "circle2"),
     sizeMan=8, sizeLat=8, edge.label.cex=1.3, color="white",
     weighted=FALSE, ...)
## S3 method for class 'osmasem'
plot(x, manNames=NULL, latNames=NULL, labels=c("labels", "RAM"),
     what="est", nCharNodes=0, nCharEdges=0,
     layout=c("tree", "circle", "spring", "tree2", "circle2"),
     sizeMan=8, sizeLat=8, edge.label.cex=1.3, color="white",
     weighted=FALSE, ...)

```

Arguments

| | |
|---------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>x</code> | An object returned from either a lavaan model class character, <code>osmasem</code> , <code>osmasem3L</code> , <code>wls</code> or <code>meta</code> |
| <code>effect.sizes</code> | Numeric values indicating which effect sizes to be plotted. At least two effect sizes are required. To plot the effect sizes of y_1 and y_2 , one may use <code>effect.sizes=c(1,2)</code> . If it is missing, all effect sizes will be plotted in a pairwise way. |
| <code>add.margin</code> | Value for additional margins on the left and bottom margins. |
| <code>interval</code> | Interval for the confidence ellipses. |
| <code>main</code> | Main title of each plot. If there are multiple plots, a vector of character titles may be used. |
| <code>axis.labels</code> | Labels for the effect sizes. |
| <code>study.col</code> | The color for individual studies. See <code>col</code> in par . |
| <code>study.pch</code> | Plotting character of individual studies. See <code>pch</code> in points . |
| <code>study.min.cex</code> | The minimum value of <code>cex</code> for individual studies. See <code>cex</code> in par . |
| <code>study.weight.plot</code> | Logical. If TRUE, the plotting size of individual studies (<code>cex</code>) will be proportional to one over the square root of the determinant of the sampling covariance matrix of the study. |
| <code>study.ellipse.plot</code> | Logical. If TRUE, the confidence ellipses of individual studies are plotted. |
| <code>study.ellipse.col</code> | The color of the confidence ellipses of individual studies. See <code>col</code> in par . |
| <code>study.ellipse.lty</code> | The line type of the confidence ellipse of individual studies. See <code>lty</code> in par . |
| <code>study.ellipse.lwd</code> | The line width of the confidence ellipse of individual studies. See <code>lwd</code> in par . |
| <code>estimate.col</code> | The color of the estimated effect size. See <code>col</code> in par . |

| | |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------|
| <code>estimate.pch</code> | Plotting character of the estimated effect sizes. See <code>pch</code> in points . |
| <code>estimate.cex</code> | The amount of plotting of the estimated effect sizes. See <code>cex</code> in par . |
| <code>estimate.ellipse.plot</code> | Logical. If TRUE, the confidence ellipse of the estimated effect sizes will be plotted. |
| <code>estimate.ellipse.col</code> | The color of the confidence ellipse of the estimated effect sizes. See <code>col</code> in par . |
| <code>estimate.ellipse.lty</code> | The line type of the confidence ellipse of the estimated effect sizes. See <code>lty</code> in par . |
| <code>estimate.ellipse.lwd</code> | The line width of the confidence ellipse of the estimated effect sizes. See <code>lwd</code> in par . |
| <code>randeff.ellipse.plot</code> | Logical. If TRUE, the confidence ellipses of the random effects will be plotted. |
| <code>randeff.ellipse.col</code> | Color of the confidence ellipses of the random effects. See <code>col</code> in par . |
| <code>randeff.ellipse.lty</code> | The line type of the confidence ellipses of the random effects. See <code>lty</code> in par . |
| <code>randeff.ellipse.lwd</code> | The line width of the confidence ellipses of the random effects. See <code>lwd</code> in par . |
| <code>univariate.plot</code> | Logical. If TRUE, the estimated univariate effect sizes will be plotted. |
| <code>univariate.lines.col</code> | The color of the estimated univariate effect sizes. See <code>col</code> in par . |
| <code>univariate.lines.lty</code> | The line type of the estimated univariate effect sizes. See <code>lty</code> in par . |
| <code>univariate.lines.lwd</code> | The line width of the estimated univariate effect sizes. See <code>lwd</code> in par . |
| <code>univariate.polygon.width</code> | The width of the polygon of the estimated univariate effect sizes. |
| <code>univariate.polygon.col</code> | The color of the polygon of the estimated univariate effect sizes. |
| <code>univariate.arrows.col</code> | The color of the arrows of the estimated univariate effect sizes. |
| <code>univariate.arrows.lwd</code> | The line width of the arrows of the estimated univariate effect sizes. |
| <code>diag.panel</code> | Logical. If TRUE, diagonal panels will be created. They can then be used for forest plots for univariate meta-analysis. |
| <code>xlim</code> | NULL or a numeric vector of length 2; if it is NULL, it provides defaults estimated from the data. |
| <code>ylim</code> | NULL or a numeric vector of length 2; if it is NULL, it provides defaults estimated from the data. |
| <code>fixed.x</code> | Argument passed to semPlotModel . |

| | |
|----------------|---------------------------------------------|
| manNames | Argument passed to semPaths |
| latNames | Argument passed to semPaths |
| labels | Argument passed to semPaths |
| what | Argument passed to semPaths |
| nCharNodes | Argument passed to semPaths |
| nCharEdges | Argument passed to semPaths |
| layout | Argument passed to semPaths |
| color | Argument passed to semPaths |
| sizeMan | Argument passed to semPaths |
| sizeLat | Argument passed to semPaths |
| edge.label.cex | Argument passed to semPaths |
| weighted | Argument passed to semPaths |
| ... | Further arguments passed to the methods. |

Note

The estimated effect sizes and random effects are based on the labels Intercept1, Intercept2, ... and Tau2_1_1, Tau2_2_1, Tau2_2_2, etc. At least two effect sizes are required for this function.

Author(s)

Mike W.-L. Cheung <mikewlcheung@nus.edu.sg>

References

Cheung, M. W.-L. (2013). Multivariate meta-analysis as structural equation models. *Structural Equation Modeling*, **20**, 429-454.

See Also

[Berkey98](#), [wvs94a](#) [meta2semPlot](#) [semPaths](#)

Examples

```
## Not run:
## lavaan model
model <- "y ~ m + x
         m ~ x"
plot(model)

## End(Not run)
```

print

Print Methods for various Objects

Description

Print methods for the `tssem1FEM`, `tssem1FEM.cluster`, `tssem1REM`, `wls`, `meta`, `meta3LFIML`, `reml`, `uniR1` and `impliedR` objects.

Usage

```
## S3 method for class 'tssem1FEM'
print(x, ...)
## S3 method for class 'tssem1FEM.cluster'
print(x, ...)
## S3 method for class 'tssem1REM'
print(x, ...)
## S3 method for class 'wls'
print(x, ...)
## S3 method for class 'meta'
print(x, ...)
## S3 method for class 'meta3LFIML'
print(x, ...)
## S3 method for class 'reml'
print(x, ...)
## S3 method for class 'uniR1'
print(x, ...)
## S3 method for class 'impliedR'
print(x, ...)
```

Arguments

| | |
|-----|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x | An object returned from either class <code>tssem1FEM</code> , class <code>tssem1FEM.cluster</code> , class <code>tssem1REM</code> , class <code>wls</code> , class <code>meta</code> , class <code>meta3LFIML</code> , class <code>reml</code> , class <code>uniR1</code> or class <code>impliedR</code> |
| ... | Further arguments to be passed to <code>summary.default</code> or <code>unused</code> . |

Author(s)

Mike W.-L. Cheung <mikewlcheung@nus.edu.sg>

See Also

[tssem1](#), [wls](#), [meta](#), [reml](#)

| | |
|------|----------------------------------------------------------------------------|
| rCor | <i>Generate (Nested) Sample/Population Correlation/Covariance Matrices</i> |
|------|----------------------------------------------------------------------------|

Description

It generates (nested) random sample or population correlation or covariance matrices. `rCor()` is a wrapper to call `rCorPop()` and then `rCorSam()`.

Usage

```
rCor(Sigma, V, n, corr=TRUE, raw.data=FALSE,
     nonPD.pop=c("replace", "nearPD", "accept"),
     nonPD.sam=c("stop", "nearPD"))
rCorPop(Sigma, V, k, corr=TRUE,
        nonPD.pop=c("replace", "nearPD", "accept"))
rCorSam(Sigma, n, corr=TRUE, raw.data=FALSE,
        nonPD.sam=c("stop", "nearPD"))
rCor3L(Sigma, V.B, V.W, n, cluster, corr=TRUE, raw.data=FALSE,
       nonPD.pop=c("replace", "nearPD", "accept"),
       nonPD.sam=c("stop", "nearPD"))
```

Arguments

| | |
|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>Sigma</code> | A list of population correlation/covariance matrices or a single matrix |
| <code>V</code> | A variance-covariance matrix of <code>Sigma</code> . |
| <code>V.B</code> | A variance-covariance matrix of between-study <code>Sigma</code> . |
| <code>V.W</code> | A variance-covariance matrix of within-study <code>Sigma</code> |
| <code>n</code> | A vector or a single sample sizes. |
| <code>cluster</code> | A vector of number of studies in clusters. |
| <code>corr</code> | Logical. Whether to generate correlation or covariance matrices. |
| <code>raw.data</code> | Logical. Whether correlation/covariance matrices are generated via <code>raw.data</code> or directly from a Wishart distribution. |
| <code>nonPD.pop</code> | If it is <code>replace</code> , generated non-positive definite matrices are replaced by generated new ones which are positive definite. If it is <code>nearPD</code> , they are replaced by nearly positive definite matrices by calling <code>Matrix::nearPD()</code> . If it is <code>accept</code> , they are accepted. |
| <code>nonPD.sam</code> | If it is <code>stop</code> , the program stops when the inputs in the <code>rCorSam</code> are non-positive definite. If it is <code>nearPD</code> , they are replaced by nearly positive definite matrices by calling <code>Matrix::nearPD()</code> . |
| <code>k</code> | A vector or a single number of studies. |

Value

An object of the generated population/sample correlation/covariance matrices.

Author(s)

Mike W.-L. Cheung <mikewlcheung@nus.edu.sg>

Examples

```
Sigma <- matrix(c(1, .2, .3,
                 .2, 1, .4,
                 .3, .4, 1), ncol=3, nrow=3)
V <- diag(c(.1, .1, .1))

## Generate two population correlation matrices
Pop.corr <- rCorPop(Sigma, V, k=2)
Pop.corr

summary(Pop.corr)

## Generate two sample correlation matrices
rCorSam(Sigma=Pop.corr, n=c(10, 10))

## The above code is the same as the following one
rCor(Sigma, V, n=c(10, 10))
```

readData

Read External Correlation/Covariance Matrices

Description

It reads full/lower triangle/stacked vectors of correlation/covariance data into a list of correlation/covariance matrices.

Usage

```
readFullMat(file, ...)
readStackVec(file, ...)
readLowTriMat(file, no.var, ...)
```

Arguments

| | |
|--------|----------------------------------------------------------------------------------------------------------------------------------------------|
| file | File name of the data. |
| no.var | The number of variables in the data. |
| ... | Further arguments to be passed to scan for readLowTriMat and to read.table for readFullMat and readStackVec. |

Value

A list of correlation/covariance matrices.

Author(s)

Mike W.-L. Cheung <mikewlcheung@nus.edu.sg>

Examples

```
## Not run:
## Write two full correlation matrices into a file named "fullmat.dat".
## x2 is missing in the second matrix.
## The content of "fullmat.dat" is
# 1.0 0.3 0.4
# 0.3 1.0 0.5
# 0.4 0.5 1.0
# 1.0 NA 0.4
# NA NA NA
# 0.4 NA 1.0

## cat("1.0 0.3 0.4\n0.3 1.0 0.5\n0.4 0.5 1.0
## 1.0 NA 0.4\nNA NA NA\n0.4 NA 1.0",
## file="fullmat.dat", sep="")

## Read the correlation matrices
## my.full <- readFullMat("fullmat.dat")

## my.full
# $`1`
#   x1 x2 x3
# x1 1.0 0.3 0.4
# x2 0.3 1.0 0.5
# x3 0.4 0.5 1.0
#
# $`2`
#   x1 x2 x3
# x1 1.0 NA 0.4
# x2 NA NA NA
# x3 0.4 NA 1.0

## Write two lower triangle correlation matrices into a file named "lowertriangle.dat".
## x2 is missing in the second matrix.
## The content of "lowertriangle.dat" is
# 1.0
# 0.3 1.0
# 0.4 0.5 1.0
# 1.0
# NA NA
# 0.4 NA 1.0
## cat("1.0\n0.3 1.0\n0.4 0.5 1.0\n1.0\nNA NA\n0.4 NA 1.0",
## file="lowertriangle.dat", sep="")

## Read the lower triangle correlation matrices
## my.lowertri <- readLowTriMat(file = "lowertriangle.dat", no.var = 3)

## my.lowertri
```



```

# `$1`
#   x1 x2 x3
# x1 1.0 0.3 0.4
# x2 0.3 1.0 0.5
# x3 0.4 0.5 1.0
#
# `$2`
#   x1 x2 x3
# x1 1.0 NA 0.4
# x2 NA NA NA
# x3 0.4 NA 1.0

## Write two vectors of correlation coefficients based on
## column major into a file named "stackvec.dat".
## x2 is missing in the second matrix.
## The content of "stackvec.dat" is
# 1.0 0.3 0.4 1.0 0.5 1.0
# 1.0 NA 0.4 NA NA 1.0
## cat("1.0 0.3 0.4 1.0 0.5 1.0\n1.0 NA 0.4 NA NA 1.0\n",
##     file="stackvec.dat", sep="")

## my.vec <- readStackVec("stackvec.dat")

## my.vec
# `$1`
#   x1 x2 x3
# x1 1.0 0.3 0.4
# x2 0.3 1.0 0.5
# x3 0.4 0.5 1.0
#
# `$2`
#   x1 x2 x3
# x1 1.0 NA 0.4
# x2 NA NA NA
# x3 0.4 NA 1.0

## End(Not run)

```

reml

Estimate Variance Components with Restricted (Residual) Maximum Likelihood Estimation

Description

It estimates the variance components of random-effects in univariate and multivariate meta-analysis with restricted (residual) maximum likelihood (REML) estimation method.

Usage

```
reml(y, v, x, data, RE.constraints = NULL, RE.startvalues = 0.1,
```

```
RE.lbound = 1e-10, intervals.type = c("z", "LB"),
model.name="Variance component with REML",
suppressWarnings = TRUE, silent = TRUE, run = TRUE, ...)
```

Arguments

| | |
|-------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>y</code> | A vector of effect size for univariate meta-analysis or a $k \times p$ matrix of effect sizes for multivariate meta-analysis where k is the number of studies and p is the number of effect sizes. |
| <code>v</code> | A vector of the sampling variance of the effect size for univariate meta-analysis or a $k \times p^*$ matrix of the sampling covariance matrix of the effect sizes for multivariate meta-analysis where $p^* = p(p + 1)/2$. It is arranged by column major as used by vech . |
| <code>x</code> | A predictor or a $k \times m$ matrix of predictors where m is the number of predictors. |
| <code>data</code> | An optional data frame containing the variables in the model. |
| <code>RE.constraints</code> | A $p \times p$ matrix specifying the variance components of the random effects. If the input is not a matrix, it is converted into a matrix by <code>as.matrix()</code> . The default is that all covariance/variance components are free. The format of this matrix follows as.mxMatrix . Elements of the variance components can be constrained equally by using the same labels. If a zero matrix is specified, it becomes a fixed-effects meta-analysis. |
| <code>RE.startvalues</code> | A vector of p starting values on the diagonals of the variance component of the random effects. If only one scalar is given, it will be repeated across the diagonals. Starting values for the off-diagonals of the variance component are all 0. A $p \times p$ symmetric matrix of starting values is also accepted. |
| <code>RE.lbound</code> | A vector of p lower bounds on the diagonals of the variance component of the random effects. If only one scalar is given, it will be repeated across the diagonals. Lower bounds for the off-diagonals of the variance component are set at NA. A $p \times p$ symmetric matrix of the lower bounds is also accepted. |
| <code>intervals.type</code> | Either <code>z</code> (default if missing) or <code>LB</code> . If it is <code>z</code> , it calculates the 95% Wald confidence intervals (CIs) based on the z statistic. If it is <code>LB</code> , it calculates the 95% likelihood-based CIs on the parameter estimates. Note that the z values and their associated p values are based on the z statistic. They are not related to the likelihood-based CIs. |
| <code>model.name</code> | A string for the model name in mxModel . |
| <code>suppressWarnings</code> | Logical. If <code>TRUE</code> , warnings are suppressed. It is passed to mxRun . |
| <code>silent</code> | Logical. An argument to be passed to mxRun |
| <code>run</code> | Logical. If <code>FALSE</code> , only return the <code>mx</code> model without running the analysis. |
| <code>...</code> | Further arguments to be passed to mxRun |

Details

Restricted (residual) maximum likelihood obtains the parameter estimates on the transformed data that do not include the fixed-effects parameters. A transformation matrix $M = I - X(X'X)^{-1}X'$

is created based on the design matrix X which is just a column vector when there is no predictor in x . The last N redundant rows of M is removed where N is the rank of X . After pre-multiplying by M on y , the parameters of fixed-effects are removed from the model. Thus, only the parameters of random-effects are estimated.

An alternative but equivalent approach is to minimize the $-2 \times \log$ -likelihood function:

$$\log(\det |V + T^2|) + \log(\det |X'(V + T^2)^{-1}X|) + (y - X\hat{\alpha})'(V + T^2)^{-1}(y - X\hat{\alpha})$$

where V is the known conditional sampling covariance matrix of y , T^2 is the variance component of the random effects, and $\hat{\alpha} = (X'(V + T^2)^{-1}X)^{-1}X'(V + T^2)^{-1}y$. `reml()` minimizes the above likelihood function to obtain the parameter estimates.

Value

An object of class `reml` with a list of

| | |
|-----------------------|------------------------------------------------------------------------------------------------|
| <code>call</code> | Object returned by <code>match.call</code> |
| <code>data</code> | A data matrix of y , v and x |
| <code>no.y</code> | No. of effect sizes |
| <code>no.x</code> | No. of predictors |
| <code>miss.vec</code> | A vector indicating missing data. Studies will be removed before the analysis if they are TRUE |
| <code>mx.fit</code> | A fitted object returned from <code>mxRun</code> |

Note

`reml` is more computationally intensive than `meta`. Moreover, `reml` is more likely to encounter errors during optimization. Since a likelihood function is directly employed to obtain the parameter estimates, there is no number of studies and number of observed statistics returned by `mxRun`. Ad-hoc steps are used to modify `mx.fit@runstate$objectives[[1]]@numObs` and `mx.fit@runstate$objectives[[1]]@num`

Author(s)

Mike W.-L. Cheung <mikewlcheung@nus.edu.sg>

References

- Cheung, M. W.-L. (2013). Implementing restricted maximum likelihood estimation in structural equation models. *Structural Equation Modeling*, **20**(1), 157-167.
- Mehta, P. D., & Neale, M. C. (2005). People Are Variables Too: Multilevel Structural Equations Modeling. *Psychological Methods*, **10**(3), 259-284.
- Searle, S. R., Casella, G., & McCulloch, C. E. (1992). *Variance components*. New York: Wiley.
- Viechtbauer, W. (2005). Bias and efficiency of meta-analytic variance estimators in the random-effects model. *Journal of Educational and Behavioral Statistics*, **30**(3), 261-293.

See Also

[meta](#), [reml3](#), [Hox02](#), [Berkey98](#)

| | |
|--------|--------------------------------------------------------------------------------------------------------------------------------------|
| reml3L | <i>Estimate Variance Components in Three-Level Univariate Meta-Analysis with Restricted (Residual) Maximum Likelihood Estimation</i> |
|--------|--------------------------------------------------------------------------------------------------------------------------------------|

Description

It estimates the variance components of random-effects in three-level univariate meta-analysis with restricted (residual) maximum likelihood (REML) estimation method.

Usage

```
## Depreciated in the future
reml3(y, v, cluster, x, data, RE2.startvalue=0.1, RE2.lbound=1e-10,
      RE3.startvalue=RE2.startvalue, RE3.lbound=RE2.lbound, RE.equal=FALSE,
      intervals.type=c("z", "LB"), model.name="Variance component with REML",
      suppressWarnings=TRUE, silent=TRUE, run=TRUE, ...)
reml3L(y, v, cluster, x, data, RE2.startvalue=0.1, RE2.lbound=1e-10,
       RE3.startvalue=RE2.startvalue, RE3.lbound=RE2.lbound, RE.equal=FALSE,
       intervals.type=c("z", "LB"), model.name="Variance component with REML",
       suppressWarnings=TRUE, silent=TRUE, run=TRUE, ...)
```

Arguments

| | |
|------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| y | A vector of k studies of effect size. |
| v | A vector of k studies of sampling variance. |
| cluster | A vector of k characters or numbers indicating the clusters. |
| x | A predictor or a $k \times m$ matrix of level-2 and level-3 predictors where m is the number of predictors. |
| data | An optional data frame containing the variables in the model. |
| RE2.startvalue | Starting value for the level-2 variance. |
| RE2.lbound | Lower bound for the level-2 variance. |
| RE3.startvalue | Starting value for the level-3 variance. |
| RE3.lbound | Lower bound for the level-3 variance. |
| RE.equal | Logical. Whether the variance components at level-2 and level-3 are constrained equally. |
| intervals.type | Either z (default if missing) or LB. If it is z, it calculates the 95% Wald confidence intervals (CIs) based on the z statistic. If it is LB, it calculates the 95% likelihood-based CIs on the parameter estimates. Note that the z values and their associated p values are based on the z statistic. They are not related to the likelihood-based CIs. |
| model.name | A string for the model name in mxModel . |
| suppressWarnings | Logical. If TRUE, warnings are suppressed. It is passed to mxRun . |

| | |
|--------|---------------------------------------------------------------------------|
| silent | Logical. Argument to be passed to <code>mxRun</code> |
| run | Logical. If FALSE, only return the mx model without running the analysis. |
| ... | Further arguments to be passed to <code>mxRun</code> |

Details

Restricted (residual) maximum likelihood obtains the parameter estimates on the transformed data that do not include the fixed-effects parameters. A transformation matrix $M = I - X(X'X)^{-1}X'$ is created based on the design matrix X which is just a column vector when there is no predictor in x . The last N redundant rows of M is removed where N is the rank of X . After pre-multiplying by M on y , the parameters of fixed-effects are removed from the model. Thus, only the parameters of random-effects are estimated.

An alternative but the equivalent approach is to minimize the $-2 \times \log$ -likelihood function:

$$\log(\det |V + T^2|) + \log(\det |X'(V + T^2)^{-1}X|) + (y - X\hat{\alpha})'(V + T^2)^{-1}(y - X\hat{\alpha})$$

where V is the known conditional sampling covariance matrix of y , T^2 is the variance component combining level-2 and level-3 random effects, and $\hat{\alpha} = (X'(V + T^2)^{-1}X)^{-1}X'(V + T^2)^{-1}y$. `reml()` minimizes the above likelihood function to obtain the parameter estimates.

Value

An object of class `reml` with a list of

| | |
|--------|--------------------------------------------------|
| call | Object returned by <code>match.call</code> |
| data | A data matrix of y , v , and x |
| mx.fit | A fitted object returned from <code>mxRun</code> |

Note

`reml` is more computationally intensive than `meta`. Moreover, `reml` is more likely to encounter errors during optimization. Since a likelihood function is directly employed to obtain the parameter estimates, there is no number of studies and number of observed statistics returned by `mxRun`. Ad-hoc steps are used to modify `mx.fit@runstate$objectives[[1]]@numObs` and `mx.fit@runstate$objectives[[1]]@num`

Author(s)

Mike W.-L. Cheung <mikewlcheung@nus.edu.sg>

References

- Cheung, M. W.-L. (2013). Implementing restricted maximum likelihood estimation in structural equation models. *Structural Equation Modeling*, **20**(1), 157-167.
- Cheung, M. W.-L. (2014). Modeling dependent effect sizes with three-level meta-analyses: A structural equation modeling approach. *Psychological Methods*, **19**, 211-229.
- Mehta, P. D., & Neale, M. C. (2005). People Are Variables Too: Multilevel Structural Equations Modeling. *Psychological Methods*, **10**(3), 259-284.
- Searle, S. R., Casella, G., & McCulloch, C. E. (1992). *Variance components*. New York: Wiley.

See Also

[meta3L](#), [reml](#), [Cooper03](#), [Bornmann07](#)

| | |
|-------|-------------------------------------|
| rerun | <i>Rerun models via mxTryHard()</i> |
|-------|-------------------------------------|

Description

It reruns models via mxTryHard().

Usage

```
rerun(object, autofixtau2=FALSE, extraTries=10, ...)
```

Arguments

| | |
|-------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| object | An object of either class tssem1FEM, class tssem1REM, class wls, class meta, class reml, class osmasem, class osmasem3L, and class MxModel. |
| autofixtau2 | Logical. Whether automatically fixes elements of tau2 with NA of standard errors. It only works for objects of class tssem1REM, class meta, and class osmasem. |
| extraTries | The number of attempts to run the model in addition to the first. |
| ... | Further arguments to be passed to mxTryHard |

Author(s)

Mike W.-L. Cheung <mikewlcheung@nus.edu.sg>

Examples

```
## Not run:
random1 <- tssem1(Digman97$data, Digman97$n, method="REM", RE.type="Diag")
random1_rerun <- rerun(random1)
summary(random1_rerun)

## End(Not run)
```

| | |
|----------|------------------------------------------------------------------------------------------------|
| Roorda11 | <i>Studies on Students' School Engagement and Achievement Reported by Roorda et al. (2011)</i> |
|----------|------------------------------------------------------------------------------------------------|

Description

The data set includes 45 studies on the influence of affective teacher-student relationships on students' school engagement and achievement reported by Roorda et al. (2011).

Usage

```
data(Roorda11)
```

Details

The variables are:

data A list of 45 studies of correlation matrices. The variables are *pos* (positive teacher-student relations), *neg* (negative teacher-student relations), *enga* (student engagement), and *achiev* (student achievement).

n A vector of sample sizes

SES A vector of average socio-economic status (SES) of the samples

Source

Roorda, D. L., Koomen, H. M. Y., Spilt, J. L., & Oort, F. J. (2011). The influence of affective teacher-student relationships on students' school engagement and achievement a meta-analytic approach. *Review of Educational Research, 81*(4), 493-529.

References

Jak, S., & Cheung, M. W.-L. (2018). Addressing heterogeneity in meta-analytic structural equation modeling using subgroup analysis. *Behavior Research Methods, 50*, 1359-1373.

Examples

```
## Not run:

## Random-effects model: First stage analysis
random1 <- tssem1(Cov = Roorda11$data, n = Roorda11$n, method = "REM",
                 RE.type = "Diag")
summary(random1)

varnames <- c("pos", "neg", "enga", "achiev")

## Prepare a regression model using create.mxMatrix()
A <- create.mxMatrix(c(0,0,0,0,
                      0,0,0,0,
```

```

      "0.1*b31", "0.1*b32", 0, 0,
      0, 0, "0.1*b43", 0),
    type = "Full", nrow = 4, ncol = 4, byrow = TRUE,
    name = "A", as.mxMatrix = FALSE)

## This step is not necessary but it is useful for inspecting the model.
dimnames(A) <- list(varnames, varnames)
A

S <- create.mxMatrix(c(1,
  ".5*p21", 1,
  0, 0, "0.6*p33",
  0, 0, 0, "0.6*p44"),
  type="Symm", byrow = TRUE,
  name="S", as.mxMatrix = FALSE)

## This step is not necessary but it is useful for inspecting the model.
dimnames(S) <- list(varnames, varnames)
S

## Random-effects model: Second stage analysis
random2 <- tssem2(random1, Amatrix=A, Smatrix=S, diag.constraints=TRUE,
  intervals="LB")
summary(random2)

## Display the model with the parameter estimates
plot(random2)

## End(Not run)

```

 Scalco17

Correlation Matrices from Scalco et al. (2017)

Description

The data set includes correlation matrices using the theory of planned behavior to predict organic food consumption reported by Scalco17 et al. (2017).

Usage

```
data(Scalco17)
```

Details

A list of data with the following structure:

data A list of correlation matrices. The variables are *ATT* (attitude), *SN* (subjective norm), *PBC* (perceived behavior control), *BI* (behavioral intention), and *BEH* (behavior)

n A vector of sample sizes

Age A vector of the mean age of the samples

Female A vector of the percentage of the female samples

Source

Scalco, A., Noventa, S., Sartori, R., & Ceschi, A. (2017). Predicting organic food consumption: A meta-analytic structural equation model based on the theory of planned behavior. *Appetite*, **112**, 235-248.

Examples

```
data(Scalco17)
```

smdMES

Compute Effect Sizes for Multiple End-point Studies

Description

It computes the standardized mean differences and their asymptotic sampling covariance matrix for two multiple end-point studies with p effect sizes.

Usage

```
smdMES(m1, m2, V1, V2, n1, n2,
        homogeneity=c("covariance", "correlation", "none"),
        bias.adjust=TRUE, list.output=TRUE, lavaan.output=FALSE)
```

Arguments

| | |
|---------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| m1 | A vector of p sample means of the first group. |
| m2 | A vector of p sample means of the second group. |
| V1 | A p by p sample covariance matrix of the first group. |
| V2 | A p by p sample covariance matrix of the second group. |
| n1 | The sample size of the first group. |
| n2 | The sample size of the second group. |
| homogeneity | If it is <code>covariance</code> (the default), homogeneity of covariance matrices is assumed. The common standard deviations are used as the standardizers in calculating the effect sizes. If it is <code>correlation</code> , homogeneity of correlation is not assumed. The standard deviations of the first group are used as the standardizer in calculating the effect sizes. If it is <code>none</code> , no homogeneity assumption is made. The standard deviations of the first group are used as the standardizer in calculating the effect sizes. |
| bias.adjust | If it is <code>TRUE</code> (the default), the effect sizes are adjusted for small bias by multiplying $1 - 3/(4 * (n1 + n2) - 9)$. |
| list.output | If it is <code>TRUE</code> (the default), the effect sizes and their sampling covariance matrix are outputted as a list. If it is <code>FALSE</code> , they will be stacked into a vector. |
| lavaan.output | If it is <code>FALSE</code> (the default), the effect sizes and its sampling covariance matrix are reported. If it is <code>TRUE</code> , it outputs the fitted <code>lavaan-class</code> object. |

Details

Gleser and Olkin (2009) introduce formulas to calculate the standardized mean differences and their sampling covariance matrix for multiple end-point studies under the assumption of homogeneity of the covariance matrix. This function uses a structural equation modeling (SEM) approach introduced in Chapter 3 of Cheung (2015) to calculate the same estimates. The SEM approach is more flexible in two ways: (1) it allows homogeneity of covariance or correlation matrices or not; and (2) it allows users to test this assumption by checking the fitted `lavaan-class` object.

Author(s)

Mike W.-L. Cheung <mikewlcheung@nus.edu.sg>

References

- Cheung, M. W.-L. (2015). *Meta-analysis: A structural equation modeling approach*. Chichester, West Sussex: John Wiley & Sons, Inc.
- Cheung, M. W.-L. (2018). Computing multivariate effect sizes and their sampling covariance matrices with structural equation modeling: Theory, examples, and computer simulations. *Frontiers in Psychology*, *9*(1387). <https://doi.org/10.3389/fpsyg.2018.01387>
- Gleser, L. J., & Olkin, I. (2009). Stochastically dependent effect sizes. In H. Cooper, L. V. Hedges, & J. C. Valentine (Eds.), *The handbook of research synthesis and meta-analysis*. (2nd ed., pp. 357-376). New York: Russell Sage Foundation.

See Also

[Gleser94](#), [smdMTS](#), [calEffSizes](#)

Examples

```
## Not run:
## Sample means for the two constructs in Group 1
m1 <- c(2.5, 4.5)

## Sample means for the two constructs in Group 2
m2 <- c(3, 5)

## Sample covariance matrix in Group 1
V1 <- matrix(c(3,2,2,3), ncol=2)

## Sample covariance matrix in Group 2
V2 <- matrix(c(3.5,2.1,2.1,3.5), ncol=2)

## Sample size in Group 1
n1 <- 20

## Sample size in Group 2
n2 <- 25

## SMD with the assumption of homogeneity of covariance matrix
smdMES(m1, m2, V1, V2, n1, n2, homogeneity="cov", bias.adjust=TRUE,
```

```

lavaan.output=FALSE)

## SMD with the assumption of homogeneity of correlation matrix
smdMES(m1, m2, V1, V2, n1, n2, homogeneity="cor", bias.adjust=TRUE,
lavaan.output=FALSE)

## SMD without any assumption of homogeneity
smdMES(m1, m2, V1, V2, n1, n2, homogeneity="none", bias.adjust=TRUE,
lavaan.output=FALSE)

## Output the fitted lavaan model
## It provides a likelihood ratio test to test the null hypothesis of
## homogeneity of variances.
fit <- smdMES(m1, m2, V1, V2, n1, n2, homogeneity="cov", bias.adjust=TRUE,
lavaan.output=TRUE)

lavaan::summary(fit)

lavaan::parameterestimates(fit)

## End(Not run)

```

smdMTS

*Compute Effect Sizes for Multiple Treatment Studies***Description**

It computes the standardized mean differences and their asymptotic sampling covariance matrix for k multiple treatment studies. The first group is assumed as the control group.

Usage

```
smdMTS(m, v, n, homogeneity=c("variance", "none"), bias.adjust=TRUE,
all.comparisons=FALSE, list.output=TRUE, lavaan.output=FALSE)
```

Arguments

| | |
|--------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>m</code> | A vector of k sample means. |
| <code>v</code> | A vector of k sample variances. |
| <code>n</code> | A vector of k sample sizes. |
| <code>homogeneity</code> | If it is variance (the default), homogeneity of variances is assumed. The common standard deviation is used as the standardizer in calculating the effect sizes. If it is none, homogeneity of variances is not assumed. The standard deviation of the first group is used as the standardizer in calculating the effect sizes. |
| <code>bias.adjust</code> | If it is TRUE (the default), the effect sizes are adjusted for small bias by multiplying $1 - 3/(4 * (n1 + n2) - 9)$. |

| | |
|------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>all.comparisons</code> | If it is FALSE (the default), all groups (except the first group) are compared against the first group. If it is TRUE, all pairwise comparisons are calculated. This may be useful in network meta-analysis. |
| <code>list.output</code> | If it is TRUE (the default), the effect sizes and their sampling covariance matrix are outputted as a list. If it is FALSE, they will be stacked into a vector. |
| <code>lavaan.output</code> | If it is FALSE (the default), the effect sizes and its sampling covariance matrix are reported. If it is TRUE, it outputs the fitted <code>lavaan-class</code> object. |

Details

Gleser and Olkin (2009) introduce formulas to calculate the standardized mean differences and their sampling covariance matrix for multiple treatment studies under the assumption of homogeneity of the covariance matrix. This function uses a structural equation modeling (SEM) approach introduced in Chapter 3 of Cheung (2015) to calculate the same estimates. The SEM approach is more flexible in three ways: (1) it allows homogeneity of variances or not; (2) it allows users to test the assumption of homogeneity of variances by checking the fitted `lavaan-class` object; and (3) it may calculate all pairwise comparisons.

Author(s)

Mike W.-L. Cheung <mikewlcheung@nus.edu.sg>

References

- Cheung, M. W.-L. (2015). *Meta-analysis: A structural equation modeling approach*. Chichester, West Sussex: John Wiley & Sons, Inc.
- Cheung, M. W.-L. (2018). Computing multivariate effect sizes and their sampling covariance matrices with structural equation modeling: Theory, examples, and computer simulations. *Frontiers in Psychology*, *9*(1387). <https://doi.org/10.3389/fpsyg.2018.01387>
- Gleser, L. J., & Olkin, I. (2009). Stochastically dependent effect sizes. In H. Cooper, L. V. Hedges, & J. C. Valentine (Eds.), *The handbook of research synthesis and meta-analysis*. (2nd ed., pp. 357-376). New York: Russell Sage Foundation.

See Also

[Gleser94](#), [smdMES](#), [calEffSizes](#)

Examples

```
## Not run:
## Sample means for groups 1 to 3
m <- c(5,7,9)

## Sample variances
v <- c(10,11,12)

## Sample sizes
n <- c(50,52,53)
```

```

## Assuming homogeneity of variances
smdMTS(m, v, n, homogeneity = "var", bias.adjust=TRUE, all.comparisons=FALSE,
        lavaan.output=FALSE)

## Not assuming homogeneity of variances and comparing all pairwise groups
## Please note that the SD of the first group is used as the standardizer
smdMTS(m, v, n, homogeneity = "none", bias.adjust=TRUE, all.comparisons=TRUE,
        lavaan.output=FALSE)

## Output the fitted lavaan model
## It provides a likelihood ratio test to test the null hypothesis of
## homogeneity of variances.
fit <- smdMTS(m, v, n, homogeneity = "var", bias.adjust=FALSE, all.comparisons=FALSE,
              lavaan.output=TRUE)

lavaan::summary(fit)

lavaan::parameterestimates(fit)

## End(Not run)

```

 Stadler15

Correlations from Stadler et al. (2015)

Description

The data set includes correlations between complex problem solving and intelligence reported by Stadler et al. (2015).

Usage

```
data(Stadler15)
```

Details

A list of data with the following structure:

ID ID of the effect sizes

Authors Authors of the studies

Year Year of the studies

N Sample size

CPSMeasure Complex problem solving (CPS) measure

IntelligenceMeasure Intelligence measure

r Correlation between CPS and intelligence

v Sampling variance of r

Source

Stadler, M., Becker, N., Godker, M., Leutner, D., & Greiff, S. (2015). Complex problem solving and intelligence: A meta-analysis. *Intelligence*, **53**, 92-101.

summary

Summary Method for tssem1, wls, meta, and meta3LFIML Objects

Description

It summaries results for various class.

Usage

```
## S3 method for class 'tssem1FEM'
summary(object, ...)
## S3 method for class 'tssem1FEM.cluster'
summary(object, ...)
## S3 method for class 'tssem1REM'
summary(object, robust=FALSE, ...)
## S3 method for class 'wls'
summary(object, df.adjustment=0, ...)
## S3 method for class 'wls.cluster'
summary(object, df.adjustment=0, ...)
## S3 method for class 'meta'
summary(object, homoStat=TRUE, robust=FALSE, ...)
## S3 method for class 'meta3LFIML'
summary(object, allX=FALSE, robust=FALSE, ...)
## S3 method for class 'reml'
summary(object, ...)
## S3 method for class 'CorPop'
summary(object, ...)
## S3 method for class 'Cor3L'
summary(object, ...)
## S3 method for class 'bootuniR2'
summary(object, probs=c(0, 0.1, 0.5, 0.9, 1),
         cutoff.chisq.pvalue=0.05, cutoff.CFI=0.9, cutoff.SRMR=0.1,
         cutoff.RMSEA=0.05, ...)
## S3 method for class 'osmasem'
summary(object, fitIndices=FALSE, numObs, robust=FALSE, ...)
## S3 method for class 'tssem1FEM'
print.summary(x, ...)
## S3 method for class 'wls'
print.summary(x, ...)
## S3 method for class 'meta'
print.summary(x, ...)
## S3 method for class 'meta3LFIML'
```

```

print.summary(x, ...)
## S3 method for class 'reml'
print.summary(x, ...)
## S3 method for class 'CorPop'
print.summary(x, ...)
## S3 method for class 'Cor3L'
print.summary(x, ...)
## S3 method for class 'bootuniR2'
print.summary(x, ...)

```

Arguments

| | |
|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| object | An object returned from either class <code>tssem1FEM</code> , class <code>tssem1FEM.cluster</code> , class <code>tssem1REM</code> , class <code>wls</code> , class <code>wls.cluster</code> , class <code>meta</code> , class <code>meta3LFIML</code> , class <code>reml</code> or class <code>CorPop</code> . |
| x | An object returned from either class <code>summary.tssem1FEM</code> , class <code>summary.tssem1FEM.cluster</code> , class <code>summary.wls</code> , class <code>summary.meta</code> , class <code>summary.meta3LFIML</code> , class <code>summary.reml</code> or class <code>summary.CorPop</code> . |
| homoStat | Logical. Whether to conduct a homogeneity test on the effect sizes. |
| allX | Logical. Whether to report the predictors and the auxiliary variables. |
| robust | Logical. Whether to use robust standard error from imxRobustSE . |
| df.adjustment | Numeric. Adjust the degrees of freedom manually. It may be necessary if the calculated is incorrect when <code>diag.constraints=TRUE</code> . |
| probs | Quantiles for the parameter estimates. |
| cutoff.chisq.pvalue | Cutoff of the p-value for the chi-square statistic. |
| cutoff.CFI | The cutoff of the CFI. |
| cutoff.SRMR | The cutoff of the SRMR. |
| cutoff.RMSEA | The cutoff of the RMSEA. |
| fitIndices | Whether to calculate the chi-square statistic and various goodness-of-fit indices in <code>osmasem</code> . Note. It may take a while since statistics of the saturated and independence models are required. |
| numObs | The number of observations in calculating the fit statistics in <code>osmasem</code> . If it is missing, the total number of observations is used. |
| ... | Further arguments to be passed to printCoefmat |

Note

If the `OpenMx` `status1` is either 0 or 1, the estimation is considered fine. If the `OpenMx` `status1` is other values, it indicates estimation problems. Users should refer to <https://openmx.ssri.psu.edu/wiki/errors> for more details.

Author(s)

Mike W.-L. Cheung <mikewlcheung@nus.edu.sg>

See Also

[tssem1](#), [wls](#), [meta](#), [rem1](#), [rCor](#), [bootuniR2](#), [osmasem](#)

Tenenbaum02

Correlation coefficients reported by Tenenbaum and Leaper (2002)

Description

Forty-eight studies reported by Tenenbaum and Leaper (2002, Table 1).

Usage

```
data(Tenenbaum02)
```

Details

The variables are:

Authors Authors of the study

Year Year of publication

N Sample size

r Correlation between parents' gender schemas and their offspring's gender-related cognitions.

v Sampling variance of r

Publication_source Publication source: 1="top-tier journal", 2="second-tier journal or book chapter", 3="dissertation", 4="other unpublished study"

Author_gender Gender of the first author: "W"="woman", "M"="man"

Parent_type Parent type: "M"="mother", "F"="father", "MF"="mother and father"

Parent_predictor Parent predictor: "S"="self gender schema", "A"="gender attitudes about others"

Offspring_age Offspring age (months)

Offspring_type Offspring type: "D"="daughter", "S"="son", "DS"="daughter and son"

Offspring_outcome Offspring outcome: "S"="gender schema for self", "A"="gender attitudes toward others", "I"="gender-related interests and preferences", "W"="work-related attitudes"

Source

Tenenbaum, H. R., & Leaper, C. (2002). Are parents' gender schemas related to their children's gender-related cognitions? A meta-analysis. *Developmental Psychology*, 38(4), 615-630. <https://doi.org/10.1037/0012-1649.38.4.615>

Examples

```
## Not run:
data(Tenenbaum02)
```

```
## End(Not run)
```


tssem1

*First Stage of the Two-Stage Structural Equation Modeling (TSSEM)***Description**

It conducts the first stage analysis of TSSEM by pooling correlation/covariance matrices. `tssem1FEM()` and `tssem1REM()` use fixed- and random-effects models, respectively. `tssem1()` is a wrapper of these functions.

Usage

```
tssem1(Cov, n, method=c("REM","FEM"), cor.analysis = TRUE, cluster=NULL,
      RE.type=c("Diag", "Symm", "Zero", "User"), RE.startvalues=0.1,
      RE.lbound=1e-10, RE.constraints=NULL, I2="I2q",
      acov=c("weighted", "individual", "unweighted"), asyCovOld=FALSE,
      model.name=NULL, suppressWarnings=TRUE, silent=TRUE, run=TRUE, ...)
tssem1FEM(Cov, n, cor.analysis=TRUE, model.name=NULL,
          cluster=NULL, suppressWarnings=TRUE, silent=TRUE, run=TRUE, ...)
tssem1REM(Cov, n, cor.analysis=TRUE, RE.type=c("Diag", "Symm", "Zero","User"),
          RE.startvalues=0.1, RE.lbound=1e-10, RE.constraints=NULL,
          I2="I2q", acov=c("weighted", "individual", "unweighted"),
          asyCovOld=FALSE, model.name=NULL, suppressWarnings=TRUE,
          silent=TRUE, run=TRUE, ...)
```

Arguments

| | |
|-----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>Cov</code> | A list of correlation/covariance matrices |
| <code>n</code> | A vector of sample sizes |
| <code>method</code> | Either "REM" (default if missing) or "FEM". If it is "REM", a random-effects meta-analysis will be applied. If it is "FEM", a fixed-effects meta-analysis will be applied. |
| <code>cor.analysis</code> | Logical. The output is either a pooled correlation or a covariance matrix. |
| <code>cluster</code> | A character vector in <code>tssem3L1</code> and <code>tssemRobust1</code> or a vector of characters or numbers indicating the clusters in <code>tssem1</code> . Analyses will be conducted for each cluster. It will be ignored when <code>method="REM"</code> . |
| <code>RE.type</code> | Either "Diag", "Symm", "Zero" or "User". If it is "Diag", a diagonal matrix is used for the random effects meaning that the random effects are independent. If it is "Symm" (default if missing), a symmetric matrix is used for the random effects on the covariances among the correlation (or covariance) vectors. If it is "Zero", there is no random effects which is similar to the conventional Generalized Least Squares (GLS) approach to fixed-effects analysis. "User", the user has to specify the variance component via the <code>RE.constraints</code> argument. This argument will be ignored when <code>method="FEM"</code> . |
| <code>RE.startvalues</code> | Starting values on the diagonals of the variance component of the random effects. It will be ignored when <code>method="FEM"</code> . |

| | |
|-------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>RE.lbound</code> | Lower bounds on the diagonals of the variance component of the random effects. It will be ignored when <code>method="FEM"</code> . |
| <code>RE.constraints</code> | A $p^* \times p^*$ matrix specifying the variance components of the random effects, where p^* is the number of effect sizes. If the input is not a matrix, it is converted into a matrix by <code>as.matrix()</code> . The default is that all covariance/variance components are free. The format of this matrix follows <code>as.mxMatrix</code> . Elements of the variance components can be constrained equally by using the same labels. If a zero matrix is specified, it becomes a fixed-effects meta-analysis. |
| <code>I2</code> | Possible options are "I2q", "I2hm" and "I2am". They represent the I2 calculated by using a typical within-study sampling variance from the Q statistic, the harmonic mean and the arithmetic mean of the within-study sampling variances (Xiong, Miller, & Morris, 2010). More than one options are possible. If <code>intervals.type="LB"</code> , 95% confidence intervals on the heterogeneity indices will be constructed. |
| <code>acov</code> | If it is individual, the sampling variance-covariance matrices are calculated based on individual correlation/covariance matrix. If it is either unweighted or weighted (the default), the average correlation/covariance matrix is calculated based on the unweighted or weighted mean with the sample sizes. The average correlation/covariance matrix is used to calculate the sampling variance-covariance matrices. This argument is ignored with the <code>method="FEM"</code> argument. |
| <code>asyCovOld</code> | Whether the old <code>asyCov</code> is used. See <code>asyCov</code> . |
| <code>model.name</code> | A string for the model name in <code>mxModel</code> . |
| <code>suppressWarnings</code> | Logical. If TRUE, warnings are suppressed. It is passed to <code>mxRun</code> . |
| <code>silent</code> | Logical. An argument to be passed to <code>mxRun</code> |
| <code>run</code> | Logical. If FALSE, only return the mx model without running the analysis. |
| <code>...</code> | Further arguments to be passed to <code>mxRun</code> |

Value

Either an object of class `tssem1FEM` for fixed-effects TSSEM, an object of class `tssem1FEM.cluster` for fixed-effects TSSEM with `cluster` argument, or an object of class `tssem1REM` for random-effects TSSEM.

Author(s)

Mike W.-L. Cheung <mikewlcheung@nus.edu.sg>

References

- Cheung, M. W.-L. (2014). Fixed- and random-effects meta-analytic structural equation modeling: Examples and analyses in R. *Behavior Research Methods*, **46**, 29-40.
- Cheung, M. W.-L. (2013). Multivariate meta-analysis as structural equation models. *Structural Equation Modeling*, **20**, 429-454.

Cheung, M. W.-L., & Chan, W. (2005). Meta-analytic structural equation modeling: A two-stage approach. *Psychological Methods*, **10**, 40-64.

Cheung, M. W.-L., & Chan, W. (2009). A two-stage approach to synthesizing covariance matrices in meta-analytic structural equation modeling. *Structural Equation Modeling*, **16**, 28-53.

See Also

[wls](#), [Cheung09](#), [Becker92](#), [Digman97](#), [issp89](#), [issp05](#)

| | |
|--------------|---------------------------------------------------------------------------------------|
| tssemParaVar | <i>Estimate the heterogeneity (SD) of the parameter estimates of the TSSEM object</i> |
|--------------|---------------------------------------------------------------------------------------|

Description

It estimates the heterogeneity of the parameter estimates of the TSSEM objects using either the bootstrap or the delta methods.

Usage

```
tssemParaVar(tssem1.obj, tssem2.obj, method=c("bootstrap", "delta"),
             interval=0.8, Rep=50, output=c("data.frame", "matrices"),
             nonPD.pop=c("replace", "nearPD", "accept"))
```

Arguments

| | |
|------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| tssem1.obj | An object of class tssem1REM returned from tssem1() |
| tssem2.obj | An object of class wls returned from tssem2() or wls() |
| method | If it is bootstrap, random correlation matrices are sampled from the tssem1.obj by the parametric bootstrap. If it is delta, the delta method is used to estimate the heterogeneity of the parameter estimates. |
| interval | The desired interval, e.g., .8 or .95. |
| Rep | The number of parametric bootstrap. It is ignored when the method is delta. |
| output | Either a data.frame or matrices of the output. |
| nonPD.pop | If it is replace, generated non-positive definite matrices are replaced by generated new ones which are positive definite. If it is nearPD, they are replaced by nearly positive definite matrices by calling Matrix::nearPD(). If it is accept, they are accepted. |

Details

The bootstrap method is based on the discussion in Cheung (2018) and Yu et al. (2016). The delta method is an alternative method to obtain the heterogeneity.

Value

Either a data.frame or matrices of the output.

Author(s)

Mike W.-L. Cheung <mikewlcheung@nus.edu.sg>

References

Cheung, M. W.-L. (2018). Issues in solving the problem of effect size heterogeneity in meta-analytic structural equation modeling: A commentary and simulation study on Yu, Downes, Carter, and O'Boyle (2016). *Journal of Applied Psychology*, **103**, 787-803.

Yu, J. (Joya), Downes, P. E., Carter, K. M., & O'Boyle, E. H. (2016). The problem of effect size heterogeneity in meta-analytic structural equation modeling. *Journal of Applied Psychology*, *101*, 1457-1473.

See Also

[bootuniR1](#), [bootuniR2](#), [Nohe15](#)

 uniR1

First Stage analysis of the univariate R (uniR) approach

Description

It conducts the first stage analysis of the uniR analysis by pooling elements of the correlation coefficients individually.

Usage

```
uniR1(Cor, n, ...)
```

Arguments

| | |
|-----|-----------------------------------------------|
| Cor | A list of correlation matrices |
| n | A vector of sample sizes |
| ... | Further arguments which are currently ignored |

Details

This function implements the univariate r approach proposed by Viswesvaran and Ones (1995) to conduct meta-analytic structural equation modeling (MASEM). It uses Schmidt and Hunter's approach to combine correlation coefficients. It is included in this package for research interests. The two-stage structural equation modeling (TSSEM) approach is preferred (e.g., Cheung, 2015; Cheung & Chan, 2005).

Value

An object of class uniR1 of the original data, the sample sizes, the harmonic mean of sample sizes, the average correlation matrix, the standard errors of the correlation matrix, and the standard deviations (heterogeneity) of the correlation matrix.

Author(s)

Mike W.-L. Cheung <mikewlcheung@nus.edu.sg>

References

- Cheung, M. W.-L. (2015). *Meta-analysis: A structural equation modeling approach*. Chichester, West Sussex: John Wiley & Sons, Inc.
- Cheung, M. W.-L., & Chan, W. (2005). Meta-analytic structural equation modeling: A two-stage approach. *Psychological Methods*, **10**, 40-64.
- Schmidt, F. L., & Hunter, J. E. (2015). *Methods of meta-analysis: Correcting error and bias in research findings (3rd ed.)*. Thousand Oaks, CA: Sage.
- Viswesvaran, C., & Ones, D. S. (1995). Theory testing: Combining psychometric meta-analysis and structural equations modeling. *Personnel Psychology*, **48**, 865-885.

See Also

[uniR2](#), [Becker09](#)

 uniR2

Second Stage analysis of the univariate R (uniR) approach

Description

It conducts the second stage analysis of the uniR analysis by fitting structural equation models on the average correlation matrix.

Usage

```
uniR2mx(x, RAM = NULL, Amatrix = NULL, Smatrix = NULL, Fmatrix = NULL,
        model.name=NULL, suppressWarnings=TRUE, silent=TRUE,
        run=TRUE, ...)
uniR2lavaan(x, model, ...)
```

Arguments

- | | |
|---------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x | An object of class uniR1 from uniR1 . |
| RAM | A RAM object including a list of matrices of the model returned from lavaan2RAM . |
| Amatrix | If RAM is not specified, an Amatrix is required. An asymmetric matrix in the RAM specification with MxMatrix-class . If it is a matrix, it will be converted into MxMatrix-class by the <code>as.mxMatrix</code> function. |

| | |
|-------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>Smatrix</code> | If RAM is not specified, an <code>Smatrix</code> is required. A symmetric matrix in the RAM specification with <code>MxMatrix-class</code> . If it is a matrix, it will be converted into <code>MxMatrix-class</code> by the <code>as.mxMatrix</code> function. |
| <code>Fmatrix</code> | If RAM is not specified, an <code>Fmatrix</code> is required. A filter matrix in the RAM specification with <code>MxMatrix-class</code> . If it is NULL (the default), an identity matrix with the same dimensions of <code>Cov</code> will be created. If it is a matrix, it will be converted into <code>MxMatrix-class</code> by the <code>as.mxMatrix</code> function. It is not required when there is no latent variable. |
| <code>model.name</code> | A string for the model name in <code>mxModel</code> . If it is missing, the default is "UniR2". |
| <code>suppressWarnings</code> | Logical. If TRUE, warnings are suppressed. It is passed to <code>mxRun</code> . |
| <code>silent</code> | Logical. An argument to be passed to <code>mxRun</code> |
| <code>run</code> | Logical. If FALSE, only return the mx model without running the analysis. |
| <code>model</code> | A model specified using lavaan syntax see <code>model.syntax</code> |
| <code>...</code> | Further arguments to be passed to either <code>mxRun</code> or <code>sem</code> . For <code>sem</code> , <code>fixed.x=FALSE</code> is passed automatically. |

Details

This function implements the univariate r approach proposed by Viswesvaran and Ones (1995) to conduct meta-analytic structural equation modeling (MASEM). It treats the average correlation matrix as if it was a covariance matrix in fitting structural equation models. The harmonic mean of the sample sizes in combining correlation coefficients is used as the sample size in fitting structural equation models. It is included in this package for research interests. The two-stage structural equation modeling (TSSEM) approach is preferred (e.g., Cheung, 2015; Cheung & Chan, 2005).

Value

A fitted object returned from `mxRun` or `sem`.

Author(s)

Mike W.-L. Cheung <mikewlcheung@nus.edu.sg>

References

- Cheung, M. W.-L. (2015). *Meta-analysis: A structural equation modeling approach*. Chichester, West Sussex: John Wiley & Sons, Inc.
- Cheung, M. W.-L., & Chan, W. (2005). Meta-analytic structural equation modeling: A two-stage approach. *Psychological Methods*, **10**, 40-64.
- Viswesvaran, C., & Ones, D. S. (1995). Theory testing: Combining psychometric meta-analysis and structural equations modeling. *Personnel Psychology*, **48**, 865-885.

See Also

[uniR1](#), [lavaan2RAM](#), [Becker09](#)

vanderPol17

Dataset on the effectiveness of multidimensional family therapy in treating adolescents with multiple behavior problems

Description

This dataset includes 61 effect sizes from 19 manuscripts nested from 8 studies reported by van der Pol et al. (2017). It studies the effectiveness of multidimensional family therapy in treating adolescents with multiple behavior problems.

Usage

```
data(vanderPol17)
```

Details

A list of data with the following structure:

Number Number of the effect size.

Study Authors of the studies.

N Total sample size.

N_target Sample size in the target group.

N_control Sample size in the control group.

Comparison_condition Either cognitive behavioral therapy (CBT), combined treatment (CT) or group therapy (Group).

Study_ID Level-3 cluster.

Age_mean Mean age of the participants.

Flow_up Follow-up duration (in months).

Per_Males Percentage of males.

Per_Minorities Percentage of minorities.

Per_Conduct_disorder Percentage of participants with conduct disorder

Per_Severe_cannabis_users Percentage of participants of severe cannabis use.

Outcome_measure Either substance abuse, delinquency, externalizing and internalizing psychopathology, and family functioning

d Effect size in Cohen's d.

v Sampling variance of d

Source

van der Pol, T. M., Hoeve, M., Noom, M. J., Stams, G. J. J. M., Doreleijers, T. A. H., van Domburgh, L., & Vermeiren, R. R. J. M. (2017). Research Review: The effectiveness of multidimensional family therapy in treating adolescents with multiple behavior problems - a meta-analysis. *Journal of Child Psychology and Psychiatry*, **58**(5), 532-545. <https://doi.org/10.1111/jcpp.12685>

Examples

```
data(vanderPol17)
```

VarCorr*Extract Variance-Covariance Matrix of the Random Effects*

Description

It extracts the variance-covariance matrix of the random effects (variance component) from either the meta or osmasem objects.

Usage

```
VarCorr(x, ...)
```

Arguments

| | |
|-----|------------------------------------------------------|
| x | An object returned from either class meta or osmasem |
| ... | Further arguments; currently none is used |

Value

A variance-covariance matrix of the random effects.

Note

It is similar to `coef(object, select="random")` in `tssem`. The main difference is that `coef()` returns a vector while `VarCorr()` returns its correspondent matrix.

Author(s)

Mike W.-L. Cheung <mikewlcheung@nus.edu.sg>

See Also

[coef](#), [vcov](#)

Examples

```
## Multivariate meta-analysis on the log of the odds
## The conditional sampling covariance is 0
bcg <- meta(y=cbind(ln_Odd_V, ln_Odd_NV), data=BCG,
           v=cbind(v_ln_Odd_V, cov_V_NV, v_ln_Odd_NV))
VarCorr(bcg)
```

vcov *Extract Covariance Matrix Parameter Estimates from Objects of Various Classes*

Description

It extracts the variance-covariance matrix of the parameter estimates from objects of various classes.

Usage

```
## S3 method for class 'tssem1FEM'
vcov(object, ...)
## S3 method for class 'tssem1FEM.cluster'
vcov(object, ...)
## S3 method for class 'tssem1REM'
vcov(object, select = c("all", "fixed", "random"), robust=FALSE, ...)
## S3 method for class 'wls'
vcov(object, ...)
## S3 method for class 'wls.cluster'
vcov(object, ...)
## S3 method for class 'meta'
vcov(object, select = c("all", "fixed", "random"), robust=FALSE, ...)
## S3 method for class 'meta3LFIML'
vcov(object, select = c("all", "fixed", "random", "allX"), robust=FALSE, ...)
## S3 method for class 'reml'
vcov(object, ...)
## S3 method for class 'MxRAMModel'
vcov(object, ...)
## S3 method for class 'osmasem'
vcov(object, select=c("fixed", "all", "random"), robust=FALSE, ...)
```

Arguments

| | |
|--------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| object | An object returned from objects of various classes |
| select | Select all for both fixed- and random-effects parameters, fixed for the fixed-effects parameters or random for the random-effects parameters. For meta3LFIML objects, allX is used to extract all parameters including the predictors and auxiliary variables. |
| robust | Logical. Whether to use robust standard error from imxRobustSE . |
| ... | Further arguments; currently not in use except for <code>tssemRobust1</code> , which to be passed to robust . |

Value

A variance-covariance matrix of the parameter estimates.

Note

vcov returns NA when the `diag.constraints=TRUE` argument is used in wls objects.

Author(s)

Mike W.-L. Cheung <mikewlcheung@nus.edu.sg>

See Also

[tssem1](#), [wls](#), [meta](#), [reml](#)

Examples

```
## Random-effects meta-analysis
model1 <- meta(y=yi, v=vi, data=Hox02)
vcov(model1)

## Fixed-effects only
vcov(model1, select="fixed")

## Random-effects only
vcov(model1, select="random")
```

vec2symMat

Convert a Vector into a Symmetric Matrix

Description

It converts a vector into a symmetric matrix by filling up the elements into the lower triangle of the matrix.

Usage

```
vec2symMat(x, diag = TRUE, byrow = FALSE)
```

Arguments

| | |
|-------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x | A vector of numerics or characters |
| diag | Logical. If it is TRUE (the default), the diagonals of the created matrix are replaced by elements of x; otherwise, the diagonals of the created matrix are replaced by "1". |
| byrow | Logical. If it is FALSE (the default), the created matrix is filled by columns; otherwise, the matrix is filled by rows. |

Value

A symmetric square matrix based on column major

Author(s)

Mike W.-L. Cheung <mikewlcheung@nus.edu.sg>

See Also

[matrix2bdiag](#)

Examples

```
vec2symMat(1:6)
#      [,1] [,2] [,3]
# [1,]  1   2   3
# [2,]  2   4   5
# [3,]  3   5   6

vec2symMat(1:6, diag=FALSE)
#      [,1] [,2] [,3] [,4]
# [1,]  1   1   2   3
# [2,]  1   1   4   5
# [3,]  2   4   1   6
# [4,]  3   5   6   1

vec2symMat(letters[1:6])
#      [,1] [,2] [,3]
# [1,] "a"  "b"  "c"
# [2,] "b"  "d"  "e"
# [3,] "c"  "e"  "f"
```

wls

Conduct a Correlation/Covariance Structure Analysis with WLS

Description

It fits a correlation or covariance structure with weighted least squares (WLS) estimation method where the inverse of the asymptotic covariance matrix is used as the weight matrix. `tssem2` conducts the second stage analysis of the two-stage structural equation modeling (TSSEM). `tssem2` is a wrapper of `wls`.

Usage

```
wls(Cov, aCov, n, RAM=NULL, Amatrix=NULL, Smatrix=NULL, Fmatrix=NULL,
    diag.constraints=FALSE, cor.analysis=TRUE, intervals.type=c("z", "LB"),
    mx.algebras=NULL, mxModel.Args=NULL, subset.variables=NULL, model.name=NULL,
    suppressWarnings=TRUE, silent=TRUE, run=TRUE, ...)
tssem2(tssem1.obj, RAM=NULL, Amatrix=NULL, Smatrix=NULL, Fmatrix=NULL,
    diag.constraints=FALSE, intervals.type=c("z", "LB"), mx.algebras=NULL,
    mxModel.Args=NULL, subset.variables=NULL, model.name=NULL, suppressWarnings=TRUE,
    silent=TRUE, run=TRUE, ...)
```

Arguments

| | |
|-------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>tssem1.obj</code> | An object of either class <code>tssem1FEM</code> , class <code>tssem1FEM.cluster</code> or class <code>tssem1REM</code> returned from <code>tssem1()</code> |
| <code>Cov</code> | A $p \times p$ sample correlation/covariance matrix where p is the number of variables. |
| <code>aCov</code> | A $p^* \times p^*$ asymptotic sampling covariance matrix of either <code>vechs</code> (<code>Cov</code>) or <code>vech</code> (<code>Cov</code>) where $p^* = p(p - 1)/2$ for correlation matrix and $p^* = p(p + 1)/2$ for covariance matrix. |
| <code>n</code> | Sample size. |
| <code>RAM</code> | A RAM object including a list of matrices of the model returned from <code>lavaan2RAM</code> . |
| <code>Amatrix</code> | If RAM is not specified, an <code>Amatrix</code> is required. An asymmetric matrix in the RAM specification with <code>MxMatrix-class</code> . If it is NULL, a matrix of zero will be created. If it is a matrix, it will be converted into <code>MxMatrix-class</code> by the <code>as.mxMatrix</code> function. |
| <code>Smatrix</code> | If RAM is not specified, an <code>Smatrix</code> is required. A symmetric matrix in the RAM specification with <code>MxMatrix-class</code> . If it is a matrix, it will be converted into <code>MxMatrix-class</code> by the <code>as.mxMatrix</code> function. |
| <code>Fmatrix</code> | A filter matrix in the RAM specification with <code>MxMatrix-class</code> . If it is NULL (the default), an identity matrix with the same dimensions of <code>Cov</code> will be created. If it is a matrix, it will be converted into <code>MxMatrix-class</code> by the <code>as.mxMatrix</code> function. It is not required when there is no latent variable. |
| <code>diag.constraints</code> | Logical. This argument is ignored when <code>cor.analysis=FALSE</code> . If <code>diag.constraints=TRUE</code> , the diagonals of the model implied matrix would be constrained at 1 by nonlinear constraints. The drawback is that standard error will not be generated. Parametric bootstrap is used to estimate the standard error by drawing samples from $\mathcal{N}(\text{vech}(\text{Cov}), \text{asyCov})$ for covariance analysis and $\mathcal{N}(\text{vechs}(\text{Cov}), \text{asyCov})$ for correlation analysis while <code>asyCov</code> is treated as fixed. This process is computationally intensive. A better approach is to request likelihood-based confidence intervals (CIs) by specifying <code>intervals.type="LB"</code> . If <code>diag.constraints=FALSE</code> and <code>cor.analysis=TRUE</code> , the diagonals are automatically constrained as ones by treating the error variances as computed values rather than as parameters. Since the error variances are not parameters, they are not reported. |
| <code>cor.analysis</code> | Logical. Analysis of correlation or covariance structure. If <code>cor.analysis=TRUE</code> , <code>vechs</code> is used to vectorize <code>S</code> ; otherwise, <code>vech</code> is used to vectorize <code>S</code> . |
| <code>intervals.type</code> | Either <code>z</code> (default if missing) or <code>LB</code> . If it is <code>z</code> , it calculates the 95% Wald CIs based on the <code>z</code> statistic. If it is <code>LB</code> , it calculates the 95% likelihood-based CIs on the parameter estimates. Please note that the <code>z</code> values and their associated <code>p</code> values are based on the <code>z</code> statistic. They are not related to the likelihood-based CIs. |
| <code>mx.algebras</code> | A list of <code>mxMatrix</code> or <code>mxAlgebra</code> objects on the <code>Amatrix</code> , <code>Smatrix</code> , and <code>Fmatrix</code> . It can be used to define new functions of parameters and their LBCIs. For example, if the regression coefficients to calculate an indirect effect are stored in <code>A[1,2]</code> and <code>A[1,3]</code> , we may define <code>list(ind=mxAlgebra(Amatrix[1,2]*Amatrix[1,3], name="ind"))</code> See the examples in Becker92 and Hunter83 . It should be noted that <code>Fmatrix</code> , <code>Amatrix</code> , <code>Smatrix</code> , <code>Iden</code> (a $p \times p$ identity matrix), <code>sampleS</code> (sample |

| | |
|-------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| | correlation or covariance matrix), impliedS1, impliedS (model implied correlation or covariance matrix), vecS, invAcov, obj, One, select and constraint and Ematrix (computed error variances when <code>diag.constraints=FALSE</code>) have been defined internally. You should not create new matrices using these names. |
| <code>mxModel.Args</code> | A list of arguments passed to <code>mxModel</code> . These include, for example, additional <code>mxMatrix</code> and <code>mxConstraint</code> . |
| <code>model.name</code> | A string for the model name in <code>mxModel</code> . If it is missing, the default is "TSSEM2 (or WLS) Analysis of Correlation Structure" for <code>cor.analysis=TRUE</code> and "TSSEM2 (or WLS) Analysis of Covariance Structure" for <code>cor.analysis=FALSE</code> . |
| <code>subset.variables</code> | An optional character vector of variable names to select variables in the analysis. For example, there are 10 variables in <code>Cov</code> , say, <code>x1</code> to <code>x10</code> . We may use <code>c("x1", "x2", "x3")</code> to select three variables in the analysis. Please note that this argument does not reorder the data. That is, <code>c("x3", "x2", "x1")</code> is the same as <code>c("x1", "x2", "x3")</code> . |
| <code>suppressWarnings</code> | Logical. If <code>TRUE</code> , warnings are suppressed. The argument to be passed to <code>mxRun</code> . |
| <code>silent</code> | Logical. An argument to be passed to <code>mxRun</code> |
| <code>run</code> | Logical. If <code>FALSE</code> , only return the <code>mx</code> model without running the analysis. |
| <code>...</code> | Further arguments to be passed to <code>mxRun</code> . |

Value

An object of class `wls` with a list of

| | |
|------------------------------|---------------------------------------------------------------------------------------|
| <code>call</code> | The matched call |
| <code>Cov</code> | Input data of either a covariance or correlation matrix |
| <code>asyCov</code> | The asymptotic covariance matrix of the input data |
| <code>noObservedStat</code> | Number of observed statistics |
| <code>n</code> | Sample size |
| <code>cor.analysis</code> | logical |
| <code>noConstraints</code> | Number of constraints imposed on <code>S</code> |
| <code>indepModelChisq</code> | Chi-square statistic of the independent model returned by <code>.indepwlsChisq</code> |
| <code>indepModelDf</code> | Degrees of freedom of the independent model returned by <code>.indepwlsChisq</code> |
| <code>mx.fit</code> | A fitted object returned from <code>mxRun</code> |

Note

If the input is a list of `tssem1.obj`, it returns a list of results for each cluster.

Author(s)

Mike W.-L. Cheung <mikewlcheung@nus.edu.sg>

References

- Bentler, P.M., & Savalei, V. (2010). Analysis of correlation structures: current status and open problems. In Kolenikov, S., Thombs, L., & Steinley, D. (Eds.). *Recent Methodological Developments in Social Science Statistics* (pp. 1-36). Hoboken, NJ: Wiley.
- Cheung, M. W.-L. (2010). Fixed-effects meta-analyses as multiple-group structural equation models. *Structural Equation Modeling*, **17**, 481-509.
- Cheung, M. W.-L. (2014). Fixed- and random-effects meta-analytic structural equation modeling: Examples and analyses in R. *Behavior Research Methods*, **46**, 29-40.
- Cheung, M. W.-L., & Chan, W. (2005). Meta-analytic structural equation modeling: A two-stage approach. *Psychological Methods*, **10**, 40-64.
- Cheung, M. W.-L., & Chan, W. (2009). A two-stage approach to synthesizing covariance matrices in meta-analytic structural equation modeling. *Structural Equation Modeling*, **16**, 28-53.
- Joreskog, K. G., Sorbom, D., Du Toit, S., & Du Toit, M. (1999). *LISREL 8: New Statistical Features*. Chicago: Scientific Software International.
- McArdle, J. J., & MacDonald, R. P. (1984). Some algebraic properties of the Reticular Action Model for moment structures. *British Journal of Mathematical and Statistical Psychology*, **37**, 234-251.

See Also

[tssem1](#), [Becker92](#), [Digman97](#), [Hunter83](#), [issp89](#), [issp05](#)

Examples

```
## Not run:
#### Analysis of correlation structure
R1.labels <- c("a1", "a2", "a3", "a4")

R1 <- matrix(c(1.00, 0.22, 0.24, 0.18,
              0.22, 1.00, 0.30, 0.22,
              0.24, 0.30, 1.00, 0.24,
              0.18, 0.22, 0.24, 1.00), ncol=4, nrow=4,
            dimnames=list(R1.labels, R1.labels))

n <- 1000
acovR1 <- asyCov(R1, n)

#### One-factor CFA model using lavaan specification
model1 <- "f =~ a1 + a2 + a3 + a4"

RAM1 <- lavaan2RAM(model1, obs.variables=R1.labels)

wls.fit1a <- wls(Cov=R1, aCov=acovR1, n=n, RAM=RAM1,
               cor.analysis=TRUE, intervals="LB")
summary(wls.fit1a)

## One-factor CFA model using RAM specification
(A1 <- cbind(matrix(0, nrow=5, ncol=4),
            matrix(c("0.2*a1", "0.2*a2", "0.2*a3", "0.2*a4", 0),
                  ncol=1)))
```

```

(S1 <- Diag(c("0.2*e1", "0.2*e2", "0.2*e3", "0.2*e4", 1)))

## The first 4 variables are observed while the last one is latent.
(F1 <- create.Fmatrix(c(1,1,1,1,0), name="F1"))

wls.fit1b <- wls(Cov=R1, aCov=acovR1, n=n, Fmatrix=F1, Smatrix=S1, Amatrix=A1,
                cor.analysis=TRUE, intervals="LB")
summary(wls.fit1b)

## Select 3 variables to analyze
model2 <- "f =~ a1 + a2 + a3"

RAM2 <- lavaan2RAM(model2, obs.variables=R1.labels[-4])

wls.fit1c <- wls(Cov=R1, aCov=acovR1, n=n, RAM=RAM2,
                cor.analysis=TRUE, subset.variables=c("a1", "a2", "a3"))
summary(wls.fit1c)

#### Multiple regression analysis using lavaan specification
R2.labels <- c("y", "x1", "x2")

R2 <- matrix(c(1.00, 0.22, 0.24,
              0.22, 1.00, 0.30,
              0.24, 0.30, 1.00), ncol=3, nrow=3,
            dimnames=list(R2.labels, R2.labels))
acovR2 <- asyCov(R2, n)

model3 <- "y ~ x1 + x2
          ## Variances of x1 and x2 are 1
          x1 ~~ 1*x1
          x2 ~~ 1*x2
          ## x1 and x2 are correlated
          x1 ~~ x2"

RAM3 <- lavaan2RAM(model3, obs.variables=R2.labels)

wls.fit2a <- wls(Cov=R2, aCov=acovR2, n=n, RAM=RAM3,
                cor.analysis=TRUE, intervals="z")
summary(wls.fit2a)

#### Multiple regression analysis using RAM specification

## A2: Regression coefficients
#   y x1 x2
# y   F T T
# x1  F F F
# x2  F F F
(A2 <- mxMatrix("Full", ncol=3, nrow=3, byrow=TRUE,
                free=c(FALSE, rep(TRUE, 2), rep(FALSE, 6)), name="A2"))

## S2: Covariance matrix of free parameters

```

```

#   y x1 x2
# y   T F F
# x1  F F F
# x2  F T F
(S2 <- mxMatrix("Symm", ncol=3, nrow=3, values=c(0.2,0,0,1,0.2,1),
               labels=c("Var_y", NA, NA, NA, "Cov_x1_x2", NA),
               free=c(TRUE,FALSE,FALSE,FALSE,TRUE,FALSE), name="S2"))

## F may be ignored as there is no latent variable.
wls.fit2b <- wls(Cov=R2, aCov=acovR2, n=n, Amatrix=A2, Smatrix=S2,
                cor.analysis=TRUE, intervals="LB")
summary(wls.fit2b)

#### Analysis of covariance structure using lavaan specification
R3.labels=c("a1", "a2", "a3", "a4")

R3 <- matrix(c(1.50, 0.22, 0.24, 0.18,
              0.22, 1.60, 0.30, 0.22,
              0.24, 0.30, 1.80, 0.24,
              0.18, 0.22, 0.24, 1.30), ncol=4, nrow=4,
             dimnames=list(R3.labels, R3.labels))
n <- 1000
acovS3 <- asyCov(R3, n, cor.analysis=FALSE)

model3 <- "f =~ a1 + a2 + a3 + a4"

RAM3 <- lavaan2RAM(model3, obs.variables=R3.labels)

wls.fit3a <- wls(Cov=R3, aCov=acovS3, n=n, RAM=RAM3,
                cor.analysis=FALSE)
summary(wls.fit3a)

#### Analysis of covariance structure using RAM specification
(A3 <- cbind(matrix(0, nrow=5, ncol=4),
             matrix(c("0.2*a1", "0.2*a2", "0.2*a3", "0.2*a4", 0), ncol=1)))

(S3 <- Diag(c("0.2*e1", "0.2*e2", "0.2*e3", "0.2*e4", 1)))

F3 <- c(TRUE,TRUE,TRUE,TRUE,FALSE)
(F3 <- create.Fmatrix(F3, name="F3", as.mxMatrix=FALSE))

wls.fit3b <- wls(Cov=R3, aCov=acovS3, n=n, Amatrix=A3, Smatrix=S3,
                Fmatrix=F3, cor.analysis=FALSE)
summary(wls.fit3b)

## End(Not run)

```


Description

Between 1990 and 1993, 57,561 adults aged 18 and above from 42 nations were interviewed by local academic institutes in Eastern European nations and by professional survey organizations in other nations. The standardized mean difference (SMD) between males and females on life satisfaction and life control in each country were calculated as the effect sizes. Positive values indicate that males have higher scores than females do.

Usage

```
data(wvs94a)
```

Details

The variables are:

country Country

lifesat SMD on life satisfaction

lifecon SMD on life control

lifesat_var Sampling variance of lifesat

inter_cov Sampling covariance between lifesat and lifecon

lifecon_var Sampling variance of lifecon

gnp Gross National Product

Source

World Values Study Group. (1994). World Values Survey, 1981-1984 and 1990-1993 [Computer file]. *Ann Arbor, MI: Inter-university Consortium for Political and Social Research*.

References

Au, K., & Cheung, M. W.-L. (2004). Intra-cultural variation and job autonomy in 42 countries. *Organization Studies*, **25**, 1339-1362.

Cheung, M. W.-L. (2013). Multivariate meta-analysis as structural equation models. *Structural Equation Modeling*, **20**, 429-454.

Examples

```
## Not run:
data(wvs94a)

## Random-effects model
random.ma1 <- meta(y=cbind(lifesat, lifecon),
                  v=cbind(lifesat_var, inter_cov, lifecon_var), data=wvs94a,
                  model.name="Random effects model")
summary(random.ma1)

## Random-effects model with both population effect sizes fixed at 0
random.ma2 <- meta(y=cbind(lifesat, lifecon),
```

```

        v=cbind(lifesat_var, inter_cov, lifecon_var), data=wvs94a,
        intercept.constraints=matrix(0, nrow=1, ncol=2),
        model.name="Effect sizes are fixed at 0")
summary(random.ma2)

## Compare the nested models
anova(random.ma1, random.ma2)

## Fixed-effects model by fixing the variance component at 0
fixed.ma <- meta(y=cbind(lifesat, lifecon),
                v=cbind(lifesat_var, inter_cov, lifecon_var), data=wvs94a,
                RE.constraints=matrix(0, ncol=2, nrow=2),
                model.name="Fixed effects model")
summary(fixed.ma)

## Mixed-effects model
## gnp is divided by 10000 and centered by using
## scale(gnp/10000, scale=FALSE)
mixed.ma1 <- meta(y=cbind(lifesat, lifecon),
                 v=cbind(lifesat_var, inter_cov, lifecon_var),
                 x=scale(gnp/10000, scale=FALSE), data=wvs94a,
                 model.name="GNP as a predictor")
summary(mixed.ma1)

## Mixed-effects model with equal regression coefficients
mixed.ma2 <- meta(y=cbind(lifesat, lifecon),
                 v=cbind(lifesat_var, inter_cov, lifecon_var),
                 x=scale(gnp/10000, scale=FALSE), data=wvs94a,
                 coef.constraints=matrix(c("0.0*Eq_slope",
                                         "0.0*Eq_slope"), nrow=2),
                 model.name="GNP as a predictor with equal slope")
summary(mixed.ma2)

## Compare the nested models
anova(mixed.ma1, mixed.ma2)

## Plot the multivariate effect sizes
plot(random.ma1, main="Estimated effect sizes and their 95% confidence ellipses",
      axis.label=c("Gender difference on life satisfaction",
                  "Gender difference on life control"))

## End(Not run)

```

wvs94b

*Forty-four Covariance Matrices on Life Satisfaction, Job Satisfaction,
and Job Autonomy*

Description

Between 1990 and 1993, 57,561 adults aged 18 and above from 42 nations were interviewed by local academic institutes in Eastern European nations and by professional survey organizations in other

nations. The covariance matrices among Life Satisfaction, Job Satisfaction, and Job Autonomy were calculated.

Usage

```
data(wvs94b)
```

Details

The variables are:

data Covariance matrix among Life Satisfaction (LS), Job Satisfaction (JS), and Job Autonomy (JA)

n Sample size in the country

Source

World Values Study Group. (1994). World Values Survey, 1981-1984 and 1990-1993 [Computer file]. *Ann Arbor, MI: Inter-university Consortium for Political and Social Research*.

References

Au, K., & Cheung, M. W.-L. (2004). Intra-cultural variation and job autonomy in 42 countries. *Organization Studies*, **25**, 1339-1362.

Cheung, M.W.-L., & Cheung, S.-F. (2016). Random-effects models for meta-analytic structural equation modeling: Review, issues, and illustrations. *Research Synthesis Methods*, **7**, 140-155.

Examples

```
## Not run:
data(wvs94b)

## Get the indirect and the direct effects and
## their sampling covariance matrices for each study
indirect1 <- indirectEffect(wvs94b$data, wvs94b$n)
indirect1

## Multivariate meta-analysis on the indirect and direct effects
indirect2 <- meta(indirect1[, c("ind_eff", "dir_eff")],
                 indirect1[, c("ind_var", "ind_dir_cov", "dir_var")])

summary(indirect2)

## End(Not run)
```

Index

- * **bootuniR**
 - bootuniR1, 30
 - bootuniR2, 31
- * **compute effect sizes**
 - indirectEffect, 72
- * **datasets**
 - Aloe14, 5
 - BCG, 15
 - Becker09, 18
 - Becker83, 22
 - Becker92, 23
 - Becker94, 25
 - Berkey98, 27
 - Boer16, 29
 - Bornmann07, 32
 - Cheung00, 37
 - Cheung09, 39
 - Cooke16, 42
 - Cooper03, 44
 - Digman97, 57
 - Gleser94, 60
 - Gnamb18, 61
 - HedgesOlkkin85, 62
 - Hox02, 65
 - Hunter83, 66
 - issp05, 74
 - issp89, 76
 - Jaramillo05, 78
 - Kalaian96, 79
 - Mak09, 83
 - Mathieu15, 84
 - Nam03, 95
 - Nohe15, 96
 - Norton13, 99
 - Roorda11, 119
 - Sca1co17, 120
 - Stadler15, 125
 - Tenenbaum02, 128
 - vanderPol17, 135
 - wvs94a, 144
 - wvs94b, 146
- * **meta-analysis**
 - asyCov, 13
 - calEffSizes, 34
 - homoStat, 63
 - meta, 88
 - meta3L, 92
 - reml, 113
 - reml3L, 116
 - smdMES, 121
 - smdMTS, 123
- * **meta**
 - rerun, 118
- * **methods**
 - anova, 7
 - coef, 40
 - lavaan2RAM, 80
 - meta2semPlot, 91
 - plot, 105
 - print, 109
 - summary, 126
 - VarCorr, 136
 - vcov, 137
- * **osmasem3L**
 - create.Tau2, 52
 - osmasemR2, 102
 - osmasemSRMR, 103
 - rerun, 118
- * **osmasem**
 - Cor2DataFrame, 45
 - create.Tau2, 52
 - create.V, 53
 - create.vechsR, 54
 - osmasem, 100
 - osmasemR2, 102
 - osmasemSRMR, 103
 - rerun, 118
- * **package**

- metaSEM-package, 4
- * **tssem**
 - lavaan2RAM, 80
 - meta2semPlot, 91
 - rerun, 118
 - tssem1, 129
 - tssemParaVar, 131
 - wls, 139
- * **uniR**
 - uniR1, 132
 - uniR2, 133
- * **utilities**
 - as.mxAlgebra, 8
 - as.mxMatrix, 10
 - as.symMatrix, 12
 - bdiagMat, 16
 - bdiagRep, 17
 - checkRAM, 36
 - create.Fmatrix, 47
 - create.modMatrix, 48
 - create.mxMatrix, 49
 - create.mxModel, 50
 - Diag, 56
 - impliedR, 69
 - is.pd, 73
 - list2matrix, 82
 - matrix2bdiag, 86
 - pattern.n, 103
 - pattern.na, 104
 - rCor, 110
 - readData, 111
 - vec2symMat, 138
- * **wls**
 - rerun, 118
- Aloe14, 5
- anova, 7
- as.mxAlgebra, 8
- as.mxMatrix, 9, 10, 12, 36, 48, 81, 88, 89, 93, 114, 130
- as.symMatrix, 11, 12
- asyCov, 13, 46, 73, 130
- asyCovOld (asyCov), 13
- BCG, 15
- bdiagMat, 16, 18
- bdiagRep, 17, 17
- Becker09, 18, 81, 91, 133, 134
- Becker83, 22
- Becker92, 23, 81, 91, 131, 140, 142
- Becker94, 25
- Berkey98, 27, 90, 108, 115
- Boer16, 29
- bootuniR1, 30, 132
- bootuniR2, 31, 31, 32, 128, 132
- Bornmann07, 32, 94, 118
- calEffSizes, 34, 122, 124
- checkRAM, 11, 36, 81
- Cheung00, 37
- Cheung09, 39, 131
- coef, 40, 136
- Cooke16, 42
- Cooper03, 44, 94, 118
- Cor2DataFrame, 45, 102, 104
- create.Fmatrix, 11, 47, 50
- create.modMatrix, 48
- create.mxMatrix, 11, 48, 49, 50
- create.mxModel, 50
- create.Tau2, 46, 52, 54, 55, 102
- create.V, 46, 53, 53, 55, 102
- create.vechsR, 46, 53, 54, 54, 102
- Diag, 56
- diag, 57
- Diag<- (Diag), 56
- Digman97, 57, 81, 91, 131, 142
- Gleser94, 60, 122, 124
- Gnamb18, 61
- HedgesOlkin85, 62
- homoStat, 63
- Hox02, 65, 90, 115
- Hunter83, 66, 81, 91, 140, 142
- impliedR, 69
- imxRobustSE, 127, 137
- indirectEffect, 72
- is.pd, 73
- issp05, 74, 76, 131, 142
- issp89, 75, 76, 131, 142
- Jaramillo05, 78
- Kalaian96, 79
- lavaan2RAM, 11, 36, 48, 51, 69, 80, 101, 133, 134, 140

- list2matrix, 82
- Mak09, 83
- match.call, 89, 115, 117
- Mathieu15, 84
- matrix2bdiag, 17, 18, 86, 139
- meta, 13, 41, 64, 88, 109, 115, 128, 138
- meta2semPlot, 91, 108
- meta3 (meta3L), 92
- meta3L, 92, 118
- meta3LFIML (meta3L), 92
- meta3X (meta3L), 92
- metaFIML (meta), 88
- metaSEM (metaSEM-package), 4
- metaSEM-package, 4
- model.syntax, 81, 134
- mvrnorm, 73
- mxAlgebra, 9, 140
- mxCompare, 7
- mxConstraint, 141
- mxMatrix, 10, 11, 49, 50, 140, 141
- mxModel, 51, 89, 94, 101, 114, 116, 130, 134, 141
- mxRun, 14, 51, 89, 90, 94, 101, 102, 114–117, 130, 134, 141
- mxTryHard, 51, 118
- Nam03, 95
- Nohe15, 31, 32, 96, 102, 103, 132
- Nohe15A1 (Nohe15), 96
- Nohe15A2 (Nohe15), 96
- Norton13, 99
- omxGetParameters, 41
- osmasem, 41, 46, 53–55, 100, 102, 103, 128
- osmasemR2, 102
- osmasemSRMR, 103
- par, 106, 107
- pattern.n, 103
- pattern.na, 104
- plot, 105
- points, 106, 107
- print, 109
- print.summary.bootuniR2 (summary), 126
- print.summary.Cor3L (summary), 126
- print.summary.CorPop (summary), 126
- print.summary.meta (summary), 126
- print.summary.meta3LFIML (summary), 126
- print.summary.reml (summary), 126
- print.summary.tssem1FEM (summary), 126
- print.summary.wls (summary), 126
- printCoefmat, 127
- ramModel, 81, 91
- rCor, 31, 110, 128
- rCor3L (rCor), 110
- rCorPop (rCor), 110
- rCorSam (rCor), 110
- read.table, 111
- readData, 111
- readFullMat (readData), 111
- readLowTriMat (readData), 111
- readStackVec (readData), 111
- reml, 41, 90, 109, 113, 118, 128, 138
- reml3, 115
- reml3 (reml3L), 116
- reml3L, 94, 116
- rerun, 118
- rimpliedR (impliedR), 69
- robust, 137
- Roorda11, 119
- Scalco17, 120
- scan, 111
- sem, 31, 34, 134
- semPaths, 108
- semPlotModel, 107
- smdMES, 35, 60, 121, 124
- smdMTS, 35, 60, 122, 123
- Stadler15, 125
- summary, 7, 126
- summary.bootuniR2 (summary), 126
- summary.Cor3L (summary), 126
- summary.CorPop (summary), 126
- summary.meta (summary), 126
- summary.meta3LFIML (summary), 126
- summary.osmasem (summary), 126
- summary.reml (summary), 126
- summary.tssem1FEM (summary), 126
- summary.tssem1REM (summary), 126
- summary.wls (summary), 126
- Tenenbaum02, 128
- tssem1, 41, 109, 128, 129, 138, 142
- tssem1FEM (tssem1), 129
- tssem1REM (tssem1), 129
- tssem2 (wls), 139

tssemParaVar, [32](#), [131](#)

uniR1, [132](#), [133](#), [134](#)

uniR2, [133](#), [133](#)

uniR2lavaan (uniR2), [133](#)

uniR2mx (uniR2), [133](#)

vanderPol17, [135](#)

VarCorr, [136](#)

vcov, [136](#), [137](#)

vec2symMat, [87](#), [138](#)

vech, [64](#), [82](#), [88](#), [114](#), [140](#)

vechs, [82](#), [140](#)

wls, [7](#), [41](#), [48](#), [109](#), [128](#), [131](#), [138](#), [139](#)

wvs94a, [90](#), [108](#), [144](#)

wvs94b, [146](#)